

2" Grinder, Angle

AT215 Order NO.: 701042



Wheel Size (inches)	Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)
2	0.37	15,000	85
Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure
¹ / ₄ " -18 NPT	3/8	<2.86	73
Length (mm)	Weight (kg)	Grinding Disc (optional)	
188	0.82	AT215GWSET	

- Ideal for body shops, automobile, truck repair and confined areas
- Grease fitting in head-enables gears to be greased for longer tool
- Includes 6-2" wheels-tool is ready for use providing convenience
- Moveable guard, up to 50° in either direction-fitting various applications
- Built in speed regulator-allows user to set desired speed
- Rear exhaust with rotating deflector
- Comfort grip housing-insulate from cold and vibration for less user fatigue
- Safety lever throttle-prevents accidental start ups for increased safety

Reciprocating Saw, Micro

AT194A Order NO.:701044



AT190-39A	AT190-41A		AT190-40A
Bi-Metal Blade, 18TPI, 3 3/4" long (qty. 5)	Bi-Metal Blade, 32 3 3/4" long (qty.		
<6.6	87	175	0.45
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
8,250	20	^{1/} 4" -18 NPT	3/8
Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)

- Compact size for easy access in tight quarters
- Low vibration level and lightweight yields reduced hand fatigue
- Performs straight or scroll cuts on metal or plastic
- Adjustable blade guard to control cutting depth
- Flexible, guarded hose extension helps prevent damage to finished surface and aids in maneuverability
- Includes three 3 3/4" bi-metal blades: (1) 18TPI coarse, (1) 24TPI medium and (1) 32 TPI fine blade, blade change wrenches and guard adjustment
- Safety trigger prevent accidental start

Reciprocating Saw

AT192A Packing: 1 Order NO.: 701043



Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	e Recommended Hose Size (inches)
11,000	28	^{1/} 4" -18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
10.1	94	235	0.80
Bi-Metal Blade, 18TPI, 3 3/4" long (qty. 5)	Bi-Metal Blade, 32 3 3/4" long (qty.		i-Metal Blade, 24TPI, 3 3/4" long (qty. 5)
AT190-39A	AT190-41A		AT190-40A

- · Adjustable blade guard to control cutting depth
- Comfort grip housing for greater control
- Performs straight or scroll cuts in metal and plastic
- Safety lever throttle
- Includes three 3 3/4" bi-metal blades: (1) 18TPI coarse, (1) 24TPI medium and (1) 32 TPI fine blade
- Optional blades in 4" lengths are also available



Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)
320	^{1/} 4" -18 NPT	3/8
Sound Level dBa Pressure	Length (mm)	Weight (kg)
48.6	235	1.2
	Speed (L/MIN) 320 Sound Level dBa Pressure	Speed (L/MIN) 320 Air Inlet I fread Size 1/4" -18 NPT Sound Level dBa Pressure Air Inlet I fread Size Length (mm)

- Paddle style trigger for maximum control
- Handle exhaust directed away from operator
- Ball bearing mounted rotary air motor for long service
- Built-in speed regulator provides torque control
- Removable brass filter screens out dirt and debris
- Use to make 3/16" and 5/16" punches in light sheet metal
- Head swivels 360° for maximum versatility





Powered Shears

AT195 Order NO.:701046



Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)
_	113	¹ / ₄ " -18 NPT	3/8
Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)	Weight (kg)
<2.5	99.6	254	1.3

- Trims, outlines and shears
- Replaceable brass filter screen
- Built in speed regulator provide

8" Sander, Dual Action

Packing: 1





Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
8	37	850	⁵ /16 -24
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
142	¹ / ₄ " -18 NPT	3/8	3.7
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad
87	281	2.18	AT408-2

- Comfort handle helps reduce fatigue
- Rear diffused exhaust
- Built in adjustable speed regulator
- Variable speed control
- Removable brass filter screens out debris

Nibbler AT180C Order NO.: 701047 Packing: 1



- Cuts mild steel sheet up to 16 gauge (0.62") (1.55mm) thick
- Anvil is adjustable for forward, backward and left or right cutting, enabling the nibbler to make sheet metal cuts of any configuration • Readily cuts most non-ferrous materials including aluminum, brass, formica, laminates, fiberglass and masonite
- Includes AT180B-10 Standard Punch



AT411A Order NO.: 701049





Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
6	0.37	10,000	^{5/} 16 -18
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
142	¹ / ₄ " -18 NPT	3/8	3.7
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad
79	203	2.14	AT411A-1

• For fine sanding operations and swirl free finishing













AT425R Order NO.: 701053



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
5	0.33	13,000	⁷ / ₁₆ -20
Air Consumption, Free Speed [L/MIN]	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
122	¹ /4" -18 NPT	3/8	<0.8
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad
93	135	1.28	AT425R-24
3" Replacement Pag	3" Replacement Pad (Optional)		ad (Optional)
AT425R-2	AT425R-22		-23

- Use in body shops and other general automotive applications
- Includes 3", 4" and 5" backing discs
- One hand reverse
- Comfort grip handle
- Built-in speed regulator
- 1 year limited warranty on tool
- No warranty on consumables
- CE-DE, ES, FR, IT, GB



In Line Sander, Heavy Duty

Packing: 1

AT475A Order NO.: 701054



Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size
_	1,800	65	¹ /4 "-18 NPT
Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)
3/8	14.9	87	406
Weight (kg)	Standard Pa	ad
3.09		AT475A-2)

- 5/8" stroke
- Minimal vibration



Jitterbug Sander

Packing: 1

AT435A

Order NO.: 701055



Rated Power (kW)	Free Speed RPM	Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size
0.37	8,000	85	¹ / ₄ " -18 NPT
Recommended Hose Size (inches)	Vibration Level (m/s²)	Sound Level dBa Pressure	Length (mm)
3/8	4.5	84	171
Weight	(kg)	Standar	d Pad
2.0	9	AT435	A-48

Features top mounted throttle

3" Surface Prep Tool, Micro

Packing: 1

AT401MCA Order NO.: 701056



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
3	0.19	15,000	1/4 -20
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
59	¹ / ₄ " -18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mm)		/eight (kg)
84	119		0.44

- Small size, light weight and a powerful motor make the AT401MCA
- Surface prep tool ideal for removing paint, rust, gasket material, grinding welds or brake rotors in confined areas
- Accepts 2" and 3" ROLOC® pads
- Pads attach/release with just a 1/4 turn
- Durable single piece polymer composite housing on prep tool stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Oversize trigger for easy operation
- Variable speed trigger
- Bottom handle diffused exhaust
- Built in speed regulator offers easy one hand operation

3" Sander, Dual Action, Micro

AT402MCA Order NO.: 701057

Packing: 1



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
3	0.19	15,000	^{5/} 16 -24
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
59	^{1/} 4 "-18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mn		/eight (kg)
84	133		0.50

- Use the AT402MCA micro sander to deliver fine swirl free results when sanding, feather edging, scuff sanding, sanding primer surfaces, top coating surface preps, scuffing door and rocker panel jams plus other finesse sanding applications
- Durable single piece polymer composite housing on sander stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Oversize trigger for easy operation
- Variable speed trigger
- Bottom handle diffused exhaust
- Built-in speed regulator is easily operated with one hand

3" Polisher, Micro

Packing: 1



AT403MCA

Order NO.: 701058

Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thread (inches)
3	0.19	6,000	⁵ / ₁₆ -24
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibration Level (m/s²)
62	¹ / ₄ " -18 NPT	3/8	<2.5
Sound Level dBa Pressure	Length (mr	n)	Weight (kg)
86	143		0.60


- Small size, light weight and a powerful motor make the AT403MCA micro polisher ideal for polishing motorcycles, bumpers, wheels and
- Durable single piece polymer composite housing on polisher stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool
- Oversize, variable speed trigger for easy operation with a gloved hand
- Bottom handle diffused exhaust
- Built in speed regulator offers easy one hand operation













Surface Prep Kit, Micro, 13 pcs

Packing: 1

AT401MCKA Order NO.: 701059 3" Polisher Kit, Micro, 5 pcs

Packing: 1

AT403MCKA Order NO.: 701061



Includes:

AT401MCA micro surface prep tool
(1) 2" ROLOC® pad
(1) 3" ROLOC® pad

- (5) 2" 40 grit pads
- (5) 3" 80 grit pads in storage case



Includes:

AT403MCA micro polisher

- (1) 3" Hook-It® pad
- (1) 3" wool pad
- (1) 3" foam pad in storage case

3" Sander Kit, Micro, Dual Action, 72 pcs Packing: 1

AT402MCKA Order NO.: 701060

Polisher, Heavy Duty, Vertical

Packing: 1

AT460BP Order NO.: 701062





Includes:

AT402MCA micro sander

(1) 3" Hook-It® pad

(25) 3" 180 grit pads

(25) 3" 200 grit pads (10) 3" 320 grit pads

(10) 3" 800 grit pads in storage case



Pad Size (inches)	Rated Power (kW)	Free Speed RPM	Spindle Thre	ead (inches)
7	0.49	4,500	5/8 .	-11
Air Consumption, Free Speed (L/MIN)	Air Inlet Thread Size	Recommended Hose Size (inches)	Vibratio (m/	
136	¹ / ₄ " -18 NPT	3/8	<2	5
Sound Level dBa Pressure	Length (mm)	Weight (kg)	Standard Pad	Spanner Wrench (opt.)
83	185	2.27	AT450-46H	AT450-50

Removable side handle



Power Tools Cordless Tools

3/8" Impact Wrench

Packing: 1

FTB14438A Order NO.: 702001



Square Drive (inches)	Blows per Minute (BPM)	Maximum Torque (N•m)	Free Speed (RPM)	Duration of eac	h full charge
3/8	2400	189	0-2, 200	More than 300 tig	htening cycles
Motor / Battery Voltage (V)	Length (mm)	Weight (kg)	Battery Pack	Battery Charger	Charge Time (min)
14.4	178	1.9	ETB14419A	ETB14401A	45

- Delivers 140 ft. lbs. max torque in a compact design to provide the user maximum versatility
- Includes two batteries and one charger packed in a blow molded
- Batteries have a 1.9 Ah that provides a long run time
- Easily replaceable carbon brushes to keep your investment running like new
- Slide-on battery provides better contact and safer operation since battery won't drop
- Perfectly balanced compact shape with surrounding soft-grip handle reduces fatigue
- Space included in the molded case to add the ETB14410A LED light

LED Light

Packing: 1

ETB14410A Order NO.: 702003




Length (mm)	Weight (kg)	Battery Pack	Battery Charger	Duration of each full charge
228	0.2	ETB14419A (not included)	ETB14401A (not included)	14 hours continuous

- LED bulb provides long life and low power draw for less job interruptions
- 90 degree pivoting head puts the light ray where you need it
- Faceted reflector provides bright uniform beam
- Perfectly balanced compact shape with surrounding soft-grip handle reduces fatique
- Slide-on battery provides better contact and safer operation since battery won't drop

3/8" Drill, Two Speed

Packing: 1





Chuck Cap (inches)	No Load Speed (RPM)	Maximun (N•		Motor/Battery Voltage (V)	Charge Time (min)
3/8	0-400/0-1400	3	0	14.4	45
Battery Pack	Battery Charger	Length (mm)	Weight (kg)	Duration of each ful	ll charge
ETB14419A (1.9Ah)	ETB14401A	216	1.9	More than 30 drillin	g cycles

- Includes cordless drill, 2 batteries and battery charger
- Keyless chuck provides quick replacement of bits to save time
- Two speed switch and variable speed trigger offers maximum control in both forward and reverse
- Clutch cap provides 20 different settings up to 260 inch pounds torque for precision jobs
- White LED illuminates when trigger is depressed for those dim working conditions
- Slide-on battery provides better contact and safer operation since battery won't drop
- Perfectly balanced compact shape with surrounding soft-grip handle reduces fatique
- Space included in the molded case to add the ETB14410A light

3/8" Drive Cordless Ratchet

Packing: 1

ETB14460A Order NO.: 702007



Square Drive	Maximum	Motor / Battery	Free Speed	Length
(inches)	Torque (N•m)	Voltage (V)	RPM	
3/8	47	14.4	225	378
Weight with Battery Pack (kg)	Battery Pack	Battery Charger	Vinyl Boot (optional)	
6.6	ETB14419A	ETB14401A	YA889A (Blac	:k)

- Cord free eliminates dragging dirty air hoses in and across the service vehicle
- High Speed (190 RPM) increases productivity
- Delivers 35 ft.lbs. (47 N·m) of torque
- 1.9 Ah Ni-cad battery provides user with ample run time between
- Aluminium housing provides durability under manual stress loads













Power Tools Cordless Tools / Impact Sockets

3/8" Drill

Packing: 1

ETB14430A Order NO.: 701064



Drilling Capability (mm)	No Loa	d Speed (RPM)	Maximum Torque (N•m)	Voltage (V)
13		0-1000	23	9.6
Charge Time (min)	Weight (kg)	Length (mm)	Duration of each full charge	Package
45	1.4	27	More than 30 drilling cycles	2Battery 1Charger 1Key

 This is a professional cordless drill suitable for general purpose drilling for all type of woods and metal, which can be used in automotive repairs, construction and home improvements works

Battery, 14.4V

Packing: 1

ETB14419A

Order NO.: 702005





- 14.4V battery pack for Blue-Point ETB series cordless tools
- Slide-on battery provides better contact and safer operation since battery won't drop
- 45 minutes charging time using ETB14401A charger

Charger, 14.4V/220V

Packing: 1

ETB14401A Order NO.: 702006



- 14.4V battery charger for batteries used on Blue-Point ETB series cordless tools
- 45 minutes charging time on ETB14419A battery

3/8" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)	i	Order No.
BLPSMIM387	7	6	703001
BLPSMIM388	8	6	703002
BLPSMIM389	9	6	703003
BLPSMIM3810	10	6	703004
BLPSMIM3811	11	6	703005
BLPSMIM3812	12	6	703006
BLPSMIM3813	13	6	703007
BLPSMIM3814	14	6	703008
BLPSMIM3815	15	6	703009
BLPSMIM3816	16	6	703010
BLPSMIM3817	17	6	703011
BLPSMIM3818	18	6	703012
BLPSMIM3819	19	6	703013

3/8" Drive, Deep, 6pt., mm



Stock No.	Size (mm)	•	Order No.
BLPLSMIM387	7	6	703014
BLPLSMIM388	8	6	703015
BLPLSMIM389	9	6	703016
BLPLSMIM3810	10	6	703017
BLPLSMIM3811	11	6	703018
BLPLSMIM3812	12	6	703019
BLPLSMIM3813	13	6	703020
BLPLSMIM3814	14	6	703021
BLPLSMIM3815	15	6	703022
BLPLSMIM3816	16	6	703023
BLPLSMIM3817	17	6	703024
BLPLSMIM3818	18	6	703025
BLPLSMIM3819	19	6	703026

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



3/8" Drive, Shallow, 6pt., inches



Stock No.	Size (inches)	V	Order No.
BLPSIM3814	1/4	6	703027
BLPSIM38516	5/16	6	703028
BLPSIM3838	3/8	6	703029
BLPSIM38716	7/16	6	703030
BLPSIM3812	1/2	6	703031
BLPSIM38916	9/16	6	703032
BLPSIM3858	5/8	6	703033
BLPSIM381116	11/16	6	703034
BLPSIM3834	3/4	6	703035

3/8" Drive, Deep, 6pt., inches



Stock No.	Size (inches)	•	Order No.
BLPLSIM3814	1/4	6	703036
BLPLSIM38516	⁵ / ₁₆	6	703037
BLPLSIM3838	3/8	6	703038
BLPLSIM38716	⁷ / ₁₆	6	703039
BLPLSIM3812	1/2	6	703040
BLPLSIM38916	⁹ / ₁₆	6	703041
BLPLSIM3858	5/8	6	703042
BLPLSIM381116	11/16	6	703043
BLPLSIM3834	3/4	6	703044

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

3/8" Drive, Extra Long, 6pt., inches



Stock No.	Size (inches)		Order No.
BLPSMS8	8	6	704056
BLPSMS10	10	6	704057
BLPSMS12	12	6	704058

- Extra length at 100 mm to reach two-wheelers transmission box screws
- Single piece construction
- For use on impact wrench without the need for extra extension

3/8" Drive Adaptor

Packing: 6





Stock No.	Size (inches)
BLPAIM1238	¹ / ₂ male X ³ / ₈ female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/8" Drive Universal Joints Packing: 6

BLPJIM38

Order NO.: 703046



Stock No.	Size (inches)
BLPJIM38	³ / ₈ male X ³ / ₈ female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/8" Drive Extension



Stock No.	Size (inches)	•	Order No.
BLPEXIM383	3	6	703047
BLPEXIM386	6	6	703048



- Specially heat treated for impact use to provide long life, safety, and
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1/4" Drive, Impact Adaptor

Packing: 6

BLPAIM3814 Order NO.: 703045



Stock No.	Size (inches)
BLPAIM3814	3/8 male X 1/4 female

- Specially heat treated for impact use to provide long life, safety, and
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove











1/2" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)	©	Order No.
BLPSMIM1210	10	6	703050
BLPSMIM1211	11	6	703051
BLPSMIM1212	12	6	703052
BLPSMIM1213	13	6	703053
BLPSMIM1214	14	6	703054
BLPSMIM1215	15	6	703055
BLPSMIM1216	16	6	703056
BLPSMIM1217	17	6	703057
BLPSMIM1218	18	6	703058
BLPSMIM1219	19	6	703059
BLPSMIM1221	21	6	703060
BLPSMIM1222	22	6	703061
BLPSMIM1223	23	6	703062
BLPSMIM1224	24	6	703063
BLPSMIM1227	27	6	703064
BLPSMIM1229	29	6	703065
BLPSMIM1230	30	6	703066
BLPSMIM1232	32	6	703067

1/2"Drive, Deep, 6pt., mm



Stock No.	Size (mm)	i	Order No.
BLPLSMIM1210	10	6	703068
BLPLSMIM1211	11	6	703069
BLPLSMIM1212	12	6	703070
BLPLSMIM1213	13	6	703071
BLPLSMIM1214	14	6	703072
BLPLSMIM1215	15	6	703073
BLPLSMIM1216	16	6	703074
BLPLSMIM1217	17	6	703075
BLPLSMIM1218	18	6	703076
BLPLSMIM1219	19	6	703077
BLPLSMIM1221	21	6	703078
BLPLSMIM1222	22	6	703079
BLPLSMIM1224	24	6	703080
BLPLSMIM1226	26	6	703081
BLPLSMIM1227	27	6	703082
BLPLSMIM1229	29	6	703083
BLPLSMIM1230	30	6	703084
BLPLSMIM1232	32	6	703085

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

1/2" Drive, Shallow, 6pt., inches



Stock No.	Size (inches)	p	Order No.
BLPSIM1238	3/8	6	703086
BLPSIM12716	7/16	6	703087
BLPSIM1212	1/2	6	703088
BLPSIM12916	9/16	6	703089
BLPSIM1258	5/8	6	703090
BLPSIM121116	11/16	6	703091
BLPSIM1234	3/4	6	703092
BLPSIM121316	¹³ / ₁₆	6	703093
BLPSIM1278	7/8	6	703094
BLPSIM121516	¹⁵ / ₁₆	6	703095
BLPSIM121	1	6	703096
BLPSIMB121116	1 ¹ /16	6	703097
BLPSIMB12118	1 ^{1/8}	6	703098
BLPSIMB12114	1 1/4	6	703099
BLPSIMB121516	1 ⁵ / ₁₆	6	703100
BLPSIMB121716	1 ^{7/} 16	6	703101

1/2" Drive, Deep, 6pt., inches



Stock No.	Size (inches)	a	Order No.
BLPLSIM1238	3/8	6	703102
BLPLSIM12716	7/ ₁₆	6	703103
BLPLSIM1212	1/2	6	703104
BLPLSIM12916	9/16	6	703105
BLPLSIM1258	5/8	6	703106
BLPLSIM121116	11/16	6	703107
BLPLSIM1234	3/4	6	703108
BLPLSIM121316	¹³ / ₁₆	6	703109
BLPLSIM1278	7/8	6	703110
BLPLSIM121516	15/16	6	703111
BLPLSIM121	1	6	703112
BLPLSIMB12116	1 ¹ / ₁₆	6	703113
BLPLSIMB12118	1 ^{1/} 8	6	703114
BLPLSIMB121316	1 ³ / ₁₆	6	703115
BLPLSIMB12114	1 ^{1/4}	6	703116

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove





1/2" Impact Adaptor

Packing: 6

BLPAIM3812 Order NO.: 703121

1/2" Drive Universal Joints

Packing: 6

BLPJIM12 Order NO.: 703123



Stock No.	Size (inches)
BLPAIM3812	³ / ₈ male X ¹ / ₂ female

- Specially heat treated for impact use to provide long life, safety, and
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



Stock No.	Size (inches)
BLPJIM12	¹ / ₂ male X ¹ / ₂ female

- Specially heat treated for impact use to provide long life, safety, and
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1/2" Impact Adaptor

Packing: 6





Stock No.	Size (inches)
BLPAIM3412	³ / ₄ male X ¹ / ₂ female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1/2" Drive Extension



Stock No.	Size (inches)	V	Order No.
BLPEXIM123	3	6	703117
BLPEXIM125	5	6	703118
BLPEXIM126	6	6	703119
BLPEXIM1210	10	6	703120

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove















3/4" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)	•	Order No.
BLPSMIM3417	17	6	703124
BLPSMIM3418	18	6	703125
BLPSMIM3419	19	6	703126
BLPSMIM3420	20	6	703127
BLPSMIM3421	21	6	703128
BLPSMIM3422	22	6	703129
BLPSMIM3423	23	6	703130
BLPSMIM3424	24	6	703131
BLPSMIM3425	25	6	703132
BLPSMIM3426	26	6	703133
BLPSMIM3427	27	6	703134
BLPSMIM3428	28	6	703135
BLPSMIM3429	29	6	703136
BLPSMIM3430	30	6	703137
BLPSMIM3431	31	6	703138
BLPSMIM3432	32	6	703139
BLPSMIM3433	33	6	703140
BLPSMIM3434	34	6	703141
BLPSMIM3435	35	6	703142
BLPSMIM3436	36	6	703143
BLPSMIM3437	37	6	703144
BLPSMIM3438	38	6	703145
BLPSMIM3439	39	6	703146
BLPSMIM3440	40	6	703147
BLPSMIM3441	41	6	703148
BLPSMIM3442	42	6	703149
BLPSMIM3443	43	6	703150
BLPSMIM3444	44	6	703151
BLPSMIM3445	45	6	703152
BLPSMIM3446	46	6	703153
BLPSMIM3447	47	6	703154
BLPSMIM3448	48	6	703155
BLPSMIM3449	49	6	703156
BLPSMIM3450	50	6	703157
BLPSMIM3452	52	6	703158
BLPSMIM3454	54	6	703159
BLPSMIM3455	55	6	703160
BLPSMIM3456	56	6	703161
BLPSMIM3457	57	6	703162
BLPSMIM3458	58	6	703163
BLPSMIM3459	59	6	703164
BLPSMIM3460	60	6	703165
BLPSMIM3463	63	6	703166
BLPSMIM3465	65	6	703167

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

3/4" Drive, Deep, 6pt., mm



Stock No.	Size (mm)	\	Order No.
BLPLSMIM3417	17	6	703169
BLPLSMIM3418	18	6	703170
BLPLSMIM3419	19	6	703171
BLPLSMIM3420	20	6	703172
BLPLSMIM3421	21	6	703173
BLPLSMIM3422	22	6	703174
BLPLSMIM3423	23	6	703175
BLPLSMIM3424	24	6	703176
BLPLSMIM3425	25	6	703177
BLPLSMIM3426	26	6	703178
BLPLSMIM3427	27	6	703179
BLPLSMIM3428	28	6	703180
BLPLSMIM3429	29	6	703181
BLPLSMIM3430	30	6	703182
BLPLSMIM3431	31	6	703183
BLPLSMIM3432	32	6	703184
BLPLSMIM3433	33	6	703185
BLPLSMIM3434	34	6	703186
BLPLSMIM3435	35	6	703187
BLPLSMIM3436	36	6	703188
BLPLSMIM3437	37	6	703189
BLPLSMIM3438	38	6	703190
BLPLSMIM3440	40	6	703191
BLPLSMIM3441	41	6	703192
BLPLSMIM3442	42	6	703193
BLPLSMIM3443	43	6	703194
BLPLSMIM3444	44	6	703195
BLPLSMIM3445	45	6	703196
BLPLSMIM3446	46	6	703197
BLPLSMIM3447	47	6	703198
BLPLSMIM3448	48	6	703199
BLPLSMIM3449	49	6	703200
BLPLSMIM3450	50	6	703201
BLPLSMIM3455	55	6	703202

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove





3/4" Drive, Shallow, 6pt., inches



Stock No.	Size (inches)	•	Order No.
BLPSIM341116	11/16	6	703203
BLPSIM3434	3/4	6	703204
BLPSIM341316	13/16	6	703205
BLPSIM3478	7/8	6	703206
BLPSIM341516	15/16	6	703207
BLPSIM341	1	6	703208
BLPSIMB341116	1 1/16	6	703209
BLPSIMB34118	1 ^{1/8}	6	703210
BLPSIMB341316	1 ³ / ₁₆	6	703211
BLPSIMB34114	1 ¹ / ₄	6	703212
BLPSIMB341516	1 ^{5/} 16	6	703213
BLPSIMB34138	1 ^{3/8}	6	703214
BLPSIMB341716	1 7/16	6	703215
BLPSIMB34112	1 ¹ / ₂	6	703216
BLPSIMB341916	1 ^{9/} 16	6	703217
BLPSIMB34158	1 ^{5/8}	6	703218
BLPSIMB3411116	1 11/16	6	703219
BLPSIMB34134	1 ³ / ₄	6	703220
BLPSIMB3411316	1 13/16	6	703221
BLPSIMB34178	1 ⁷ /8	6	703222
BLPSIMB3411516	1 15/16	6	703223
BLPSIMB342	2	6	703224

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

3/4" Drive Adaptor

Packing: 6

BLPAIM1234 Order NO.: 703232



Stock No.	Size (inches)
BLPAIM1234	¹ / ₂ male X ³ / ₄ female

- Specially heat treated for impact use to provide long life, safety, and
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/4" Drive Adaptor

Packing: 6

BI PAIM134 Order NO.: 703316



Stock No.	Size (inches)
BLPAIM134	1 male X ³ / ₄ female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/4" Drive Universal Joint

Packing: 6

BLPJIM34 Order NO.: 703233



Stock No.	Size (inches)
BLPJIM34	3/4 male X 3/4 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

3/4" Drive Extension



Stock No.	Size (inches)	V	Order No.
BLPEXIM343	3 1/2	6	703225
BLPEXIM344	4	6	703226
BLPEXIM346	6	6	703227
BLPEXIM347	7	6	703228
BLPEXIM348	8	6	703229
BLPEXIM3410	10	6	703230
BLPEXIM3413	13	6	703231

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove











1" Drive, Shallow, 6pt., mm



Stock No.	Size (mm)		Order No.	Stock No.	Size (mm)	I	Order No.
BLPSMIM117	17	6	703234	BLPSMIM142	42	6	703259
BLPSMIM118	18	6	703235	BLPSMIM143	43	6	703260
BLPSMIM119	19	6	703236	BLPSMIM144	44	6	703261
BLPSMIM120	20	6	703237	BLPSMIM145	45	6	703262
BLPSMIM121	21	6	703238	BLPSMIM146	46	6	703263
BLPSMIM122	22	6	703239	BLPSMIM147	47	6	703264
BLPSMIM123	23	6	703240	BLPSMIM148	48	6	703265
BLPSMIM124	24	6	703241	BLPSMIM149	49	6	703266
BLPSMIM125	25	6	703242	BLPSMIM150	50	6	703267
BLPSMIM126	26	6	703243	BLPSMIM151	51	6	703268
BLPSMIM127	27	6	703244	BLPSMIM152	52	6	703269
BLPSMIM128	28	6	703245	BLPSMIM153	53	6	703270
BLPSMIM129	29	6	703246	BLPSMIM154	54	6	703271
BLPSMIM130	30	6	703247	BLPSMIM155	55	6	703272
BLPSMIM131	31	6	703248	BLPSMIM156	56	6	703273
BLPSMIM132	32	6	703249	BLPSMIM157	57	6	703274
BLPSMIM133	33	6	703250	BLPSMIM158	58	6	703275
BLPSMIM134	34	6	703251	BLPSMIM159	59	6	703276
BLPSMIM135	35	6	703252	BLPSMIM160	60	6	703277
BLPSMIM136	36	6	703253	BLPSMIM163	63	6	703278
BLPSMIM137	37	6	703254	BLPSMIM165	65	6	703279
BLPSMIM138	38	6	703255	BLPSMIM167	67	6	703280
BLPSMIM139	39	6	703256	BLPSMIM168	68	6	703281
BLPSMIM140	40	6	703257	BLPSMIM169	69	6	703282
BLPSMIM141	41	6	703258				



- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove

1" Drive, Deep, 6pt., mm



Stock No.	Size (mm)	i i i i i i i i i i i i i i i i i i i	Order No.
BLPLSMIM117	17	6	703283
BLPLSMIM118	18	6	703284
BLPLSMIM119	19	6	703285
BLPLSMIM120	20	6	703286
BLPLSMIM121	21	6	703287
BLPLSMIM122	22	6	703288
BLPLSMIM123	23	6	703289
BLPLSMIM124	24	6	703290
BLPLSMIM125	25	6	703291
BLPLSMIM126	26	6	703292
BLPLSMIM127	27	6	703293
BLPLSMIM128	28	6	703294
BLPLSMIM129	29	6	703295
BLPLSMIM130	30	6	703296
BLPLSMIM131	31	6	703297
BLPLSMIM132	32	6	703298
BLPLSMIM133	33	6	703298
BLPLSMIM134	34	6	703299
BLPLSMIM135	35	6	703301
BLPLSMIM136	36	6	703302
BLPLSMIM137	37	6	703303
BLPLSMIM138	38	6	703304
BLPLSMIM140	40	6	703305
BLPLSMIM141	41	6	703306
BLPLSMIM142	42	6	703307
BLPLSMIM143	43	6	703308
BLPLSMIM146	46	6	703309
BLPLSMIM149	49	6	703310
BLPLSMIM150	50	6	703311
BLPLSMIM155	55	6	703312

- Designed for maximum engagement on 6 point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



1" Drive Adaptor

Packing: 6

BI PAIM341 Order NO.: 703317

1" Drive, Universal Joint

Packing: 6

BI PJIM1 Order NO.: 703315



Stock No.	Size (inches)
BLPAIM341	^{3/4} male X 1 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1" Drive Adaptor Packing: 6

BLPAIM1121 Order NO.: 703318



	1		1
	10	*	9
		-	
	1		13

Stock No.	Size (inches)
BLPAIM1121	1 ^{1/2} male X 1 female

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

1" Drive Extension



Stock No.	Size (inches)	I	Order No.
BLPEXIM17	7	6	703313
BI PEXIM113	13	6	703314

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove











Regulator, Combination Air Line

Packing: 1

AHRB200 Order NO.: 704001



Inlet/Outlet Port Size	1/2" NPT (F)
Adjustable Pressure Range	5-120 PSIG (.5-8.5 kgf/cm²)
Maximum Service Pressure	140 PSIG (9.9 kgf/cm2)
Oil Capacity	80 ml
Operating Temperature Range Pressure	41-140° F (5-60° C)

Grinding Wheel

Packing: 1



- Use for rough grinding applications
 Use on 4 1/2" grinders with 5/8" x 11 thread arbor
- Re-order in multi-packs

Step Drill Set, 3 pcs

Packing: 1

YAS203A Order NO.: 704005



Stock No.	Hole Sizes Per Bit	Increments (inches)	Length (inches)	Shank Size (inches)	Size Range (inches)	Order No.
YA261A	13	1/32	3 1/4	1/4	1/8 - 1/2	704002
YA262A	6	1/16	3 ³ /8	1/4	³ / ₁₆ - ¹ / ₂	704003
YA263A	9	1/16	2 ^{5/8}	3/8	1/4 - 3/4	704004

Includes YA261A, YA262A and YA263A (3 pcs)

Grinding Wheels Set

Packing: 1

ETA125A Order NO.: 704006



- Use with ET1350/ET1360
- Maximum rating of 12,000 RPM

Cut Off Wheel

Packing: 1

Order NO.: 704021

AT415T27MP

Order NO.: 704022

AT415CWMP



- Use for metal notching and bolt cutting
- Use on 4 1/2" grinders with 5/8" x 11 thread arbor
- Re-order in multi-packs

Flap Discs



Stock No.	Diameter (inches)	Туре	Grit	Quantity to Pack	I	Order No.
AC2Z40T27MP	2	27	40	10	1	704013
AC2Z60T27MP	2	27	60	10	1	704014
AC2Z80T27MP	2	27	80	10	1	704015
AC4Z60T27MP	4	27	60	10	1	704019





Flap Wheels



Stock No.	Diameter (inches)	Туре	Grit	Quantity to Pack	Ü	Order No.
AC3160FWMP	3	_	60	10	1	704017
AC3180FWMP	3	_	80	10	1	704018
AC31120FWMP	3	_	120	10	1	704016

- Applications include cleaning, edge blending and smoothing metal, plastic or wood
- 3" aluminum oxide flap wheel is designed to provide fast cutting action
- 1/4" stem on solid hub permits a higher RPM rating and increased productivity
- Use on electric and pneumatic drills

Wire Wheel

Packing: 1





- 3" crimped wire wheel is a great general purpose cleaner
- Features individual crimped filaments that support each other while
- General applications include deburring, weld cleaning and rust and paint removal
- Use on electric and pneumatic drills
- .0118 CWS-1/4

Wire Brush



Stock No.	Brush Dia. (inches)	Shank Size Arbor Size (inches)	Wire Diameter (inches)	Maximum Rated RPM	•	Order No.
AC17D	1	1/4	.006	20,000	1	704011
AC243	3	⁵ /8 - 11	.014	14,000	1	704012

- Features individual crimped filaments that support each other while being flexible
- Use for medium duty general purpose cleaning

Wire Brush



Stock No.	Brush Dia. (inches)	Maximum Safe Free Speed (RPM)	Shank Size Arbor Size	Wire Diameter (inches)	P	Order No.
AC420A	4	20,000	⁵ /8" X 11	0.020	1	704007
AC421A	4	20,000	M10 x1.25	0.020	1	704008

- Knotted wire wheel
- Use for heavy duty cleaning
- Ideal for pre-welding prep and weld cleaning

End Brush



Stock No.	Brush Dia. (inches)	Shank Size Arbor Size (inches)	Wire Diameter (inches)	Maximum Rated RPM	•	Order No.
AC10302	1/2	1/4	.014	25,000	1	704009
AC10306	3/4	1/4	.014	22,000	1	704010

- Features individual crimped filaments that support each other while being flexible
- Ideal for cleaning right angles



Wool Buffing Pad

Packing: 1



POLISHW8A Order NO.: 704023

- Ideal for cutting, buffing, and removal of scratches and paint imperfections
- 1 1/2" wool pile last longer that standard wool pads
- Washable for easy clean up
- Use for base and clear coats, acrylic, enamel, lacquer, urethane, fiberglass, plastics and other applications
- Can be used with AT450CP, AT460BP and ETB1580B Polishers











Blow Gun

Packing: 1

JT13B

Order NO.: 704024



- Tapered, rubber tip for a leak proof connection between gun and fluid line
- Won't mar surfaces
- Vinyl coated control lever
- Hanging hook for storage
- 4 1/2" long

Blow Gun

Packing: 1

YA1050B Order NO.: 704025



- Pistol grip style with front full size trigger
- Infinitely variable flow
- 10 1/4" long



Air Hoses

Packing: 1

AIRHOSE35 Order NO.: 704026



- Extremely lightweight for easy maneuverability
- Reinforced construction eliminates layer separation resulting from expansion and contraction during pulsating operations
- More abrasion resistant than PVC and rubber hoses
- Easy to wrap and store even in subzero weather
- UV stabilized for longer outdoor life
- Strain relief features an tight bending radius to virtually eliminate hose kinking
- Reusable fittings and strain reliefs for longer life

Cobalt Drill Bit Set, 21 pcs

Packing: 1

DBBPC21 Order NO.: 704053



 DBBPC1/16 thru DBBPC3/8 (21 pcs) (1/16" to 3/8") in metal drill bit index

HSS Drill Bit Set, 21 pcs

Packing: 1

DBBP21

Order NO.: 704054



 DBBP1/16 thru DBBP3/8 (21 pcs) (1/16" to 3/8") in metal drill bit index

Titanium Coated Drill Bit Set, 13 pcs

Packing: 1

DBBPT13

Order NO.: 704055



 DBBPT1/16 thru DBBPT1/4 (13 pcs) (1/16" to 1/4") in metal drill bit index

Air Line Couplers and Adaptors

Packing: 1

AHC21PD Order NO.: 704033



Stock No.	Body Size (inches)	Style	Thread Size
AHC21PD	1/4	Rigid Mounting	¹ /4" -18 NPT



Air Line Couplers and Adaptors



Stock No.	Body Size (inches)	Style	Thread Size	Quick Coupler Male	Ü	Order No.
AHC21PMD	1/4	Industrial Interchange	¹ /4" -18 NPT	AHC21PMC	1	704036
AHC21D	1/4	Industrial Interchange	¹ / ₄ " -18 NPT	AHC21PMC	1	704052
AHC21MD	1/4	Industrial Interchange	^{1/} 4" -18 NPT	AHC21PMC	1	704041
AHC21FD	1/4	Industrial Interchange	¹ / ₄ " -18 NPT	AHC21PMC	1	704032



Stock No.	Body Size (inches)	Style	Thread Size	•	Order No.
AHC22E	3/8	Industrial Interchange	¹ /4" -18 NPT	1	704028
AHC22MD	3/8	Industrial Interchange	¹ /4" -18 NPT	1	704030
AHC22FD	3/8	Industrial Interchange	¹ /4" -18 NPT	1	704046



Stock No.	Body Size (inches)	Style	Thread Size	Quick Coupler Male	•	Order No.
AHC23PMD	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704039
AHC23D	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704037
AHC23MD	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704051
AHC23FD	1/4	ARO	¹ /4" -18 NPT	AHC23PMC	1	704047



Stock No.	Body Size (inches)	Style	Thread Size	•	Order No.
AHC24D	1/4	True-Flate	¹ /4" -18 NPT	1	704048
AHC24MD	1/4	True-Flate	¹ /4"-18 NPT	1	704049
AHC24FD	1/4	True-Flate	1/4" -18 NPT	1	704050

Air Line Couplers and Adaptors



Stock No.	Body Size (inches)	Style	Thread Size	•	Order No.
AHC25D	3/8	True-Flate	¹ /4" -18 NPT	1	704031
AHC25MD	3/8	True-Flate	¹ /4" -18 NPT	1	704043
AHC25FC	3/8	True-Flate	¹ /4" -18 NPT	1	704040



Stock No.	Body Size (inches)	Style	Thread Size	•	Order No.
AHC26D	1/4	Lincoln	¹ /4" -18 NPT	1	704027
AHC26MD	1/4	Lincoln	¹ /4" -18 NPT	1	704029
AHC26FD	1/4	Lincoln	¹ /4" -18 NPT	1	704038



Stock No.	Body Size (inches)	Style	Thread Size	•	Order No.
AHC27D	1/2	Industrial Interchange	¹ /2 " -14 NPT	1	704045
AHC27FD	1/2	Industrial Interchange	¹ / ₂ " -14 NPT	1	704042



Stock No.	Body Size (inches)	Style	Thread Size	•	Order No.
AHC28D	3/8	Industrial Interchange	^{3/} 8" -18 NPT	1	704035
AHC28MD	3/8	Industrial Interchange	³ / ₈ "-18 NPT	1	704044
AHC28FD	3/8	Industrial Interchange	³ /8" -18 NPT	1	704034















Striking & Cutting

When it comes to striking tools, Blue-Point's lineage stretches back to 1940 when the company first produced punches and chisels that managed to penetrate and cut through quarter-inch steel. That was a remarkable achievement then.

The range today includes other selection of tools for various striking and cutting applications, bearing the same trademark hardness and toughness. Our wide range of superior hammers and cutting tools set us apart from the competition.





SHOPE RESERVE

Hammers

Punches & Chisels **Cutting Tools**

108

110

111



Striking & Cutting Hammers

Ball Peen - Wood Handle



Ball Peen, Wood Handle

Ball Peen, Fiberglass Handle


Cross Peen, Hickory Handle



801018

801019


801020



32

40

48






Stock No.	Weight (oz.)	Head Length (inches)	Overall Length (inches)	Replacement Handle		Order No.
BH141A	32	4 1/2	15	BPH20C	1	801006
BH142A	40	5	15	BPH40C	1	801007



Striking & Cutting Hammers

Soft Face











BF623

Order NO.: 801009



Stock No.	Weight (oz.)	Length (inches)
BH232A	32	13

- Combination steel and soft face dead blow
- One-piece urethane construction
- The 13" long fiberglass handle has a plastic, shock-absorbing grip
- Tip diameter is 1 5/8"
- Includes two replaceable tips: soft (BH232-2) and hard (BH232-3)
- Optional nylon tip (BH232-4)

- Solid rubber head
- 11" Hardwood handle

13 ^{1/4}

Rubber Head Mallet

Packing: 1

• Ideal for replacing hubcaps, bodywork, etc

 $3^{3/4} \times 2^{1/4}$

 Use on all types of surfaces and assemblies including metal, glass, plastic and wood

 $1^{7/8} \times 2^{1/8}$

- Conforms to irregular surfaces
- Designed for maximum surface contact
- Low rebound

Soft Blow

Packing: 1

BF620C

Order NO.: 801010

- Dissipates hand jarring shock
- Resists most chemicals
- Wood handle
- Reduces denting and marring







Striking & Cutting Hammers / Punches and Chisels

Brass Hammer



Stock No.	Weight (lbs.)	Length (inches)	•	Order No.
HBR15	1 ^{1/2}	12	1	801011
HBR25	2 1/2	12	1	801012

- Non-sparking/non-marring surface for many applications
- Flat surface for even distribution of blow
- Fiberglass handle for strength
- Comfortable, non-slip handle grip

Fiberglass Hammer



Stock No.	Description	Weight, Ibs	Striking Face Dia. (inches)	Handle Length (inches)	Overall Length (inches)	Replacement Handle	•	Order No.
BC4SG	Cross Peen	4	1 ^{1/2}	12	14	BD4SG-1	1	801021
BD4SG	Engineer	4	1 ¹ /2	12	14	BD4SG-1	1	801022
HD4SG	Hand Drilling	4	1 ^{1/} 2	8 3/4	10 ^{3/} 4	HD4SG-1	1	801023

- Fiberglass handle dampens vibration and provides extra strength and safety
- Brass head absorbs blow and reduces rebound Handle is epoxy-welded to hammer head and will withstand 8,000 lbs. of separation force
 - Handle is resistant to dry rot, warp and splintering
 - Comfortable, non-slip handle grip
 - Materials will resist most shop chemicals

Punch Set Packing: 1

DPFT528B Order NO.: 802001 **Automatic Center Punch**

Packing: 1

YA879A Order NO.: 802002

Automatic Center Punch

Packing: 1

YA900 Order NO.: 802003



- For transferring hole patterns
- Set includes punches from 3/32" to 1/2" in 1/64" increments plus 17/32"
- Each punch is marked with its size and manufactured from tempered steel to promote long tool life
- A metal index provides convenient storage
- Punches are 4 7/8" in length



- Single handed operation
- Design eliminates need for striking with hammer
- Adjustable spring tension cap
- Hardened steel point is replaceable
- 1/2" diameter
- 5" long



- Strikes blow when pressure is applied-no hammer needed
- · Cap adjusts force of blow
- 7/16" diameter
- 4 3/4" long





Scraper Set

PKB500A Packing: 1 Order NO.: 802004



Stock No.	Handle Length (inches)	Blade Length (inches)	Blade Width (inches)	Blade Style	Edge		Order No.
PKB50A	4 ⁷ /8	3 1/2	2	Stiff	Straight	1	802005
PKB52A	4 ⁷ /8	3 ¹⁹ /32	1 ¹ /4	Stiff	Straight	1	802006
PKB53A	4 ⁷ /8	3 19/32	1 ¹ /4	Stiff	Single Bevel	1	802007

- Set includes PKB50A, PKB52A and PKB53A Putty Knives Scrapers
- Spring tempered, solid brass blades are non-marring, non-sparking, non-magnetic and non-corrosive
- Soft molded rubber handles maximize hand grip, are easy to clean and are resistant to most solvents
- Broad hilt design helps protect against hand slippling when scraping
- Stiff blade style

Scraper set

Packing: 1

USS103 Order NO.: 802012



Stock No.	Blade Style	Blade Length (inches)	Length (inches)	P	Order No.
US710	Spoon	3 ¹ /2	8	1	802013
US711	Chisel Tip	2 ¹ /2	7 ¹ /8	1	802014
US712	Ovster	2 ¹ /8	6 ³ /4	1	802015

- Set includes US710, US711 and US712 Knife Blade Scrapers
- Remove gaskets, sealers and other caked on materials
- Blade edge designed to work effectively in both push and pull directions
- Stainless steel blades for durability
- Polished blades clean up easily
- Comfortable composite handles feature a contour thumb stop for maximum control and a wide hilt for control

Scraper Set

Packing: 1

PK500A Order NO.: 802008



Stock No.	Blade Length (inches)	Blade Width (inches)	Blade Style	Edge	I	Order No.
PK50A	3 ¹ /2	2	Flexible	Straight	1	802009
PK52A	5 ¹⁹ /32	1 ¹ /4	Flexible	Straight	1	802010
PK53A	2 ¹⁹ /32	1 ¹ /4	Stiff Chisel	Single Bevel	1	802011

- Set includes PK50A, PK52A and PK53A Putty Knives Scrapers
- Features full length steel blades for strength and durability
- Soft molded rubber handles maximize hand grip, are easy to clean and are resistant to most solvents
- Broad hilt design helps protect against hand slipping when scraping

Walnut Handle Scraper



Stock No.	Blade Length, (inches)	Blade Width (inches)	Blade Style	Edge	Length (inches)	•	Order No.
PKWLR53A	5 ¹ /2	1 ¹ /4	Straight	Chisel	9 ¹ /2	1	802018
PKWSS53A	2 ³ /4	1 ¹ /4	Straight	Chisel	6 ³ /4	1	802019

- Quality crafted for hard scraping applications
- Walnut wood handle for comfort
- Full length heavy duty blades for strength
- Large steel cap for striking capability
- Remove gaskets, sealants and body weld breakaway



- Mirror finished hardened steel blade extends through hardwood handle, solidly riveted for durability
- Redwood handle has metal bolster where handle meets blade







Aviation Snips (Discontinued)



Stock No.	Description	Length (inches)	I	Order No.
DAR9A	Green handled; Right hand cut	9 ¹ / ₂	1	803010
DAL9A	Red handled; Left hand cut	9 1/2	1	803011

- Offset blades allow cut material to flow beneath your hand without curling
- Maneuverable for angle cutting or pattern configurations
- Cuts up to 18 ga. mild steel
- 1 1/8" cutting edge

Tin Snips



Stock No.	Description	Blades Length (inches)	Length (inches)	Ü	Order No.
CD7A	Duckbill Snips	1 ^{1/2}	7	1	803005
CD10A	Duckbill Snips	2 1/4	10	1	803006
CD12A	Combination Snips	3	12	1	803007
CD16A	Bulldog Snips	2 1/2	16	1	803008

• Cut straight, circular, or irregular patterns; right or left cuts

Metal Cutting Shears (Discontinued)

Packing: 1

DAS30

Order NO.: 803004



Stock No.	Description	Length (inches)	P	Order No.
DAL10B	Red handled; Left hand cut	10 ^{1/} 4	1	803001
DAR10B	Green handled; Right hand cut	10 ¹ / ₄	1	803002
DAS10B	Yellow handled; Straight cut	10 ^{1/4}	1	803003

- Serrated cutting blades
- Narrow bodies allow metal to pass over shears
- Oil and grease resistant grips
- DAS30 Set includes DAL10B, DAR10B and DAS10B

Shears, Angled, Heavy Duty

Packing: 1

SNP2A Order NO.: 803009



- For leather, cloth, plastic, rubber sheet, rubber hose, cardboard, gasket material, rope and many other materials
- Stainless steel blades and fasteners ensure durability
- Precision ground and heat treated for a long lasting edge
- Ergonomic handles can be used right or left handed
- Top of blade is notched for hard wire and twine
- Locking switch ensures safety during storage
- Control switch allows blades to be held in a tighter position for easier handling
- Angled shears allow easier cutting through flat materials
- Soft mold grip for comfort and control

Vinyl Cutter



Stock No.	Description	i i	Order No.
YA444B	Cutter, Vinyl	1	803013
YA444B1	Replacement Blades	1	803014

- Cleanly cuts plastic, rubber, vinyl, upholstery, leather, hoses, and rope
- ERGO Grip handle with safety lock
- Blade storage in handle
- Includes three (YA444B1) stainless steel replacement blades YA444B1 Replacement Blades
- Includes 3 replacement blades and anvil for YA444B



Scissors, Shop, Heavy Duty

Packing: 1

HDSCISSORS Order NO.: 803012



- For leather, cloth, plastic, rubber sheet, rubber hose, cardboard, gasket material, rope and many other materials
- Stainless steel blade and fasteners
- Precision ground and heat treated for a long lasting edge
- Ergonomic handles can be used right or left handed

Cutter, Multi-Purpose



Stock No.	Description	i i	Order No.
YA580A	Cutter, Multi-purpose	1	803015
YA580A-1	Replacement Blades	1	803020

- Features auto locking, fully retractable blade
- All metal body is black with pocket clip
- Includes (1) premium steel 13 pt. snap blade
- Overall length of 5 3/8" (136.5mm) YA580A-1 Replacement Blades
- Pack of 5

Cutter, Multi-Purpose



Stock No.	Description	i i	Order No.
YA581A	Cutter, Multi-purpose	1	803016
YA581A-1	Replacement Blades	1	803023

- Has three blades with eight snap off points.
- Minimum blade wobble
- Fully retractable

YA581A-1 Replacement Blades

Pack of 10

Utility Knife

Packing: 1





- Convenience and good looks of a folding lock back knife with easily replaceable two notch razor blades
- Folding lock back blade, hardwood handle with belt clip and thumb stud for one-hand opening
- Includes utility knife and leather pouch (both with Blue-Point® logo) plus 10 replacement blades
- Uses UKBU10 (10 pack) or UKBU50PK (50 pack) replacement blades

Utility Knife (Discontinued)

Packing: 1

LBUK2

Order NO.: 803018




- Thumb pad allows controlled application of pressure
- Blades are easily replaced with a flip of a switch
- Blade storage under spring loaded door
- Includes leather pouch with belt loop plus 5 replacement blades

Utility Knife (Discontinued)

Packing: 1

LBUK3 Order NO.: 803019





- Two notch blades are easily changed with quick change switch
- Includes belt pouch and 10 titanium replacement blades
- Uses UKBU10 (10 pack) or UKBU50PK (50 pack) replacement






Utility Knife Blades

Packing: 1

UKBU10 Order NO.: 803021

Double Flaring Tool Set





- Bi-metal construction allows blade to bend/flex without breaking under normal work conditions
- Bi-metal lasts up to 3 times longer than normal utility knife blades
- Two-notch blade design fits most standard utility knives
- Use with LBUK1, LBUK2 and LBUK3 Utility Knives
- Pack of 10 blades



Stock No.	\tilde{\	Order No.
TF5A	1	803038
TFM5A	1	803039

TF5A

- Makes double or single flares on soft steel, brass, or aluminum tubing from 3/16" to 1/2" OD
- Makes a smooth fitting, crack free 45° flare
- Set includes five adaptors, yoke assembly, bar assembly, and handle
- Storage case included

TFM5A Metric Double Flaring Tool Set

- Same design as TF5A except it is for tubing with an OD from 4.75 to 10mm
- Set includes yoke, bar assembly, handle, and five adaptors: 4.75, 5, 6, 8, and 10mm
- Storage case included

Utility Knife Blades

Packing: 1

UKBU50PK Order NO.: 803022

Flaring and Swaging Set

Packing: 1

TF275A

Order NO.: 803040



- High performance blades are perfect for thick, dense materials
- Bi-metal construction allows blade to bend/flex without breaking under normal work conditions
- Bi-metal lasts up to 3 times longer than normal utility knife blades
- Two-notch blade design fits most standard utility knives
- Convenient dispenser provides storage for used blades
- Use with LBUK1, LBUK2 and LBUK3 Utility Knives
- Dispenser of 50 blades



- 45° flare or swage soft copper, brass, or aluminum tubing
- Die blocks handle 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", and 3/4" OD tubing
- Swages 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4" OD tubing
- TF275PB storage case included





Metric Bubble Flaring Set

Packing: 1

TFM428 Order NO.: 803041



- For automotive brake systems
- Designed for crack free bubble flares on soft wall tubing up to a wall thickness of .028"
- Adaptors included for 4.75, 6, 8, and 10mm flares
- TFM428PB storage case included

Tube Cutting and Double Flaring Set

Packing: 1

TF528D Order NO.: 803037



- Contains TC28C tubing cutter and a double flaring set with a flaring bar, rod handle, yoke, and 5 adaptors: 3/16", 1/4", 5/16", 3/8", and 1/2"
- Storage case included

Tubing Cutter



Stock No.	V	Order No.
TC28C	1	803030
TC28B1	1	803032

- Cuts soft metal tubing ranging from 1/8" to 1" in diameter
- OD capacity is 1/8" to 1 1/8"
- Micrometer type adjustment
- Retractable locking reamer blade
- Cutter wheel is easily replaceable **TC28B1 Cutting Wheel**
- Extra cutter wheel for TC28C

Tubing Cutter



Stock No.		Order No.
TC123C	1	803031
TC123CRH	1	803035
TC123C1	1	803033

- Handles tubing from 1/8" to 5/8" OD
- Can be used where clearance around tubing is less than 1 3/8"
- 1 1/2" long when closed and 2" long when open; feed knob is 7/8"
- TC123CRH Ratcheting Tube Cutter Handle Handle for TC123C tube cutter
- TC123C1 Cutting Wheel Extra cutter wheel for TC123C

Ratcheting Tube Cutter

Packing: 1





• TC123C cutter and TC123CRH handle combined into one unit







Measuring & Other Hand Tools







Measuring & Other Hand Tools Measuring Tools

Feeler Gauges, 13pcs

FB310B Order NO.: 804001

Feeler Gauges, 25pcs

FB325A

Feeler Gauges, 35pcs

FB335





Packing: 1

Order NO.: 804002



Order NO.: 804003





Stock No.	Increments	Blade Size	Style	Blade Dimensions (inches)	No. of Blades	Description
FB310B	-	.001", .0015", .002" thru .008", .010", .012", .013", .015"	General Use	¹/2 x 3	13	Double stamped with U.S. and metric sizes
FB325A	.001"	.0015", .002" thru .025"	General Use	¹/2 x 3	25	Double stamped with U.S. and metric sizes
FB335	.001"	.0015", .002" thru .035"	General Use	¹/2 x 3	35	Swedish feeler blade steel

Feeler Gauges, 25pcs

Packing: 1

FBL325A

Feeler Gauges, 20pcs

FBM320

Feeler Gauges, 18pcs

FB316B

Order NO.: 804004

Packing: 1

Order NO.: 804005

Packing: 1

Order NO.: 804006







Stock No.	Increments	Blade Size	Style	Blade Dimensions (inches)	No. of Blades	Description
FBL325A	.001"	.0015", .002" thru .021", .025", .027", .030", .040"	Long Blade General Use	¹/₂ x 12	25	Long blade, double stamped with U.S. and metric sizes
FBM320	.05mm	.05 thru 1mm	Metric General Use	^{1/} 2 x 3	20	Metric Feeler Gauge Set
FB316B	.001"	.010", .012", .013", .015" thru .022", .024" thru .026", .028", .030", .032", .035"	Short Blade Ignition/Spark Plug Gauge	¹ / ₄ x 1 ³ / ₄	18	Short Blade, Ignition/Spark Plug Gauge Set

Feeler Gauges, 26pcs

Packing: 1

FB326B Order NO.: 804007

Feeler Gauges, 25pcs

FB300A

Feeler Gauges, 12pcs

FB308D

Packing: 1

Order NO.: 804009







Stock No	. Increments	Blade Size	Style	Blade Dimensions (inches)	No. of Blades	Description
FB326B	.001"	.008", .010", .012", .013", .015", .017", .018", .020", .022", .024" thru .026", .028", .030", .032", .035"	Combination Feeler/Ignition Gauge	¹/2 x 3	26	Double stamped with U.S. and metric sizes
FB300A	.001"	.006" thru .030"	Bent Blade	¹ / ₂ x 3	25	Feeler Gauge Set
FB308D	.001"	.008"010", .011"013", .013"- .015", .015", .017", .017"- .019", .018"020", .020"022", .023"- .025", .025"028", .028"030"	Step Blade	½ x 3	12	Step Feeler Gauge Set , Bent handle to clear manifolds, double stamped with U.S./Metric sizes. Blades are mounted on FBFT7 holder



Measuring & Other Hand Tools Measuring Tools

Feeler Gauges, 22pcs

FB322 Packing: 1 Order N804010

Feeler Gauges, 2pcs

FB328A

Feeler Gauges, 2pcs Packing: 1

FBM322 Order NO.: 804012






Packing: 1

Order NO.: 804011






Feeler Gauges, 14pcs

Packing: 1

FB307D

Order NO : 804013



• Bent blade cummins diesel, blade ends are bent at 90° angle: blades are secured on FB307C1 ring

Measuring Tapes



Stock No.	Length (meter)		Order No.	
BMPLM3	3	1	804018	
BMPLM5	5	1	804019	

- Rubberized coating for better grip
- Tape auto-lock when extended
- Nylon coated tape

Measuring Tapes



Stock No.	(meter)		No.
ВМРМ3	3	1	804015
BMPM5	5	1	804016
BMPM8	8	1	804017

- Tough and durable construction
- Dual scale-- metric and imperial

Long Tape, Steel, 100ft

TPM100 Order NO : 804014

Packing: 1



- Includes inch/metric scale
- Quick rewind design for ease of use
- Rewinding lever conveniently stored in housing
- Non-slip grip provides confidence and comfort

Spirit Levels, 9"

Packing: 1

TL100A Order NO.: 804021



- 9" precision measuring tool designed for close quarter work
- Magnetic strips and v-grooving make it ideal for pipe and conduit

Angle Locator

Packing: 1

YA328A Order NO.: 804022



- Precise, accurate tool to determine angle measurements
- Ideal for checking drive shaft angle
- Red degree indicator located behind numbers for exact reading of graduations
- English and metric scales molded into base of tool in 1/8" and DM
- Large 1 7/8" x 7/8" magnet inserted in base for secure retention







Packing: 1

Measuring & Other Hand Tools

Combination Measuring Set

SQUARECOMB12 Order NO.:804023

Packing: 1

Measuring Tools

Digital Caliper

MCAL6A Order NO : 804029



Stock No.	Description		Order No.
SQUAREB180	Square Protractor Head	1	804026
RULER12BSQ	Steel Rulers, 12"	1	804027
SQUAREB90	Square Sliding Head	1	804025
SQUAREB45	Square Sliding Head 45°	1	804028

• Set includes SQUAREB180 Protractor, RULER12BSQ steel ruler plus SQUAREB90 and SQUAREB45 sliding heads in fitted storage



- Gauge is 0" to 6" (0 to 150mm) in 0.0005" (0.01mm) resolutions
- Use for inside, outside, depth and step measurements
- Inch/metric conversion with one button
- Large LCD display
- Hardened stainless steel frame
- Conform to standard : GB1214

Machinist's Measuring Set

Packing: 1

SQUAREB12 Order NO.:804024



Stock No.	Description	V	Order No.
SQUAREB90	Square Sliding Head	1	804025
RULER12BSQ	Steel Rulers, 12"	1	804027

ruler in fitted storage case

Digital Caliper

Packing: 1

MCAL12A Order NO.: 804030



• Set includes SQUAREB90 sliding head and RULER12BSQ steel

- Essential tool for working on larger vehicles, trucks, tractors and earth moving equipment
- Range is 0" to 12" (0 to 305mm) in 0.0005" (0.01mm) resolutions
- Use for inside, outside, depth and step measurements
- Inch/metric conversion with one button
- Large LCD display with floating zero set
- Locking nut and thumb roll for smooth action
- Conform to standard : GB1214

Dividers, 6"

Packing: 1

CNT6521 Order NO.: 804057



- Spring type divider has virtually no torsion or side play
- Previous part number was PMF129

Dial Type Caliper

Packing: 1





PMF147A

- Gauge is 0" to 6" in high (0.001" increments) and metric (0.1mm increments)
- Includes storage case
- Conform to standard : GB1214





Measuring & Other Hand Tools

Digital Micrometers



Stock No.	Range (mm)	Increments (mm)	P	Order No.
MIC1MB	0-25	0.01	1	804032
MIC2MB	25-50	0.01	1	804033
MIC3MB	50-75	0.01	1	804034
MIC4MB	75-100	0.01	1	804035
MIC5MB	100-125	0.01	1	804036

 MIC103MB Digital Metric Micrometer Set includes: MIC1MB. MIC2MB and MIC3MB

Digital Micrometers



Stock No.	Range (inches)	Increments (inches)		Order No.
MIC1B	0-1	0.0001	1	804037
MIC2B	1-2	0.0001	1	804038
MIC3B	2-3	0.0001	1	804039
MIC4B	3-4	0.0001	1	804040
MIC5B	4-5	0.0001	1	804041

• MIC103B Set includes: MIC1B, MIC2B and MIC3B

Outside Micrometers



ı	Stock No.	Range (inches)	Increments (inches)	V	Order No.
ı	MICB1B	0-1	0.0001	1	804042
ı	MICB2B	1-2	0.0001	1	804043
1	MICB3B	2-3	0.0001	1	804044
1	MICB4B	3-4	0.0001	1	804045
1	MICB5B	4-5	0.0001	1	804046

• MICB103B Set includes: MICB1B, MICB2B, MICB3B

Measuring Tools

Electronic Digital Micrometers

Packing: 1

MICED1B

Order NO.: 804048



- Display reads to 0.00005" (0.001mm)
- Zero set for absolute and incremental measuring modes
- Auto shut-off after 10 minutes
- Insulated frame, hardened body, carbide tipped anvil, positive locking clamp and ratchet stop thimble

Inside Micrometer Set, 7 pcs

Packing: 1

MICINSIDE12 Order NO.: 804047



- Tubular design
- Range is 2" to 12" in .001" increments
- Includes inside micrometer head and a series of coil spring pressure contact rods

Depth Micrometer Set

Packing: 1

DM6

Order NO.: 804049



Stock No.	Description		Order No.
DM61	4" rod	1	804050
DM62	5" rod	1	804051
DM63	6" rod	1	804052
DM64	7" rod	1	804053
DM65	8" rod	1	804054
DM66	9" rod	1	804055
DM67	Micrometer Head	1	804056

- Measure depths of slots, counterbores, holes and keyways up to 6"
- 4" satin chrome base for greater stability
- Graduated in .001" increments
- · Includes fitted storage case







Measuring & Other Hand Tools

Penlight, Blue Packing: 1 Order NO.: 805001

- High intensity 3 watt LED, 100 lumen penlight
- Extremely bright light output
- Uses (3) AAA alkaline cells
- Only 6.25" in length and 1/2" in diameter
- Includes pocket clip and protective rubber tip
- Blue in color

Penlight, Silver ECFB200S Packing: 1 Order NO.: 805002

- High intensity 3 watt LED, 100 lumen penlight
- Extremely bright light output
- Uses three AAA alkaline cells
- Only 6.25" in length and 1/2" in diameter
- Includes pocket clip and protective rubber tip
- Silver in color



 3 watt LED flashlight features a K2 Luxeon LED that produces 130 lumens

- The flashlight body is aerospace grade extruded aluminum with heavy anodization
- Average run time is 10-hours on 2D alkaline batteries
- Reflector is highly polished for maximum light output
- The switch is self cleaning
- Water and shock resistant
- Requires 2 "D" cell batteries (not included)

Flashlights

ECFB200BL

Compact Flashlight



BLED1 Order NO.: 805018

ECF1600

YA5100B

Order NO.: 805006

Adjustable beam by sliding zoom

- Anodized aluminum casing
- LED type : CREE XP-E-R2
- Luminance flux:195mm
- Switch mode: High Light, Low Light, Strobe, SOS
- Power Source : 3x AAA alkaline batteries
- Waterproof grade: IPX6

Bendable Light

Packing: 1



- · Heavy duty barrel handle and switch
- Features 10 flexible shaft and 3/16" high intensity lamp
- Includes (2) AA batteries

Bendable Light Packing: 1 Order NO.: 805007

- Features brilliant krypton lamp on a slender, 15" long, flexible shaft
- Includes 24" extension cover, which can make the light almost 40" long for difficult-to-view areas
- 3/16" lamp diameter
- Runs on (2) AA alkaline batteries

LED Under Hood Light

Packing: 1

ECF201A

Order NO.: 805009

ECUB9500AP Order NO.: 805011



- Extendable lightweight aluminum holder
- Length of 47"-71" covers a wide range of vehicles
- 95 ultra bright LED's provide 900LUX at 0.5m
- Rubber coated hooks protect paintwork from damage
- Cordless design improves safety and convenience
- 4400 mAh battery provides 5 hours constant light output
- Test results show 27% brighter, +28% longer life than primary competitive unit





Measuring & Other Hand Tools Flashlights

Rechargeable LED Shop Light





Rechargeable LED Shop Light


Packing: 1

ECFLED215AP Order NO.: 805013









- 21 front-facing LEDs provide high light output to work surfaces
- 5 LED spot light provides up to 15 hours of continuous illumination
- Multi-function switch toggles between front and top LED illumination
- 180° folding design offers the ultimate in flexible positioning
- Dual magnetic design for parallel use or multi angle







- 20 high output LEDs provide 1,600 lux of light
- Strong rechargeable Lithium-ion battery lasts up to 4 hours
- 360 degree folding design enables flexible light positioning
- Magnetic base allows placement on metal surface
- Handy pocket size with belt clip for great portability
- CE/UL certificated charger 110-240V





Flashlights / Safety

Rechargeable Shop Light

Packing: 1



- IP65 rating, heavy duty and robust
- Vapor, water and dust proof
- Rechargeable, Li-ion battery with 4 hours constant output
- 3 pcs magnets, totally hand free works, easier for technicians to operate
- 1 hook new design, rotate 360 degree
- 1 Stand to support this light work on 3 angles
- 180 degree bendable. Offering all lighting angle possibilities.
- CE/UL certificated charger

Rotating Light Mag Base

Packing: 1



ECFBP20AP

Order NO.: 805014



- 24 high output LEDs project light in wide area
- Provides 40 lumens light output
- (3) AAA alkaline cells provide 4~5 hours of light
- Strong magnet mounts securely on any magnetic surface
- Mounts under-hood, under-dash, under-car wherever it is needed
- Direct light to any angle using rotating magnetic base
- Keeps hands free to do the work, while lighting the work area

Flood Light

Packing: 1





- Powerful and uniform illumination ideal for lighting working environment
- Utilizing LED reduces energy consumption
- 70 SMD LED provides up to 2500 lumen, 35W
- IP65 Resistant to water and dust infiltration
- Compact and robust construction with strong rubber protection frame
- With flexible stand to allow placing the lamp in the desired angle
- Total aluminum design for better heat distribution

LED Headlight

Packing: 1



- LED headlight for applications requiring hands free lighting
- Bright watt LED never needs replacing
- Pivoting head and adjustable headband
- Water resistant
- 30 hours continuous run time on (3) AAA alkaline batteries

Washable Work Gloves



Stock No.	Size	Color		Order No.
GLOVE103MA	Medium	Black	1	806003
GLOVE103LA	Large	Black	1	806001
GLOVE103XLA	X-Large	Black	1	806005
GLOVE103MAB	Medium	Blue	1	806004
GLOVE103LAB	Large	Blue	1	806002
GLOVE103XLAB	X-Large	Blue	1	806006

ECFHEAD1A

Order NO.: 805003

- Gloves feature stretch knit with padded back to provide extra feel and flexibility to grasp small objects
- Extra knuckle protection on back of fingers
- Heat resistant synthetic double layered leather palm for longer life
- Elastic cuff with hook and loop closure

Abrasion Resistant Nitrile Gloves



Stock No.	Size		Order No.
GLOVE400S	Small	3	806009
GLOVE400M	Medium	3	806008
GLOVE400L	Large	3	806007
GLOVE400XL	X-Large	3	806010
GLOVE400XXL	XX-Large	3	806011

- Nitrile dipped coating for protection on dirty jobs
- Ergonomically pre-curved design gives you comfort at all times
- High abrasion resistance protects hand on sharp edges and rough castings
- Incredible grip and dexterity on wet and dry surfaces
- Lightweight nylon shell provides a nice snug fit
- CE rated for abrasion, blade cut, tear and puncture resistance





Welders Gloves

Packing: 1



YA427B Order NO.: 807030

- Helps protect hands from sparks when welding
- Leather construction with added insulation for heat protection
- Reinforced palm for durability

Tig Welding Gloves

Packing: 1



- Ideal for TIG welding processes
- Pigskin material for precise control
- Helps protect hands from heat and sparks
- Thick leather cuff for wrist protection

Welding Sleeves 1 Pair

Packing: 1

YA4280 Order NO.: 807031



- Helps protect arms from sparks when welding or cutting
- Elastic bands at each end of sleeve
- Constructed of flame retardant fabric
- 18" long
- 1 pair

Face Shield

Packing: 1

GA225 Order NO.: 806012



Shield Style	Shield Size (inches)
Flat	7 ^{3/} 4 x 15 ^{1/} 4
Shield Included	Replacement Shields
Clear	GA225-1 (with PETG) GA225-2 (with PC)

- Adjustable, cushioned head band is removable
- Face shield provides impact resistance
- Includes visor (GA225-1) with PETG (impact resistance perferred)
- Optional visor (GA225-2) with PC (high temperature resistance) is available

Safety Glasses



Stock No.	Lens	Frame		Order No.
GLASS30R	Clear	Red	1	806016
GLASS30BK	Clear	Black	1	806015
GLASS31R	Clear	Red	1	806018
GLASS31BK	Clear	Black	1	806017

- Complies with ANST Z87.1-2003
- Lens provide 99.9% UV protection
- Angle and length adjustable temples provide various suitable fitting
- Soft nose pad and soft temple tips provide comfort for long-time
- Anti-fog lens coating with anti-scratch protection
- GLASS30BK and GLASS30R have a ventilation channel between frame and lens

Ear Protector

Packing: 1

GA3200 Order NO.: 806013



Noise Reduction Rating, dB	Headband
28	Cushioned
Ear Piece	Weight (lbs.)
Cushioned	0.77

- Noise reduction rating of 28 dB for protection
- Lightweight and comfortable with cushioned headband
- Cushioned ear piece for a comfortable and snug fit that keeps out
- Each ear piece pivots to provide a comfortable and secure fit
- Blue hard protective ear cups with Blue-Point[®] logo in white
- Each ear piece easily adjusts to fit a variety of sizes

Ear Protector, Ear Plug Style

YA160A

Packing: 1



Headband	
Plastic	
Ear Piece Replacements	Weight (lbs.)
YA160A1	0.06
	Pla Ear Piece Replacements




- 25 dB noise reduction rating
- Cushioned ear piece for comfort and snug fit to keep out noise
- Non-conductive
- Includes extra set of foam ear piece and reusable storage bag





Measuring & Other Hand Tools Miscellaneous





PHT5 Order NO.: 807004

er NO.: 807004 Packing: 1



PT5CBL Order NO.: 807006

- Lifts 2.5 lbs.
- Chrome plated shaft extends from 5 1/2" to 25 1/2"
- Black cushion grip will not slip in oily or wet hands
- Includes pocket clip
- Hinged head magnetic pick up tools
- · Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads

- This 5 7/8" tool extends to 25 9/16"
- Magnet lifts up to 2 lbs.
- Includes pocket clip
- Blue
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads



Pick Up Tool Packing: 1

PT5C Order NO.: 807005

- 01401110... 001000
- Pick Up Tool
 Packing: 1

UPT15 Order NO.: 807007

- This 5 7/8" tool extends to 25 9/16"
- Magnet lifts up to 2 lbs.
- Includes pocket clip
- Chrome
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads

- Lifts 2 lbs.
- 6 5/8" long, and extends to 33 1/4"
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads



Pick Up Tool UPT2FL Packing: 1 Order NO.: 807008

- 29" aluminum shaft can be easily bent at any angle to retrieve dropped metal objects in hard to reach areas
- Power cap slides over the magnet and shield its sides from attaching to unwanted metal surfaces
- Will pick up 5 lbs, with the power cap
- Textured cushion pistol grip will not slip in wet or oily hands

Pick Up Tool UPT35 Packing: 1 Order NO.: 807009 Blue-Point verse

- Lifts 4 1/2 lbs.
- 6 5/8" long, and extends to 33 1/4"
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads



- Lifts 10 lbs.
- 6 5/8" long, and extends to 33 1/4"
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads



- Perfect for retrieval of heavy ferrous objects in hard to reach areas
- Goblet shaped magnetic head pushes the flux to the front of the magnet enabling the user to lift 16 lbs
- Head shields the sides of the magnet from attaching to unwanted ferrous surfaces
- Telescopes from 9" to 34 1/4" (229 to 870mm)
- Stainless steel handle is strong, lightweight and inhibits corrosion
- Cushion textured pistol grip will not slip in wet or oily hands

Miscellaneous

Inspection Mirrors



Stock No.	i i	Order No.
UIM125	1	807001
UIM225	1	807002
UIM325	1	807003

UIM125 Telescoping Inspection Mirror

• 1 1/4" diameter mirror. 6 1/2" long, and extends to 35"

UIM225 Telescoping Inspection Mirror

2 1/4" diameter mirror. 6 1/2" long, and extends to 35"

UIM325 Telescoping Inspection Mirror

• 3 1/4" diameter mirror. 6 1/2" long, and extends to 29 1/2"

Hose Nozzle

Packing: 1

UPT50A

Order NO.: 807010



NOZZLE360A Order NO.: 807014

- Turns any standard 5/8" hose into a multi-function cleaning tool
- Five different spray patterns for multiple applications
- Wash/rinse vehicles or water plants using a softer, cascading
- Clean pools, deck and driveways with heavy duty stream
- Clean service bays, shop floors and blast mud/dirt from vehicles with a powerful jet stream
- 360° jetted nozzle is engineered from rugged extruded aluminum. forged stainless steel, high grade fiberglass and comfort grip santoprene rubber
- Patented 2-way shut off

Rivet Tool

Packing: 1



HP2 Order NO.: 807012

- Has four nose pieces for 3/32" to 3/16" diameter rivets
- For 1/8" thru 5/8" thickness
- Made of aluminum alloy









Deburring Tool

Packing: 1

DEBUR300

Order NO.: 807013



- Easily deburr drilled and machined holes
- Push button locking collet enables quick, easy blade changes
- Includes three round head deburring blades
- Blades conveniently store in handle of tool
- Weighs 1 lb
- 6" long

Packing: 1

Magnetic Holder

Order NO.: 807016

CM6416



- Magnet has "on/off" switch
- Base is 2 3/8" x 1 7/8" x 2 1/2"
- Post is 7" x 15/16"
- Rod is 6" x 25/64"
- Will grip flat or curved metal surfaces

Deluxe Air Vacuum System

AV1000A

Packing: 1

Order NO.: 807015



	Stock No.	Air Consumption, Average, DFM (SCFM) [l/min]	Free Speed, dBa
	AV1000A	3 (21) [84.95]	81.2
0	Sound Level, Working (dBa)	Recommended Hose Size (inches)	Length (without bag), inches (mm)
	81.2	3/8	13 (330)
	Brush Size, inches (mm)	Bag Size, inches (mm)	Weight, lbs. (kg)
	1 ^{1/8} x 2 ^{5/8} (28.5 x 66.7)	6 ^{1/2} x 11 ^{1/4} (165 x 285)	0.88 (0.4)

- Ideal for vehicle media installation and body shops plus other applications in need of picking up dust, metal shavings or broken glass
- Large collection bag includes a debris baffle and sliding bag clamp for emptying debris
- Lightweight ergonomic handle design
- Includes 8.7" aluminum extension tube, 8 1/2" plastic extension tube (AV1000A10), flexible extension tube (AV1000A9), pointed nozzle (AV1000A11) and crevice tool with brush (AV1000A8)

Miscellaneous

Bench Vise



Stock No.	Jaw Width		Order No.
BLPMV4	4" jaws	1	807017
BLPMV5	5" jaws	1	807018
BLPMV6	6" jaws	1	807019

- Single piece steel blocks for higher load capacity
- Extended anvil
- Lubrication points for maintenance
- Optional swivel base
- Capacity range from 3.5 ton to 9 ton at maximum opening
- Reinforced cantilever support
- Interchangeable jaws
- Diamond ground for better grip
- Heavy duty cast iron construction
- Precise jaw alignment
- Rolled thread spindle for easy locating and tightening parts
- Protected spindle

C-Clamps



	Stock No.	Capacity (inches)	Throat Depth (inches)		Order No.
-	CL404VIS	0 - 4 1/2	3 1/4	1	807027
	CL406VIS	0 - 6 1/16	3 ⁵ /8	1	807028
	CL408VIS	0 - 8 1/4	5	1	807029

- Similar to CL series c-clamps
- High visibility models conform to OSHA safety color standard for physical hazards regulation #19110.144
- 3/4" spindle diameter

Welding Helment, Auto Darkening

YA4603

Packing: 1



- Two arc sensors for enhanced lens triggering
- Fixed shade #10
- Clear shade of 3.5
- Fixed delay
- Viewing area 1.38"x 3.81"
- Solar powered
- Fixed shade auto darkening welding helmet has a lens that is designed for carbon arc welding processes. Two arc sensors provide a range of sensitivity to trigger the lens under most welding conditions.
- Meets ANSI Z87.1-2003, CE, DIN 4647 PZ, EN379, EN175, CSA Z 94.3 and AS/NZS 1338.1 standards





Standard Duty Welding Kit

Packing: 1

WE200A Order NO.: 807034



Stock No.	Description
HRC1401340	85 Weld Handle with Check Valves
HRC1300380	72-3 Cut Attach
HRC9100614	D-85 Weld Mixer
HRC4300557	³ /16 x 20 Twin Hose
HRC4304482	Cover Goggle
HRC9004486	Striker
WE200A1	Oxygen Regulator
WE200A2	Acetylene Regulator
HRC1502172	6290-1 #1 AC Cut Tip
HRC1600890	23-A-90-5 #5 Weld Tip
HRC1600870	23-A-90-3 #3 Weld Tip
HRC1600850	23-A-90-1 #1 Weld Tip

Optional Accessories

Stock No.	Description
HRC1800710	J-63-1 Heating Assembly
HRC1600840	23-A-90-0 #0 Weld Tip
HRC1600860	23-A-90-2 #2 Weld Tip
HRC1600880	23-A-90-4 #4 Weld Tip
HRC1502170	6290-00AC #00AC Cut Tip
HRC1502171	6290-0AC #0AC Cut Tip
HRC1502173	6290-2AC #2AC Cut Tip
HRC1502174	6290-3AC #3AC Cut Tip
HRC4301650	88-5FBT PR. Torch Flash Arrestor
HRC9000160	E-9 Tip Cleaner (2 pc tip)
HRC9004484	Replacement Flints

- Use for auto repair, construction, fabrication, manufacturing and maintenance
- Cuts up to 1" and welds up to 1/8"
- Cuts up to 4" and welds up to 1/2" with optional tips
- Durable and strong forged brass regulator
- Regulator diameter 2 1/4" allows precise control of gas
- Internal Iter keeps particles from entering regulator
- PTFE Teon seat ensures positive sealing
- Handle shut-o valve color coding provide ease in identifying the corresponding gas control
- Two piece cutting tip allow easy cleaning
- High quality hose oers reduced tear resistance and increased exibility

Miscellaneous

Industrial Paper

BPAP1 Order NO.: 807035





Stock No.	Size(mm)	Color	Pieces / Roll	I	
BPAP1	31*34cm	White	1100	1	

- Excellent for cleaning off oil and residue from tools, hardware, equipment and mechanical components
- Tough for industrial use
- Lint free to prevent electrostatic charge as well as a clean surface
- Made from cellulous and polypropylene for better absorbability

Industrial Paper

Packing: 1

BPAP2

Order NO.: 807036





Stock No.	Size(mm)	Color	Pieces / Roll	V
BPAP2	25*35cm	Green	300	6

- Excellent for cleaning off oil and residue from tools, hardware, equipment and mechanical components
- Tough for industrial use
- Lint free to prevent electrostatic charge as well as a clean surface
- Made from cellulous and polyethylene for softness and finer surface

Roller Stand

Packing: 1

BPAPS1 Order NO.: 807039



Foldable Metal Stand for BPAP1





Shop & Technician Tools







Shop & Technician Tools Testing and Electronics

Borescope
Packing: 1


BKB6500 Order NO.: 901017

SPECIFICATIONS:

Ontimal Viewing	1" to 12" (2.5 cm — 30 cm)
Optimal Viewing	
Power Supply	Li-Ion Battery 3.7V, 4200 mAh
Estimated battery run time	3-5 hours
Weight	1lbs 14oz. (0.5 kg)
Internal Memory	512 MB storage
Built in micro SD card bay	high capacity compatible
Dimensions	7" (17.8 cm) L x 3.63" (9.2 cm) W x 6.25" (15.9 cm) H
Temperature	2°F to 113°F (0°C to 45°C)
Humidity	5% to 95% non-condensing (display unit)
Storage Temp	-4°F to 158°F (-20°C to 70°C)
Water Resistance	Imager to 10' (3.05 m) depth

- 4.3" TFT LCD Display with a native resolution of 480 RGB X 240
- Digital camera technology provides superior imagery under all light conditions compared to analog cameras
- Dual view Imager allows the user to see forward or 90° to the side with one touch
- Easy to use touch screen interface
- File naming for convenient file management
- Text annotation aids in documentation
- Coil cord imager handle allows for greater maneuverability while the base stays at a comfortable viewing position
- Low optical distortion provides superior image quality
- Capture still images at 640 X 480 resolution
- Capture video at a rate of 20 fps (frames per second)
- 2X digital zoom
- Excellent near-field focus (0.5" to 12")
- Imaging head made of robust aluminium

- Resistant to common automotive and industrial chemicals
- Super Bright LED
- 8.5mm outside diameter fits in most spark plug holes
- Built in microphone and speaker for recording comments and sounds
- 36" long imager is coated with a non conductive covering for protection of surfaces and safety
- Mini-USB connector for uploading images and video to a computer
- Analog video out to a larger format screen or recording device
- Rubber over-mold on all contact/gripping areas for added ergonomics and durability
- Integrated rubberized magnets secure unit to metal surfaces
- External microSD Card access
- External mini-USB access
- Integrated three position stand for added convenience
- Rechargeable internal Lithium-ion battery
- D/C plug allows the unit to be used while battery is being charged





Shop & Technician Tools Testing and Electronics

Pick Sets



Stock No.	Description	Length (inches)		Ord er No.
PSLR4-1	Hook Pick	9 3/4	1	901011
PSLR4-2	90° Hook Pick	9 3/4	1	901012
PSLR4-3	Straight Pick	9 3/4	1	901013
PSLR4-4	Complex Pick	9 3/4	1	901014
PSLR4-5	Combo Pick	9 3/4	1	901015
PSLR4-6	Double Angle Pick	9 3/4	1	901016

- PSLR4 (Order No.901010) extra long pick set includes PSLR4-1 thru PSLR4-4 (4 pcs) in vinyl storage pouch
- PSLR6 (Order No.901001) extra long pick set includes PSLR4-1 thru PSLR4-6 (6 pcs) in vinyl storage pouch

Tweezer Kit, 5 pcs

Packing: 1

TZK5

Order NO.: 901006




- Includes five tweezers neatly arranged in a vinyl zipper pouch
- All stainless steel construction
- Pointed tweezers w/plain ends, 4 3/8" long
- Self closing tweezers w/plain ends, 4 1/2" long
- Sharp point utility tweezers w/bent plain ends, 7" long
- Sharp point uitility tweezers w/plain ends, 7" long

Tweezer Kit, 7 pcs

Packing: 1

TZK7 Order NO.: 901007





- All stainless steel construction
- Pointed tweezers, 4 3/8" long
- Curved head utility tweezers, 6 3/4" long
- Sharp pointed utility tweezers, 7" long
- Side locking tweezers, 6" long
- Spade point tweezers, 4 3/8" long
- Weighted solder tweezers, 6" long

Wire Cutter

Packing: 1

PWC27 Order NO.: 901005



Description	(inches)	Sizes
Automatic Wire Stripper	6 ^{1/4}	10, 12, 14, 16, 18, 20, 22
Strips Metric Sizes, (mm)	Application	Replacement Blades
_	Strips PVC, THHN, and THWN	PWC27-7

- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator
- Precision ground, knife-type blades provide clean, accurate stripping
- Cleanly strips wire up to full 7/8" (22mm)

Wire Stripper

Packing: 1

PWC28A

Order NO.: 902016



- One-step stripping enhances productivity
- Spring-action motion increases leverage and reduces operator fatigue
- Precision ground, knife-type blades provide clean, accurate stripping
- Cleanly strips wire up to full 7/8" (22mm)

Wire Stripper

PWC6

PWC12A

Order NO : 001002



Wire Stripper



	0.0	101 110 00 1002
Description	Length (inches)	Strips AWG Sizes
Wire Stripper/Cutter/ Crimper	9 1/2	10, 12, 14, 16, 18
Strips Metric Sizes (mm)	Application	Replacement Blades
10-18 Insulated and		

Non-Insulated 7-8mm Ignition Terminals

Wire Stripper

Packing: 1



PWC14
Order NO.: 901003

	Description	Length (inches)	Strips AWG Sizes
)	Wire Stripper/Cutter/ Crimper/Bolt Cutter	8 ^{3/4}	10, 12, 14, 16, 18, 20, 22
	Strips Metric Sizes (mm)	Application	Replacement Blades
	10-22 Insulated and Non-Insulated 7-8mm Ignition Terminals	_	_









Shop & Technician Tools Special Tools

Wire Cutter PWC19 Packing: 1 Order NO.: 902015 Micro Shear Wire Cutters Up to 20 Up to .80



Stock No.	Sq. Stock (inches)	Edge (inches)	Length (inches)		Order No.
1412A	1/2	5/8	14	1	902006
1658C	1/2	5/8	16	1	902010
2420A	3/4	¹⁵ / ₁₆	20	1	902011
2430C	3/4	5/8	30	1	902012
2438C	3/4	7/8	38	1	902007
2842C	7/8	1	42	1	902008

Crimp Tool PWC34 Packing: 1 Order NO.: 902013

- Double compound action with ratchet control for almost effortless operation
- Use with insulated connectors on 10 to 22 gauge wire
- For easy, efficient, single squeeze crimping of modular connectors
- Both primary and secondary crimps are made simultaneously to factory specifications
- Has a comfortable ergonomic design and full cycle ratchet action



PBFG415



- Drop forged, hardened steel wedge end with rust-resistant black finish, is chemically bonded to fiberglass handle
- 50,000 strands of fiberglass are sleeved by a polypropylene jacket for comfort and variable hand placement during use
- About one-half the weight of a steel prybar of the same length and less flexible than a steel prybar for greater leverage
- Polypropylene sleeve is resistant to heat and cold for greater comfort in all temperatures

Power Bit Set, 52 Pcs

Packing: 1



YA52PBSQC Order NO.: 902005

- Ideal for use with cordless drills and screwdrivers Includes:
- 49 1/4" hex shank bits in short and long lengths
- 2 hex adaptors
- Flat tip bits (long): 6-8, 8-10, 10-12
- Hex bits (short): 1/8", 9/64", 5/32", 3/16", 7/32", 1/4", 9/32"
 Hex bits (long): 5/32", 3/16", 7/32"
- PHILLIPS® tip bits (short): #1, #2 (2 each), #3
- PHILLIPS® tip bits (long): #1, #2, #3
- TORX[®] tamper resistant bits (short and long): T10, T15, T20, T25, T27, T30, T40
- Square bits (short and long): #1, #2, #3
- Clutch bits (short and long): 5/32", 3/16"
- Double end bits: 6-8 x #2 PHILLIPS®, 8-10 x #3 PHILLIPS®
- Adaptors: 1/4" hex female to 1/4" hex female, 1/4" hex male to 1/4" square male, 1/4" hex quick change chuck

Magnetic Trays



Stock No.	Description	Sizes	Ü	Order No.
MRB5A	Magnetic tray, Round	Round 152mm diameter	1	902018
MRB10A	Magnetic tray	250mm x 140mm	1	902019
MRB12A	Magnetic tray	355mm x 140mm	1	902020
MRB15A	Magnetic tray	290mm x 265mm	1	902021

- Securely holds small parts and tools
- Magnetically attaches to any flat iron or steel surface
- Material: 430 Stainless Iron





Shop & Technician Tools Special Tools

Magnetic Tool Holder

Packing: 1

MAGWRENCH

Order NO.: 902022 Packing: 1 SDM11KT

Order NO : 902004



- Industrial strength magnets keep it secured to a metal surface
- Holds tools for quick and easy access
- Chrome plated steel bar with chrome plated nylon ends
- Overall size is 20" (with approximately 12" of magnetic holding



• 1/4" shank bits for use in difficult access applications where fastener cannot be approached straight-on 11 pc. set includes:

- TORX® Ball Hex Bits: T10, T15, T20, T25, T27, T30, T40, T45, T50
- Magnetic Insert Bit Holder

Torx Ball Hex Bit Set, 11pcs

- 1/4" Female Hex to 1/4" Female Sq. Dr. Adaptor
- All components store in case with belt clip

Blow Gun

Packing: 1

YA105020 Order NO.: 902001

YA1055B



• 20" bent nozzle

Blow Gun

Packing: 1

- Trigger provides variable air flow control
- Lightweight body with ergonomically designed grip provides comfort and control
- Insulated handle prevents cold hands
- Venturi tip directs air sideways if tip end is obstructed
- Reinforced 1/4"-18NPT inlet
- Maximum air pressure: 232 PSI (16 BAR)

Master Ball Hex Bit Set, 32pcs

Packing: 1

SDM32KT

Order NO.: 902003





- Variable flow trigger offers precise air flow control
- Six-outlet "star tip" delivers an even distribution of air
- 4" Full Flow tube
- Ergonomic handle design for increased comfort
- Complies with OSHA safety standards
- Air Inlet: 1/4" NPT
- Maximum Working Pressure: 175 PSI (12 bar)
- Vented Tip
- Triggers regulate airflow from partial to full line pressure
- Valve has no cutoff and no restrictions
- Each tip is side vented
- Each gun includes hanging hook and paddle-type air control lever

- 1/4" shank bits for use in difficult access applications where fastener cannot be approached straight-on 32 pc. set includes:
- Fractional Ball Hex Bits: 3/32", 7/64", 1/8", 9/64", 5/32", 3/16", 7/32", 1/4", 5/16", 3/8"
- Metric Ball Hex Bits: 2, 2.5, 3, 4, 5, 6, 7, 8, 9, 10mm
- TORX[®] Ball Hex Bits: T10, T15, T20, T25, T27, T30, T40, T45, T50,
- Magnetic Insert Bit Holder
- 1/4" Female Hex to 1/4" Female Sq. Dr. Adaptor
- All components store in case with belt clip









Shop & Technician Tools Special Tools / Automotive Specialty Tools

Prybar Set BLPPB704 Packing: 1 Order NO.: 902009

- Set includes 1412A (14") and 2420A (20") pinch bars, 7031A close quarter bar (16")and BPPC1878 flat chisel (18")
- All bars have a 100% black oxide finish



- For cutting battery cables and other soft metal cables
- Has vinyl covered handles
- 7 1/2" long



- Makes left, right, or offset bends up to a 90° angle
- Degrees shown for accurate bending angle
- Handles 3/16", 1/4", 5/16", and 3/8"
- (4, 6, and 8mm) OD aluminum, copper, and stainless steel tubing
- Aluminum unit is 8 1/4" long when opened

Gauge Set Packing: 1



• 5 piece set includes FB300A Bent Blade Feeler Gauge, FB305A Non-magnetic Feeler Gauge, and FB325A General Use Feeler Gauge, plus GA461B and FB360B Spark Plug Gap Gauges in the FBS5-1 Kit Bag

Digital Drum Gage



DG530 Order NO.: 903029



- Measures automotive and heavy duty brake drums
- Pointed anvils and 4.25" long arms allow increased measurement accuracy and coverage
- Easy to read digital display with inch/metric conversion
- Selectable depth stops for easier use
- Range 6"-20.65"/150mm-515mm
- Graduations .0005"/.01mm

Pad Spreader

Packing: 1



YA2440

Order NO : 903128

- For use on most domestic and import cars and light duty trucks with single piston disc brakes without parking brakes
- Compresses the disc brake piston for easy pad installation

Brake Rotor Tool

Packing: 1

TBS200A

FBS5

Order NO.: 903027

Order NO.: 902017

YA9329A Order NO.: 903031



- Use to rotate piston back into caliper cylinder when replacing pads
- Also rotates parking brake cylinder back into the caliper cylinder on vehicles with four wheel disc brakes
- For 1975 and later Ford and Mercury plus some imports

Spreader

Packing: 1



GA395 Order NO.: 903129

- For standard four piston caliper disc brakes Frees hands to assemble caliper over rotor
- 6 3/4" long





4 Ton Portaset

Packing: 1

YA1544A

Order NO.: 903132



- 4-ton capacity kit includes hydraulic unit, five "Snap-Set" extensions, spreader plus a full selection of attachments for most push applications
- Automatic pump overload system protects against damage to rams and equipment
- 1/2-ton capacity hydraulic spreader has 2" jaw and spreads from 5/8" to 3 3/4"
- Flex head includes permanently molded rubber pad
- Heavy walled extensions tubes stand up to the toughest loads
- Long handle reduces required pumping effort
- 18 piece set is stored in durable storage case

Tap & Die Set

Packing: 1

GA541 Order NO.: 903037



- Taps and dies from 1/4" to 1/2" in both NF and NC threads, taps and dies from 4-40 thru 12-24 and corresponding dies in Machine Screw Threads, a pipe thread tap and die, plus two die stocks and three tap wrenches, a screw pitch gauge, and a die adjusting screwdriver (41 pcs) in a storage case
- Die size 1/4" to 1/2" and 7 mm to 12 mm are a one-piece, 12-point design that can be turned with a 1" socket wrench (5/8" socket wrench for 3 to 6 mm dies) when working in places where a normal die stock cannot be used

Metric Tap & Die Set

Packing: 1

GAM541

Order NO.: 903038



- 40-pc set features 1" single hex non-adjustable dies from 3 to 12mm, a 1/8"-28 BSP die plus taps in the same sizes
- Also includes a die stock, 2 T-handle tap wrenches, a thread pitch gauge, a drill/tap chart and a midget screwdriver, all in a storage case

Extractor Set

Packing: 1



Order NO.: 903040

F1020

- Extracts broken screws from 1/4" to 1/2" diameter
- Comes in a storage case

Extractor Set

Packing: 1



E1025

Order NO.: 903039

- Extract broken screws from 1/4" to 1" diameter and standard pipe sizes 1/8" to 1'
- Packaged in a storage case

Meter ATV And Motorcycle

Packing: 1



MTPV1000

Order NO.: 903041

- · Peak voltage measurement of secondary ignition systems on all types of vehicles and pleasure craft
- CDI ignition diagnosis on motorcycles, ATVs, and snowmobiles
- Digital Multimeter functions to measure battery, sensor and circuit
- Check continuity of wiring and resistance of ignition wires

Circuit Tester

Packing: 1



BPECT1

- Circuit tester for 6 and 12 volt systems.
- Quickly and safely tests high and low voltages on all vehicles including computerized engine.
- Can be used to detect power, ground and find shorts and breaks.
- High impedance to protect sensitive electronic sensors, microprocessors, electronic ignition components and air bags.
- LED indicates red for power (high) and green for ground (low).
- Insulated alligator clip.









Exhaust Hanger Removal Pliers

Packing: 1





- For removing hanger brackets from their rubber mounting straps
- Place removal jaw behind the rubber grommet ring and the forcing pin of the pliers on the end of the steel hanger
- When handles are squeezed, the forcing pin pushes the ring off the
- Applications on most domestic and import cars as well as light trucks
- 14" long

Boot Pliers

YA824C Order NO.: 903036



- 45° offset jaws
- Vinyl coated jaws and handles assure gripping ability
- Use only on automotive type ignition systems
- 9 1/2" long

Fuse Buddy Pro Test Kit

FFFB310 Packing: 1 Order NO.: 903044



- Great tool for reading circuit amperage draws and troubleshooting up to 30 amps
- Pro Kit includes one meter with 3 interchangeable test functions: 30 amp MINI circuit current testing, 30 amp ATC circuit current testing and 30 amp all purpose current test
- Plugs directly into MINI and ATC fuse sockets
- Additional 30 amp test clips expand the testing capability
- Original fuse is replaced in-line, thereby maintaining circuit
- Easy connection into fuse socket, Fuse Body[™] end is shaped like a fuse
- LCD display features analog bar graph
- Unit also features Data Hold and Auto Power-Off
- Measuring Range:0-30 Amps/48 VDC-10 seconds
- Accuracy: ±2% of reading
- Resolution: 100 mA

Boot Pliers

Packing: 1

YA824ASTR Order NO.: 903035

- Straight jaw version of YA824C
- 9 3/4" long

Fuse Saver Kit

Packing: 1

YA8005 Order NO.: 903045



- Dual type fuse box connector with 10' cord allows you to move around the vehicle shaking testing wires while looking for the short
- No wasted fuses
- Includes 3 resetting breaker handles: 10, 15 and 20 Amp
- Use when installing radios, CD players, radar detectors and other accessory equipment
- Includes YA8005-7, YA8005-10, YA8005-15 and YA8005-20 in YA8005-PB storage case
- YA8005-5 Fuse Handle and YA8005-EXT are optional accessories for the YA8005 Kit and are not included

Max Fuse Buddy®

Packing: 1

EEFB315 Order NO.: 903046



- MAXI circuit testing capability up to 80 Amps
- Also works with ATC and mini circuits-includes adapters
- Large LCD display with analog bar graph
- Unit features peak hold functions
- One touch zero function
- Amps: 0-80 Amps DC
- Resolution: 0.1A
- Accuracy: +2.0% of reading + 4 digits
- Power by: 9 volt Battery





Automatic Meter

Order NO.: 903043

Meter Manual Ranging

MT501C

Meter Autoranging

MT574C

Packing: 1

MT454C

Packing: 1

Order NO.: 903042

Packing: 1



- The MT454C is a durable, easy to use compact size digital multimeter
- Include:
- Compact size fits comfortably in the palm of your hand
- Easy-to-read 4000 count digital display
- Automatically selects the correct function of DC Volts. AC Volts or Ohms (Resistance)
- Use DC Voltage ranges to verify that the proper voltage level is arriving at a sensor or circuit
- Measure ohms to determine resistance of a coil
- Also test resistance of fuses, fusible links, components and circuits
- Measure AC voltage signals on digital MAF sensors, wheel speed sensors and vehicle speed sensors
- Protective boot with tilt stand, test leads. battery and instruction manual included
- Five year limited warranty



- Ergonomic, compact size fits comfortably in the palm of the hand
- Measure Ohms to determine resistance of a coil or spark plug wire
- Also test continuity of fuses, fusible links, components and circuits
- Use DC voltage ranges to verify proper voltage level is arriving at a sensor or circuit
- Large, easy-to-read, 2000 count LCD display
- Lock readings on display with data hold
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Added protection against drops and the elements with included rubber boot
- Safety cULus 3111 Listed. Meets CE and IEC 1010 safety standards
- 5 year limited warranty



- The MT574C offers both automatic and manual ranging
- Measure Ohms to determine resistance of a coil or spark plug wire
- Use the diode function to test the diode pack on a typical alternator
- Use DC voltage ranges to verify proper voltage level is arriving at a sensor or
- Large, easy-to-read, 4000 count LCD display with low battery indication
- Lock readings on display with data hold
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Measure DC current to determine presence of a parasitic load
- Added protection against drops and the elements with included rubber boot
- Safety cULus 3111 Listed. Meets CE and IEC 1010 safety standards
- 5 year limited warranty

Specifications.	MT454C	MT501C	MT574C
Display Count	4,000	2,000	4,000
AC Volts	600	600	600
DC Volts	600	600	600
Basic DC Accuracy	0.50%	0.75%	0.30%
AC Amps	_	_	400mA
DC Amps	_	_	400mA
Resistance	40M Ohm	2K Ohm	40M Ohm
Auto Range	Yes	_	Yes
Data Hold	_	Yes	Yes
Min/Max	_	_	Yes
Auto Power Off	Yes	-	Yes
CE or UL Listed	CE, cULus 3111	CE, cULus 3111	CE, cULus 3111
CAT Rating	CATIII 600 Volt	CATIII 600 Volt	CATIII 600 Volt









5 Pin Trailer Light Tester

Packing: 1

TLT5

Order NO.: 903047 Packing: 1

Trailer Circuit

Packing: 1

Order NO.: 903049



- Easily locates electrical problems in the tow vehicle
- Checks 7 pin round trailer connectors with LED indicator lights
- Tests left and right signals, brake lights and running lights
- Applications include newer light trucks and SUV's

• Easily locates electrical problems in the tow vehicle

- Checks both 4 and 5 pin flat trailer connectors with LED indicator lights
- Tests left and right signals, brake lights and running lights
- Unique and durable design allows user to leave the tester in line to continuously monitor the lighting system on the tow vehicle

6 Pin Trailer Light Tester

Packing: 1

TLT6 Order NO.: 903048



- Easily locates electrical problems in the tow vehicle
- Checks 6 pin round trailer connectors with LED indicator lights
- Tests left and right signals, brake lights and running lights

Dual 12V Trailer Plug Adaptor

Packing: 1

TLT8003 Order NO.: 903051



- Converts 12 volt feed at the back of a truck or SUV trailer socket and to a dual 12 volt power outlet
- Powers 12 volt test equipment, charging equipment and work lights in shop environment
- Recreation purposes such as running air pumps, radios or TV's while tailgating and camping
- Dual 12 volt power supply sockets
- Plugs into any 7-way spade pin trailer connection
- Use as 12 volt feed for diagnostic equipment
- Convenient power source for accessory plug-ins
- Both shop and recreational uses
- Includes dust cover to help prevent corrosion



Packing: 1

TLT8000 Order NO.: 903050



- Applications include medium/light duty trucks, 1/2 ton, 3/4 ton and 1 ton pickups, campers, and other heavy duty applications
- Adapts 7 way connection to 6 round pin and 4/5 pin connections
- Sealed plugs to keep road debris from corroding connections
- One adaptor for all your trailer needs
- Made from strong nylon 6
- Winged grip for easy installation and removal

Gas Cap Adaptor

Packing: 1

EELDGASCAP1 Order NO.: 903053



- Quickly pops-on virtually any filler neck
- · Costly replacement seals are no longer needed
- One size fits all (new model vehicles may be subject to change)



YA76462

Order NO.: 903058

Shop & Technician Tools Automotive Specialty Tools

Mini Engine Electronic Stethoscope

Packing: 1



RTEMPB3A

YA76562

Order NO.: 903052

Order NO.: 903055



- Sensor clamp helps to detect noises during test drives that can not be duplicated in the work bay
- Sensor tip mounted on 6" flexible shaft allows access to hard-to-reach areas
- 5" inductive metal probe allows user to pinpoint source of noise or
- Ultra sensitive microphone provides a full range of sound
- Rotary volume control allows easy adjustment
- Ear-bud style earphones provide excellent sound quality

Infrared Thermometer

Packing: 1



- Temperature range of -58° to 932°F (-20°C to 500°C)
- Use for most automotive and industrial applications requiring an infrared thermometer
- Compact size of 5.88" x 3.62" x 1.38" (149.2 x 92.1 x 34.9mm)
- Laser targeting accuracy
- Enhanced backlit 4 digit LCD for easy viewing
- Automatic power-off after 10 seconds
- Nylon holster for transport and safe storage
- Safely monitor hot, hazardous, or hard to reach materials without contamination or damage to the surface
- Simply point at target, pull the trigger, and read the temperature on the large, backlit LCD display

Probe, Coil-On-Plug

Packing: 1

- Super bright KV & ARC indicator LEDS
- 7" signal receiver probe
- Battery operated
- Sensitivity thumb-wheel

Universal EFI Quick Probe

Packing: 1



- · Quickly detects electronic fuel injector functions on any gas or diesel engine
- Specifically designed to detect the vibrations emitted when the electronic injector fires
- No hunting for injector wires to test at the connector
- No need to remove the injector for testing
- Super bright LED strobe
- 7" removable probe tip
- Battery operation
- Sensitivity thumb wheel

Terminal Tool Kit

Packing: 1

TT12KT Order NO : 903057



- Applications include most GM and other domestic computer connectors and terminals. Individual handles for easy assess in tight places. Designed for weather pack and pack-con terminals with flat blade to open connectors and fork for ALDL connectors to access trouble codes. Color coded: Red handle for GM and Green for wire terminal tools. Includes storage case
- Kit includes these GM C3 System Terminal Tools (red handle): Tube, Spring Loaded, 3.3mm x 28mm

Square Blade, 1.4 x 19.00mm

Flat Blade, 1.5 x 24.75mm

Flat Blade, 2.0 x 23.00mm

Fork Blade, 8.0 x 24.00mm

Flat Blade Screwdriver, 3/16" x 1.00"

• Kit includes these Wire Terminal Tools (green handle):

Tube. 3.30 x 28.0mm

Tube, 4.30 x 13.0mm

Tube, 3.75 x 13.0mm

Tube, 3.00 x 13.0mm

Flat Twin Blade, 3.0mm Flat Twin Blade, 1.6mm









Line Clamp Set

Packing: 1

HCP3KT

Order NO.: 903005

Master Line Disconnect Set

Packing: 1

I DT8

Order NO.: 903059



- HCP6A, HCP7A and HCP10A (6", 7", 10") in storage pouch **HCP6A Hose Pinching Pliers**
- For sealing hose sizes 1/8" to 5/16"
- Also use on brake lines, fuel lines and vacuum hoses

HCP7A Hose Pinching Pliers

- For sealing hose sizes 1/2" to 3/4"
- Also use on heater hoses and vacuum lines
- 7" long

HCP10A Hose Pinching Pliers

- For sealing hose sizes 3/4" to 2 1/4"
- Also use on radiator hoses
- 10" long

Portable Booster Pack

Packing: 1

EECS1AP

Order NO.: 903151



- Starting current: 660AMP
- Peak current: 1200AMP
- 12V/22AH Sealed Lead-acid batteries
- With 12VDC 15A cigarette lighter socket
- Automatic circuit overload protection
- 100% Copper 4GA Heavy Duty Jump Cable

Master Plus Disconnect Set

Packing: 1

I DT14

Order NO : 903006



- LDT14 contains all tools from the popular LDT8, Master Disconnect Set; in addition the kit has:
- The two most popular Jiffy-tite Disconnect tools
- The new blue 5/16"fuel line adapter
- A set of 4 air line push-pull disconnect tools that work on heavy duty trucks and industrial applications
- Label inside cover of carrying case shows images and applications



- A complete set of disconnect tools for spring lock and quick disconnect couplings used on air conditioning and fuel lines on Ford, GM and Chrysler vehicles
- Includes a set of six standard disconnect tools (5/16", 3/8", 1/2", 5/8", 3/4" and 7/8") and six color coded, angled disconnect tools for use in tight spots
- SPECIALIZED GM APPLICATIONS:

Includes tools for use on GM 3/8" flex fuel capable fuel filter removal plus 5/16" and 3/8" GM fuel modules

• SPECIALIZED FORD APPLICATIONS:

Includes tools for use on 3/8" and 1/2" Ford transmission and cooler lines with stepped line plus 5/16" x 3/8" scissor disconnect and Ford coupler disconnect tools

Battery System Tester

Packing: 1

YA2612B

Order NO.: 903061



- No conversion tables needed for CCA, SAE, IEC, EN, or Ah
- Battery condition is shown in % of capacity
- Uses conductance technology
- Tests 12V starting/charging systems
- Tests both flooded lead acid and AGM batteries
- Multi-colored bar graph displays battery condition
- Low voltage indicator LED lights when charging is necessary
- Bad cell is detected and displayed
- Comfortable grip with easy to use clamps
- Tests discharged batteries
- Patented circuitry
- Reverse polarity protection
- Made in USA

Terminal Brush

Packing: 1

BTC3A



- Stiff wire bristles thoroughly clean posts and clamps
- 3 3/8" long





Battery Carrier

Packing: 1

BL1B Order NO.: 903064



- For top post and side terminal batteries
- Rubber pads securely grip battery widths from 5" to 7"
- Plastic hand grip provides a firm hold

Manifold Repair Kit

Packing: 1

ACT1234PKT Order NO.: 903065



- Includes various replacement lens, knobs, O-rings, gaskets and
- Kit components are used to service ACTR41511

Manifold Set

Packing: 1

ACTR4131A Order NO.: 903066



- Anti-flutter gauges smooth out needle movement
- Easy grip all metal side mounted knobs
- Piston type free floating valves reduce O-ring wear
- Manual R134a couplers
- Gauges can be recalibrated to maintain accuracy
- 60" inner nylon layer hoses meet EPA, SAE, and UL standards
- Yellow hose includes shut off valve

UV Leak Detection Flashlight Kit

Packing: 1

ECFUVLITE Order NO.: 903068



- High intensity LED bulb with 100,000 hour service life
- Over four hours of peak performance per charge
- Power comparable to high intensity 75 watt lamps
- Compatible with all standard leak detection dyes
- Inspection range of up to 6'
- Three "AAA" batteries and fluorescence enhancing glasses are included

Replacement Hose (R12)



Stock No.	i i	Order No.
ACTB72	1	903069
ACTY72	1	903078

ACTB72

- 1/4 turn manual shutoff valves
- Blue, 6' length

ACTY72

- 1/4 turn manual shutoff valves
- Yellow, 6' length

Replacement Hose (R12)



Stock No.	I	Order No.
ACTB72A	1	903070
ACTY72A	1	903079

ACTB72A

- Automatic shutoff valves
- Blue, 6' length

ACTY72A

- Automatic shutoff valves
- Yellow, 6' length







Replacement Hose (R134a)



Stock No.		Order No.
ACTRB72	1	903072
ACTRR72	1	903074
ACTRY72	1	903076

Low permeation hoses for internal equipment connections

ACTRB72

Blue, 6' length

ACTRR72

• Red, 6' length

ACTRY72

• Yellow, 6' length

Replacement Hose (R134a)



Stock No.	i i	Order No.
ACTRB96	1	903073
ACTRR96	1	903075
ACTRY96	1	903077

Low permeation hoses for internal equipment connections

ACTRB96

Blue, 8' length

ACTRR96

• Red, 8' length

ACTRY96

Yellow, 8' length

Manual A/C Hose Crimper

Packing: 1





- Unit is easily mounted to bench with holding fixture or held securely in a vise
- Includes a complete set of dies covering standard #6, #8, #10 and #12 hose sizes
- Includes storage case

Thermometer

Packing: 1



- Range 0° F to 220° F (-18° C to 105° C) in 2° increments
- Checks temperature of condenser, outside air, and cooling power



- Range 0° F to 220° F in 2° increments
- Storage case
- Stem should be immersed about 2" in liquids, 4" in gases

Pocket Digital Thermometer

TEMP10 Order NO.: 903082

ACT73A

Order NO.: 903080

Packing: 1



- Measures liquid, air and surface temperatures via sturdy stainless steel probe
- Digital display for easy viewing
- Angle viewing head can be lifted and rotated 180° for a different viewing angle
- Convertible from Fahrenheit (F) to Centigrade (C) temperature ranges
- The -58° F to 300° F (-50° C to 150° C) temperature range enables use on a wide range of applications
- Tactile on/off button for easy operator use (auto off function extends battery life)
- Tactile data hold button holds the reading when the display cannot be seen
- Temperature range noted on bevel
- Plastic carrying sheath protects the user when carried in shirt pocket

Fin Straightener & Cleaner

Packing: 1

ACT407 Order NO.: 903083



- Multi-head tool handles 8, 9, 10, 12, 14, and 15 fins per inch
- 4 1/4" long





Spanner Wrench Packing: 1

ACT499A Order NO.: 903084



ACT1009A Order NO.: 903087



- Adjustable three stud design for GM R-4 compressors
- Also has applications on some GM, Warner, Pitts, and Ogura clutches



- Use as CCOT and FFOT screen extractor
- Use in conjunction with ACT106B
- Manual shut-off valves

Core Service Tool

Packing: 1

ACT81290 Order NO.: 903085



• Use on R12/R134a standard valve cores and JRA/EATON large bore R134a valve cores

Flush Kit

Packing: 1



ACT1046C Order NO.: 903088




ACT1008A Order NO.: 903086

ACT106B

Order NO.: 903089



- Services A/C systems
- Manual shut-off valves



• Designed to work with any lightweight flushing material that can be mixed with pressurized air

Includes flush gun, hose, canister, and canister adaptor


- 6 1/4" long

Spring Lock Coupler Set

Packing: 1

ACT118B Order NO.: 903091





Color coded:

Red, 3/8"

Blue, 1/2"

Black, 5/8"

Beige, 3/4"





- For most GM models
- 4" long
- Manual shut-off valves







Oil Injector Adaptor

Packing: 1

ACT111B Order NO.: 903090



- Has an aluminum body and holds up to 2 oz. of oil
- Uses pressure differential of the high and low side of A/C system

Quick Connect Set

Packing: 1

ACT119 Order NO.: 903092



- Simplifies connecting to core valve service fittings
- Includes both a straight coupler and a 90° coupler that accept either of two adaptors (one for low side, one for high side)
- Manual shut-off valves

Gas/Diesel Combustion Leak Tester

Packing: 1

GDCT16 Order NO.: 903095



- Provides an easy and quick way to diagnose engine overheating problems
- Checks for leaks between the combustion chamber and the cooling system
- Test head and gasket for combustion leaks before removing the radiator
- Double chamber in testing unit provides a high level of accuracy
- For use on water cooled gas and diesel engines
- Kit includes complete test chamber, 16 oz. bottle of testing fluid and instructions

Universal Valve Core Service Tool

Packing: 1

ACT1290A Order NO.: 903093



 Removes and replaces standard size Schrader style valve cores plus the larger size found in GM systems

Disconnect Set

Packing: 1

ACT1370 Order NO.: 903004



- Set includes six tools for disconnecting spring couplings on fuel lines
- Convenient plastic holder included
- Also useful on A/C spring couplings as well as push lock connectors on radiator and transmission lines
- Includes six tools for disconnecting spring couplings on Ford, GM, and Chrysler A/C lines
- Works on fuel lines and can be used as push lock connectors on radiator and transmission lines
- Included sizes are 5/16", 3/8", 1/2", 5/8", 3/4" and 7/8"

Cooling System Adaptor Set

Packing: 1

SVTAB1400



- TAB Series Adaptors feature a composite metal/plastic construction for a lower cost option
- Set includes 14 radiator composite metal/plastic radiator adaptors
- Includes all TAB Series Adaptors plus TA4503 Adaptor
- PBSVTA1417 Storage Case has a removable cover for display purposes





YA6160

Order NO.: 903099

Shop & Technician Tools Automotive Specialty Tools

Leverage Hose Cutter

Packing: 1

- (8 1/2") Compound action multiplies normal hand pressure to easily slice through many types of rubber and plastic hose up to 1 1/8" in diameter
- Includes stainless steel cutter blades and internal components

Antifreeze Hydrometer

Packing: 1

AF102 Order NO.: 903094

PWC60

Order NO.: 903097



- Degree of protection is indicated by direct reading-no temperature compensating scales are required
- Range of +32°F to -60°F
- Includes Celsius scale
- Tests hot and cold solutions

Cooling System Pressure Tester

Packing: 1

SVT275 Order NO.: 903098



- Inflatable bladder sealing system enables use with most passenger and light commercial vehicles
- Tests header tanks and radiator systems as well as thread type and bayonet-style caps
- Locate leaks from head gaskets, radiator and heater cores, Welch plugs and housings, water pumps and hoses
- Test cap relief pressure and seal condition
- Suitable for marine applications
- Fluid drain tube allows coolant to be returned to reservoir or safely collected for recycling
- Bladders are cycle tested to over 1,500 inflations

Fan Clutch Pulley Holder

Packing: 1



- Removes and replaces the fan clutch on vehicles using "bolt on" water pump pulleys
- Reverse pulley holder for assembly operations
- Use with YA9521 36/48mm wrench or YA9526 40mm wrench for many Chrysler, Ford, Lincoln, Mercury and GM applications

Tire Gauge and Inflator

Packing: 1

TPGDL1000A Order NO.: 903101



- Measures from 5 to 150 PSI
- Displays reading in psi, bar, kPa or kg/m²
- 1/4" NPT fitting for inlet air connection
- Shock proof rubber quard helps prevent damage if dropped
- On/Off button for display light
- Clip on air chuck
- Batteries included

Dial Tire Inflator / Gauge

Packing: 1

TIF160 Order NO.: 903153



- 1% accuracy allows for use on vehicles equipped with TPMS sensors
- Shorter hose and body length make this gauge ideal for use on cars and light trucks
- Rugged dial and plunger style mechanism preserve gauge accuracy when dropped
- Stainless Steel Braided Hose
- 6-160 PSI, 60-1100kPa











Pressure Gauge

Packing: 1

TPGIF1600 Order NO.: 903102



- 10 to 120 PSI in 2 pound increments 1/4"
- 1/4" FNPT air inlet fitting
- Swiveling hose for easy gauge positioning
- Zinc body with heavy duty brass valves
- Easy to read sight glass featuring PSI and kPa readings

• Measures to a depth of 1" in 1/32" increments

Plastic body with aluminum probe and sliding gauge

Includes pocket clip

Tread Depth Gauge

Packing: 1

Pressure Gauge

Packing: 1

TPGP120 Order NO.: 903103



- Calibrated in 2 psi increments from 20 to 150 PSI and in 10 kPa increments from 150 to 800 kPa
- Chrome plated
- 5 3/4" long

Valve Stem Inserter

Packing: 1

VT1A

GA599A

Order NO.: 903100

Order NO.: 903001



- Simplify installation of valve stem in tubeless tire rim
- Shank is notched to accommodate various rim styles
- Has a comfortable, screwdriver type handle
- 12" long

Universal Valve Core Tool

Packing: 1

VT14 Order NO.: 903104



- Double ended wrench removes and installs large and small valve
- Reverse the double ended wrench in the tool body to fit both large and small valve cores
- Use the cup end to remove valve caps
- Valve Stem Inserters
- Simplify installation of valve stem in tubeless tire rim
- Shank is notched to accommodate various rim styles
- Has a comfortable, screwdriver type handle
- 12" long

1/2" Torque Stick Set, 5 pcs

Packing: 1

BTQS500



- Entry level set covers the most popular models
- Size ranges from 19 to 22mm
- Torque range from 80 to 147 ft. lbs
- 1/2" drive
- Includes BTQS12B, BTQS12BB, BTQS12C, BTQS12EE and BTQ12SI (5 pcs) in BTQSCASE storage case





1/2" Torque Stick Set, 6 pcs

BTQS600

Inner Tie Rod Tool

Packing: 1

YA3000C Order NO : 903110



Order NO : 903106



- Set contains sticks to compliment the BTQS1000 set to cover any applications you may still have
- Size ranges from 17 to 22mm
- Torque range from 55 to 113 ft. lbs
- 1/2" drive
- Includes BTQS12AA, BTQS12F, BTQS12G, BTQS12H, BTQS12K and BTQS12MM (6 pcs) in BTQSCASE storage case



- Designed to remove tie rods lacking a full hex on the socket end
- Removable crowfoot adaptors are placed on hex of tie rod
- Tool then engages crowfoot for removal or installation of tie rod
- Includes crowfoot adaptors in 1 3/16", 1 1/4", 1 5/16", 1 7/16", 1 1/2" and 33.6mm sizes

1/2" Torque Stick Set, 10 pcs

Packing: 1

BTQS1000 Order NO.: 903107



- Master set covers the majority of domestic and foreign cars and light trucks
- Size ranges from 19 to 24mm
- Torque range from 80 to 160 ft. lbs
- 1/2" drive
- Includes BTQS12A, BTQS12B, BTQS12BB, BTQS12C, BTQS12E, BTQS12EE, BTQS12I, BTQS12T, BTQS12XX and BTQS12Y (10 pcs) in BTQSCASE storage case

Inner Tie Rod Tool

YA3100 Order NO.: 903111

Packing: 1



- Use on inner tie rods with inaccessible wrench flats found on many trucks and SUV's
- Large inner tie rod tool includes 4 crowsfoot wrenches: 1 7/16", 33.6mm, 38.4mm and 42mm
- The long socket slips over the tie rod end and the crowsfoot engages on socket for easy removal and installation
- Applications include many Toyota, Nissan, Ford, Lincoln Mercury and Chevrolet truck and SUV's
- Also fits some Cadillac Escalade, Hummer H2, Honda Passport and Jeep Liberty

Wheel Lock Kit

LSR1000A

Packing: 1

Order NO.: 903108



- Wheel Lock Removal Socket Set
- · Easily removes most lug nuts and wheel locks on most domestic and import passenger vehicles and light trucks
- Use with hand driver or impact wrench
- Some sockets cover specific GM, Ford and Chrysler applications
- Set includes 11 sockets, extension and extractor punch in storage

Inner Tire Rod Tool

Packing: 1

YA3500





- Removes inner tie rods equipped with completely round end sockets
- Designed to remove and install all inner tie rod sockets up to 1 31/64"
- Wrench head has 3 set screws that tighten against the socket
- Includes 1/4" short head hex wrench





Master MacPherson Strut Tool

MSC₁ Order NO.: 903007



- Designed to quickly and easily compress most MacPherson strut
- Compresses up to 5/8" (.625mm) coil diameter
- Broad spring contact for stable compression
- Acme threaded rod and built in detent latches to help lock coil in place
- Forged construction for strength and durability

Coil Spring Compressor

MSC2

Order NO.: 903112



- Removes and installs coil springs quickly and safely
- Compresses coil springs on all passenger cars and pick up trucks
- Features Acme threaded rod

Cam Lock Tool Set

Packing: 1

Packing: 1

ML6000COMBO Order NO.: 903118



- Includes (4) CC100 Single Cam Clamps and (1) ML6000 Dual Cam Clamp in storage tray
- Single cam clamp can be used on engines where the dual clamp will not fit
- Compact design permits easy operation in confined engine areas
- Simple and easy to use
- Manufactured from high strength industrial polymers which will not corrode or damage engine pulleys
- Dual cam clamp prevent engine damage resulting from incorrect timina
- Maintain valve timing during belt replacement on twin and quad cam engines
- Compact design allows access in transverse engines
- Fits timing gear diameters from approximately 4" (101mm) to 6" (152mm)
- Fits gear spacing from approximately 0.06" (1.6mm) to 3" (76mm)

Manual Fluid Dispenser

Packing: 1

VAC201 Order NO.: 903113



- Easily remove engine oil, gear and transmission oil, coolant and brake fluids
- Unit creates vacuum or pressure providing a clean, fast and simple way to evacuate or dispense a wide range of fluids
- Automatic shut off prevents the overflow of the reservoir tank with shut off at 8 liters
- 2.3 gallon (8.8 liter) total capacity
- Durable polyethylene construction is impervious to automotive and house hold chemicals
- No electrical or compressed air required
- Sturdy base with exterior pump helps prevent evacuator from tipping
- Complete system includes manual fluid evacuator, main hose assembly (5/16" ID x 54" long) plus two rigid dipstick tubes for engine oil removal (3/16" ID x 34" and 1/8" ID x 34")

Strap Wrench

Packing: 1

A91F Order NO.: 903114



- Use on large diameter oil filters 1 to 6"
- Includes both 3/8" and 1/2" square drives

Oil Filter Pliers, Adjustable

YA4274

Packing: 1



Order NO : 903008

- Use on filters from 2 1/2" to 5 1/4" diameters
- Use on automotive and truck applications
- · Spring action size adjustment assures a solid grip on filter
- Offset handle offers increased accessibility
- Heavy duty forged levers
- Cushioned grips for comfort
- Industrial black finish with blue grips
- Overall length of 13 1/2"





Oil Filter Pliers, Extra Large

YA4275 Packing: 1 Order NO.: 903115



- Use on filters from 4 1/4" to 7" (108-178mm) diameters
- Applications include truck, tractor and high torque diesel engines
- Spring action size adjustment assures a solid grip on filter
- Offset handle offers increased accessibility
- Heavy duty forged levers
- Cushioned grips for comfort
- Industrial black finish with blue grips
- Overall length of 19" (482.6mm)

Oil Filter Wrenches

Packing: 1 Order NO.: 903108



Stock No.	Size (mm)	Steps	Flats	Style	I	Order No.
FW656714A	65, 67	2	14	Cup	1	903009
FW757715A	75, 77	2	15	Cup	1	903010
FW7630A	76	1	30	Cup	1	903011
FWA62121A	62, 121	_	_	Adjustable	1	903012

Stock No.	Square Drive (inches)	Application
FW656714A	3/8	Fram-PH4386, PH4967, PH6017, PH6018, PH6607
FW757715A	3/8	NAPA, AC Delco, Castrol, STP, Penske
FW7630A	3/8	Fram, IAPCO, Motorcraft, Parts Plus, Pennzoil
FWA62121A	3/8	Adjustable filter wrench for 62 to 121mm diameter oil filters, 3/4" external hex

Funnel Packing: 1

FUNN15 Order NO.: 903116



- High visibility red funnel for large neck fillers
- Both ends of the funnel have screw on caps to contain fluids if needed
- 1.5 qt. capacity

Oil Filter Wrench Set, 7 pcs

Packing: 1

FWK7A Order NO.: 903013



- Wrenches in set cover 95% of domestic and import automobile and light truck oil filters
- Storage/carrying case keeps wrenches together for quick access and contains any oil residue keeping it out of your tool storage unit
- · Includes laminated application chart
- FWK7A set includes FW656714A, FW757715A, FW7614A. FW7630A, FW8015, FW9315A and FWA62121A oil filter wrenches

Grease Gun

Packing: 1

GA472

Order NO.: 903014

13 ¹/4"

3 1/2"



- Standard series grease guns
- All are steel with zinc plating
- Inner-spring chamber can be either cartridge or bulk loaded

Grease Gun, Lever

Packing: 1

YA728A Order NO.: 903022



Specification	PSI	Nozzle
Lever	6,000	_
Capacity	Flexible Hose	Rigid Extension
16 oz. Bulk and 14 1/4 oz. Cartridge	18"	6"
	Loading	
	Bulk or Cartridge	

- Lever operated, large capacity gun accepts 16 oz. bulk or 14 1/4 oz. cartridge grease
- Develops 6,000 PSI
- Includes tough, 18" flexible whip hose with coupler and 6" rigid extension











Grease Gun, Pistol

Packing: 1

YA734A

Order NO : 903017

H

Specification	PSI	Nozzle
Pistol Grip	6,000	_
Capacity	Flexible Hose	Rigid Extension
16 oz. Bulk and 14 1/2 oz. Cartridge	18"	6"
	Loading	
	Bulk or Cartridge	

- Develops 6.000 PSI maximum pressure
- Pistol grip unit features suction, cartridge, or filler pump loading
- Includes flip over follower, 18" flexible hose, 6" rigid extension and hydraulic coupler

Grease Gun, Air

Packing: 1

YA772B

Order NO.: 903016



PSI	Air Operating PSI	Pump Ratio		
4,000	60 - 150	40:1		
Capacity	Flexible Hose	Rigid Extension		
14 oz. Cartridge	18"	6"		
Loading Nozzle				
Bulk, Filler Pump, or Cartridge —				

- Automatic operation provides continuous grease flow with trigger depressed
- Pumps at a 40:1 ratio with a maximum pressure of 6,000 PSI
- Use with standard 14 oz. cartridge, bulk fill or filler tube
- Heavy duty 18" flexible nylon hose improves accessibility and reach
- Air vent allows easy removal of trapped air after loading grease tube
- Light weight of 3.52 lbs
- Helps reduce operator fatigue

Accessory Pack, Grease-dispensing

Packing: 1

YA7500

Order NO.: 903015



 Includes 10 pcs. as follows in a storage tray Universal swivel

Needle nozzle coupler

Flex whip hose 12"

Flex whip hose 18" (for manual grease guns)

Flex whip hose 18" (for powered grease guns)

Heavy duty coupler

Swivel coupler

Coupler

Coupler extension

Angle lube adaptor



- For powered and hand operated grease guns
- 1/8" NPT(m) both ends
- 4,500 maximum PSI
- 12" long





- 1/8" NPT(f.) thread
- 2 3/4" long



- For universal joint fittings, water pumps, and metal covered springs
- 4 7/8" long



- 16 oz. capacity
- Fast, clean method for removing or adding transmission and gear oil
- Special follower is impervious to oil, grease, and water
- Flexible nozzle





Serpentine Belt Tool Kit YA9350B Packing: 1 Order NO : 903119 *****

Hex Applications

YA9350-6 (13mm or 1/2") - GM "Quad 4" 2.3L and Volkswagen 2.0L YA9350-2 (14mm) - Isuzu 3.1L, Lexus (2.5L, 3.0L, 4.0), Mazda (2.3L, 3.0L, 4.0L), Saturn 1.9L with 4mm hex on idler pulley, Toyota 3.0L, Volkswagen (1.8L, 2.5L, 2.8L)

YA9350-8 (15mm) - GM 2.2L, Isuzu 2.8L, Jeep 4.7L YA9350-7 (16mm or 5/8") - Ford/Lincoln/Mercury (2.3L, 3.8L, 4.0L, 4.9L, 5.0L, 5.8L), GM (4.3L, 5.0L, 5.7L) YA9350-3 (18mm) - GM (2.0L, 3.1L, 3.3L, 3.4L, 3.8L)

YA9350-9 (19mm or 3/4") - Mercedes (use with 15mm adapter for extra reach), Toyota (1.8L, 2.4L)

Wrench Only - Dodge/Chrysler/Plymouth (3.0L, 3.3L, 3.9L) (has 15mm drive), Ford/Lincoln/Mercury (2.3L, 3.0L, 3.8L)

Square Applications

YA9350-4 (3/8") - Ford/Lincoln/Mercury (1.9L, 2.3L, 2.5L, 4.0L), GM (2.0L, 2.2L, 2.8L, 3.1L, 3.4L), Isuzu (2.8L, 3.1L) YA9350-5 (1/2") - Dodge/Chrysler/Plymouth (2.0L, 3.0L), Ford/ Lincoln/Mercury (2.3L, 3.0L, 4.2L, 4.6L)



- Works on all serpentine belts
- Clamping jaw allows user to position serpentine belt without the belt slipping out of the tool
- Positive grip allows belt routing in tight access areas that would normally be difficult to reach
- Ergonomic handle provides comfort and ease in use, acting as an extension of the user's hand
- Lightweight steel body for durability and strength

Valve Spring Compressor

CF700B

Order NO.: 903121

Packing: 1

- 7/8" to 2 1/2" capacity
- Operates on 90 PSI to 150 PSI, but develops up to 3 times output pressure
- Tool measures 1" x 8"

C-Clamp Compressor

Packing: 1



- 1" to 2" capacity
- For "L" head, valve-in-head, high compression engines and vehicles with overhead valves
- Activating mechanism prevents cocking of valve spring as it is compressed

C-Clamp Compressor

CF19R Order NO.: 903123

Packing: 1



• This compact model includes CF19-3A Jaws for 1/4" to 1 1/16" diameter springs on small, air cooled engines and CF19A5 Jaws for both 17mm and 20.8mm diameter springs on Honda engines

Brake Bleeding Kit

Packing: 1



BB500 Order NO.: 903028

• Kit includes BB5001 Vacuum Brake Bleeder and BB5002 Auto Refiller **Bottle**

BB5001 Vacuum Brake Bleeder:

- Large 3-pint (1.5 liter) container
- Generates 25 in Hg vacuum with air pressure of 100 psi
- On/OFF valve and flow regulator
- Quick release locking trigger, safety shut off valve and overfill check valve
- Compact design fits under wheel well
- 19.5" (500mm) suction hose
- Universal brake screw fitting

BB5002 Auto Refiller Bottle:

- 20 fluid oz (592 ml) container
- Automatically keeps the reservoir filled to the correct level
- Retaining clip for positive attachment
- Compact design fits under hood
- Positive venting system supplies continuous flow
- Unit can be sealed when not in use to prevent spillage





Air Adjusting Valve, with Gauge

🃦 Packing: 1



- Designed for use with HVLP spray guns
- Includes 160 PSI pressure gauge
- Air Inlet: 1/4" M.P.T
- Air Outlet: 1/4" F.P.T. (swivel nut)

Seal Pliers

Packing: 1



YA8230 Order NO.: 903023

BF555

Order NO.: 903145

- Removes valve stem seals from overhead camshaft engines including 4 valve per cylinder engines that have restricted access to the valve stem seal due to the head design
- Gripping serrations in the pliers tip easily grab both OEM and aftermarket seals with ease
- Easy grip handles

Ring Compressor Set

RC980

Order NO.: 903124

Packing: 1



- Works both horizontally and vertically with pliers grip handle
- Has a fine tooth ratcheting mechanism
- Includes 6 hardened steel bands:
 2 7/8" to 3 1/8", 3 1/8" to 3 3/8", 3 3/8" to 3 5/8", 3 5/8" to 3 7/8", 3 7/8" to 4 1/8", and 4 1/8" to 4 3/8"

Bearing Race and Seal Driver Set

Packing: 1

A1310A Order NO.: 903125



- Collars fit most standard wheel bearing sizes
- The three largest sizes fit most late model 4 wheel drive vehicles

Ring Compressors



Stock No.	Band	Capacity (inches)	Deep (inches)		Order No.
RC40C	2	$2^{1/8}$ to 5	3 1/2	1	903024
RC50C	2	3 ½ to 7	3 1/2	1	903025

- Clutch control holds tension band in position as piston is inserted into cylinder
- 1/2" wide spring bands equalize tension over belt width so ring assembly may be compressed into groove until flush with piston
- "V" beads on lower edge of belt keep tool from entering cylinder
- RC40C can be used upside down for Chevrolet, Mercury, and Ford trucks with angled blocks

Rotor Micrometer

Packing: 1

RM130 Order NO.: 903030



- Range of .30" to 1.3" in .0001" graduations
- 3.5" deep frame
- Pointed anvil for checking grooves
- Includes 1" checking standard and storage case

Oval Tube Creeper

Packing: 1

JCW8A Order NO.: 903126



Pad Color	Overall Size (inches)	Pad Length (inches)
Black	40 (L) x 17 (W) x 4 (H)	39
Pad Width (inches)	Number of Casters	Caster Diameter (inches)
11	4	2 1/2

- 40" long creeper is constructed of 16 ga. steel and has a unique drop in the shoulder area to provide for generous shoulder clearance; low 3/4" ground clearance
- Fully padded with heavy duty foam for durability; pad measures 1 3/4" thick, headrest pad measures 2 3/4" thick covered with heavy duty vinyl
- Four 2 1/2" oil resistant, full ball bearing casters
- Weight is 18 lbs





Brake Spring Tool

Packing: 1

BT9 Order NO.: 903127



- Quickly and easily removes or replaces springs
- Allows mechanics to press spring into place with one simple motion, taking the place of the slide mechanism
- Includes two mechanisms to allow easy removal and replacement of springs on brakes
- Patent pending
- 8 3/4" long

Air Riveter

Packing: 1

HP301C

Order NO.: 903133



Recommended Air Pressure (psi)	Air Consumption, average cfm (scfm) [l/min]
85-95	_
Air Inlet Thread Size	Traction Power (lbs)
1/2" NPT	3,300
Stroke	Weight (kg.)
⁵ /8" (15.8 mm)	3.0

- Sets structural rivets, KLIK-FAST[®] rivets from 5/32" to 1/4" diameter in all alloys plus KLIK-SPLIT® / Monobolt rivets from 3/16" to 1/4"
- Includes 5/32", 3/16" and 1/4" nosepieces plus mandrel collection bottle

Brake Caliper Kit, 7pcs

Packing: 1

YA8610B Order NO.: 903033



- Assists in replacement of brake pads on most 4-wheel disc brake cars
- Tool and adaptors position brake piston back into caliper to allow clearance for newer, thicker brake pads
- Designed for most Audi, Chrysler Corporation, Ford, GM, Honda, Jaguar, Mazda, Mini Cooper, Mitsubishi, Nissan, Saturn, Subaru, Toyota, Volkswagen and Volvo
- Set includes one tool and seven adaptors in a storage case

Brake Caliper Press

Packing: 1

BTCP1

Order NO : 903032



- Works on both fixed and floating calipers
- Generates more than 1600 ft. lbs. of force to retract the toughest caliper pistons
- Single lever mechanism used to apply and release force for ease of operation and faster service
- Prevents damage to pistons, hubs or calipers
- Ensures parallel piston retraction on dual and quad piston calipers
- Easy left and right side use

Throttle Depressor Packing: 1

Order NO.: 903131

B240B



- Holds throttle at a constant RPM
- · Easily adjusts to desired length
- Adjustment screw fine tunes desired RPM
- Rubber tip keeps the tool firmly positioned on the accelerator pedal
- Overall length of 40" (102cm)
- Can also be used as a pedal depressor

Brake Gauge Set

Packing: 1



BTG8

Order NO.: 903130

- Color coded gauges provide instant feedback on brake pad/shoe
- Constructed from 20 gauge sheet metal with durable powder coat
- Pad/shoe condition is indicated with color by the respective testing gauge
- Red indicates service required, yellow indicates caution and green indicates an OK situation
- Set includes 8 different testing blades of various colors and thickness Red 2mm (0.0787")

Red 3mm (0.1181")

Yellow 4mm (0.1575")

Yellow 5mm (0.1969")

Yellow 6mm (0.2362") Green 8mm (0.3150")

Green 10mm (0.3937")

Green 12mm (0.4724")









HVLP Spray Gun



Stock No.	BLP13HVLP	BLP14HVLP	BLP15HVLP	BLP18HVLP
Fluid Tip (mm)	1.3	1.4	1.5	1.8
Air Consumption (scf m)	9.5	9.5	9.5	9.5
Max. Inlet HVLP psi (bar, kPa)	29 (2.0, 20 0)	29 (2.0, 200)	29 (2.0, 200)	29 (2.0, 2 00)
Dry Weight without Cup, oz. (grams)	12.6 (359)	12.6 (359)	12.6 (359)	12.6 (3 59)
Air Inlet Thread Size	1/4" NPSM	1/4" NPSM	1/4" NPSM	1/4" NPSM
Cup Size (cc)	600	600	600	600
Application	High solids, colors and clears	High solids, colors and clears	Medium solids, colors and clears	Primer, high viscosity materials
i i i	1	1	1	1
Order No.	903140	903142	903143	903144

1.0 Mini HVLP Spray Gun Packing: 1

BLP10MHVLP Order NO.: 903139



Fluid Tip (mm)	Air Co	nsumption (scfm)	
1.0	7.0		
Max. Inlet HVLP psi (bar, kPa)	Dry Weight without Cup, oz. (grams)		
29 (20, 200)	11.4 (322)		
Air Inlet Thread Size	Cup Size (cc)	Application	
1/4" NPSM	125	Primer, base and clear	

1.4 Conventional Spray Gun

BLP14CONV Order NO.: 903141





Fluid Tip (mm)	Air Consumption (scfm)			
1.4	9.5			
Max. Inlet HVLP psi (bar, kPa)	Dry Weight with out Cup, oz. (grams)			
_	12.6 (359)			
Air Inlet Thread Size	Cup Size (cc)	Application		
1/4" NPSM	600	All automotive colors and clears		

- Designed for the automotive refinishing painter, Blue-Point[®] spray guns are lightweight and feature great balance while delivering a quality, first class automotive finish
- A new generation of Blue-Point® spray guns for primer, base and clear coat
- Lowest trigger pull among guns in their class
- Unmatched spray pattern size and quality repair kits
- Optional interchangeable 125cc, 250cc and 600cc aluminum cups are available
- Optional 3M PPS adaptor is also available

1.4 HVLP Spray Gun Packing: 1

BLPK14HVLP Order NO.: 903138



Fluid Tip (mm)	Air Consumption (scfm)		
1.4	14.5		
Air Inlet Thread Size	AirPressure Range (psi)		
¹ / ₄ " NPSM	30 to 43		
Fluid (Water) Delivery	Cup Size (cc)		
190 to 250 ml/min	600		

- · Lightweight and comfortable for all kinds of painting jobs
- Provides superior spray performance
- Stainless steel needle and tip

Windshield Removal Tool

YA109C Order NO.: 903137






- Steel cable pull handle
- Replaceable steel cutting blades can be resharpened
- For GM, Chrysler, and other cars with windshields set in place with sealant

Brake Service Tools

YA4000B Order NO.: 903146

Packing: 1





- Comfortable ergonomic design
- One finger trigger vacuum/pressure release
- Durable, accurate diaphragm type pressure/vacuum gauge
- Handheld vacuum/pressure pump with 2" compound gauge and rubber boot
- 12 oz. fluid reservoir bottle with fluid transfer and storage lids plus fluid pick up tube
- 6 tapered adaptors for connecting to tubing from .09" to .50" ID
- 2 tapered manifold plugs
- 2 universal bleed screw adaptors
- 12 vacuum cap plugs, vacuum line T-adaptor
- (2) 1/4" ID x 24" long connection tubes with quick-change connector
- 5/32" ID x 1/4" ID tubing adaptor
- 5/32" ID x 3" long vacuum test tube
- Rubber cupped adaptor
- Master cylinder refill kit Applications:
- Vacuum and pressure related engine performance diagnostics and tune-ups
- Brake bleeding
- Fluid transfer, evacuation and sampling





Door Lockout Set


Packing: 1

LOS145A Order NO.: 903136

Thread Setter Kits



Stock No.	•	Order No.
HP650	1	903134
HP650M	1	903135



- Actuate the door handle, manual lock button or electric lock button on most cars and trucks
- Includes:
 - 4 pc door-unlocking tool that screws together without couplers for easy assembly and storage, plastic slim jim, 2 glow-in-the-dark tips, 2 plastic wedges to create gap between door and frame without damaging door or weather stripping and BF272 inflatable wedge
- Use the BF272 to easily separate door from body without damage to the vehicle
- Unlocking tool features a middle extension piece to reach across the car in extended use applications
- For sale to registered locksmiths, police and bona fide repair professionals only

HP650

- Includes: rugged thread setter tool and an assortment of fractional Klik Poly-Nuts: 12 each 8-32, 10-24, 10-32; (8) 1/4"-20 and (6) 5/16"-18 threads
- Includes required nosepieces and mandrels for setting the above
- Packaged in a storage case

HP650M

- Metric version of the HP650 with metric poly-nuts, including 25 each 4 and 5mm, (15) 6mm and (10) 8mm threads
- Includes thread setter tool, required nosepieces and mandrels packaged in a storage case

High Volume Hose Connectors









AHCC90C AHCC91C AHCCP90C AHCCP97C

Stock No.	Description	Size	•	Order No.
AHCC90C	Quick Coupler High volume ¹ / ₄ " female quick coupler	1 /4"	1	903147
AHCC91C	Quick Coupler High volume ¹ /4" male quick coupler	1 /4"	1	903148
AHCCP90C	Nipple (¹ / ₄ " Female) Quick connect ¹ / ₄ " female nipple	1 /4"	1	903149
AHCCP97C	Impact Wrench Adaptor	1 /2"	1	903150

AHCC90C AHCC91B AHCCP90C

• Designed to deliver high volumes or air to spray guns and air tools

 Use with AHCC98C high flow coupler to improve low pressure performance of 1 /2" drive impact wrenches and other high air comsumpition tools







Shop Equipment

Bringing on bigger sized gear, we have some heavier equipment further catering to automotive specialized needs. All equipment conform to Blue-Point's quality commitment, and complement the rest of our quality tools to be the number one choice in automotive tools.



Blue-Poin



Z_R
TM

Shop Equipment

160



Shop Equipment Shop Equipment



- Low Profile
- Dual hydraulic cylinders
- Soft rollers for smoother & silent operation



- Fast acting pump reaches lifting height in less than a pump to allow user to reach a variety of service height situations quickly
- One piece handle for professional users features a foam pad to limit damage to vehicles
- Universal joint release mechanism for smooth action
- Rolled side frames with generous flanges to resist flexing
- Low profile design allows for easy access under vehicles
- Floor Jack used to lift cars and light trucks
- Meets ANSI-PALD standards

Motorcycle Floor Jack

Packing: 1

YA1715

Order NO.: 904009



- 1,500 pound capacity
- Low height of 4 1/2", maximum height of 14 3/4"
- Wide base for extra stability
- Double rubber lined pad provides extra protection to motorcycle while on the jack
- Pull handle assists user to maneuver jack into position
- · One foot operation for ease of use
- Safety straps to secure motorcycle to jack
- Self locking safety feature and overload safety valve

12 Ton Jack Stands

YA512 Order NO.: 904006

Packing: 1



YA512	12 (per pair)	17 ^{1/2}	27 ^{1/2}
Stock No.	Capacity (tons)	Low Height (inches)	Maximum Height (inches)

- Counter-weighted pawl serves as a secure locking device to prevent the load from accidentally disengaging
- Sturdy, welded steel construction for superior strength
- One piece, multi-position ductile ratchet bar provides super strength and durability and quick adjustment mechanism that securely locks into desired location

Automotive Jack Stands

YA874BP Order NO.: 904012

Packing: 1





Stock No.	Capacity (tons)	Max. Height	Min. Height	COO	
YA874BP	3 (each piece)	430mm	290mm	China	

1/2 Ton Trans Jack

Packing: 1

YA714D Order NO.: 904007



Capacity (tons)	Maximum Height (inches)	Saddle Base (inches)	Lifting Head Size (inches)
1/2	69 ^{7/8}	$8^{7/8} \times 7^{1/8}$	15 ^{1/2} x 15 ^{1/2}
Handle Length (inches)	Chassis Length (inches)	Chassis Width (inches)	Tilt
11	_	33 1/2	12°
Minimum Height (inches)	Exp.Saddle Area (inches)	Jack Size (inches)	Net Weight, lbs. (kg)
33	21 x 21	34 ^{1/8} (L) x 36 ^{1/8} (W)	181 (82.1)

- Crank for precise and easy alignment
- Four adjustment load support arms fit most transmission pan flanges
- Adjustable to 0.030 inches or less
- Foot pedal pump permits hands free operation
- · Wide base and four casters for stability





Shop Equipment Shop Equipment

Engine Crane

Packing: 1



Order NO.: 904011

YA12AP

Heavy Duty Workbench Packing: 1

BPWORKBENCH Order NO.: 904001



- Features a full bottom shelf and superior powder coat finish
- Dimensions-60.08" x 30.73" x 34.08"
- Net Weight-138.9 lbs. (63.06 kg)
- Weight Capacity-1,200 lbs.
- Top panel: 2.0mm thickness
- Bottom shelf: 2.0mm thickness
- Steel support: 2.5mm thickness

Capacity	Min. Height	Max. Height	Dimension
2 Ton	340 mm	1,797 mm	1,830 x 760 x 1,550 mm
Certificate	Net Weight	Gross Weight	Packaging
2005 ASME/ PALD	109 kg	114 kg	#1 – 810 x 570 x 90 mm #2 – 1,695 x 195 x 85 mm #3 – 1,295 x 315 x 170 mm

Bottle Jacks

Packing: 1



Stock No.	Capacity (tons)	Min Height (inches)	Max Height (inches)	Adjust Height (inches)	Base (inches)	Handle (inches)
YB2AP	2	6 ^{3/4}	14 ^{5/8}	4 ² /5	4 x 4 ¹ / ₁₀	16 ¹ / ₂
ҮВЗАР	3	6 ³ / ₄	14 ⁵ /8	4 ² / ₅	4 x 4 ¹ / ₁₀	16 ¹ / ₂
YB5AP	5	8 ¹ / ₃	18 ^{2/} 5	5 ^{3/} 4	$4^{1/3} \times 4^{2/5}$	16 ^{1/2}

Stock No.	Cap Dia (inches)	Operating Force (lbs)	Ü	Order No.
YB2AP	1 ^{1/} 10	45	1	904015
YB3AP	1 ^{1/} 10	78.75	1	904016
YB5AP	1 ¹ /4	90	1	904017

• Improved Design with Welded Joints to Prevent Seal Leakage

8 Ton Bottle Jack

Packing: 1

YA1228 Order NO.: 904005



Capacity (tons)	Low Height (inches)	Maximum Height (inches)	Screw Extension (inches)
8	8 ¹ / ₈	17 ⁵ /8	2 ³ / ₄
Base Size (inches)	Handle Length (inches)	Cap Diameter (inches)	Operating Force (lbs.)
4 ^{3/4} x 4 ^{3/4}	18 1/8 (assembled)	1 ^{3/} 8	101

- Hydraulic system is protected from internal damage by a patented by-pass mechanism
- Machined and polished cylinders with die-cut threading provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel

Welder & Plasma Cutter Cart

Packing: 1

MIGCARTA Order NO.: 904002



Overall Dimensions	Shipping Weight (lbs.)
41" L x 19 ¹ / ₂ " W x 25" H	43

- Welder and plasma cutter cart features two trays along with 20" (L) x 12.75" (W) top tray to hold MIG welders and plasma cutters
- Includes cylinder bracket with adjustable chain to hold multiple diameter gas bottles
- Handle has storage tray for smaller items













Important Words About Safety for Users and Bystanders

Following these basic safety rules
is a good start toward
protecting yourself and others
in the vicinity
from injury while using tools

- Wear safety goggles
- Use the right tool
- Use the tool properly
- Maintain the tool regularly
- Keep tools away from children
- Do not use tools on live electrical circuits unless specifically designed for such use
- · Read and follow instructions

Prohibited Actions



THIS SYMBOL INDICATES PROHIBITED ACTION



DO NOT OVER-TORQUE NO PIPES OR LEVER EXTENSIONS



NO HAMMERING



NO PRYING



DO NOT STRIKE HARD OBJECTS



NO IMPACT/POWER DRIVE



DO NOT STEP IN OR ON DRAWERS



DO NOT OPEN MULTIPLE DRAWERS



DO NOT PULL TO MOVE



KEEP CHILDREN AWAY

Mandatory Actions



THIS SYMBOL INDICATES MANDATORY ACTION



MANDATORY EAR PROTECTION



MANDATORY FACE SHIELD



MANDATORY MASK



MANDATORY RESPIRATOR



MANDATORY PROTECTIVE CLOTHING



MANDATORY PROTECTIVE GLOVES



MANDATORY EYE PROTECTION



MUST READ INSTRUCTIONS BEFORE USE

Hazard Alerts



THIS SYMBOL INDICATES A HAZARD ALERT

RED BACKGROUND - DANGER ORANGE BACKGROUND - WARNING YELLOW BACKGROUND - CAUTION



VIBRATION HAZARD



RISK OF EXPLOSION



OVERHEAD/OVERLOAD HAZARD



RISK OF ELECTRIC SHOCK



RISK OF FIRE



RISK OF ENTANGLEMENT

Safety messages in this catalog use the guidelines of the American National Standard ANSI Z535. 4 for Product Safety Signs and Labels and ANSI Z535.3 Criteria for Safety Symbols. Messages associated with specific products use a triangular hazard alert symbol, signal word (CAUTION, WARNING, DANGER) and how to avoid the hazard.

PLEASE READ AND FOLLOW these messages to avoid injury to yourself and bystanders.



Snap-on Asia Pacific Division, or its assigns, ("Snap-on") warrants to customers who purchase products from authorized Blue-Point distribution channels that Blue-Point® brand products will be free from defects in workmanship and materials for a duration depending upon the nature of the product. Prior to a product purchase, customer can obtain the product warranty duration from a Blue-Point reseller. Customers may also contact the closest sales office as listed below.

During the applicable duration of the warranty, at its option, Snap-on will repair or replace its products which fail to give satisfactory service due to defective workmanship or materials, or provide a refund by repaying or crediting customer with an amount equal to the purchase price of such products. Repair, replacement or refund shall be at the election and expense of Snap-on, and is customer's exclusive remedy in place of all other rights and remedies. Any products or parts replaced or for which Snap-on has provided a refund are the property of Snap-on and will not be returned.

THE FOREGOING WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES NOT EXPRESSLY SET FORTH HEREIN. WHETHER EXPRESS, IMPLIED OR COLLATERAL, BY OPERATION OF LAW OR OTHERWISE, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Descriptions of product contained in this catalog are for the sole purpose of identifying product and shall not be construed as an express warranty.

LIMITATION OF LIABILITY. SNAP-ON AND ITS AFFILIATED COMPANIES AND THIRD PARTY SUPPLIERS SHALL NOT BE LIABLE FOR ANY INCIDENTAL, SPECIAL OR CONSEQUENTIAL LOSSES, COSTS OR DAMAGES INCURRED BY CUSTOMER OR OTHERS, INCLUDING PERSONAL INJURY OR DEATH, DIRECTLY OR INDIRECTLY ARISING FROM THE SALE, HANDLING OR USE OF THE PRODUCTS, OR FROM ANY OTHER CAUSE WITH RESPECT TO THE PRODUCTS OR THE FOREGOING WARRANTY, WHETHER SUCH CLAIM IS BASED UPON BREACH OF CONTRACT, BREACH OF WARRANTY, STRICT LIABILITY IN TORT, NEGLIGENCE OR ANY OTHER LEGAL THEORY (INCLUDING WITHOUT LIMITATION, LOST PROFITS, REVENUES, ANTICIPATED SALES, BUSINESS OPPORTUNITIES, GOODWILL, OR INTERRUPTION OF BUSINESS OR OTHER INJURY OR DAMAGE).

Snap-on® and Blue-Point® are registered trademarks of Snap-on Incorporated

SNAP-ON ASIA PACIFIC OFFICES

Asia / Pacific Division

25 Tagore Lane. #01-02 Singapore 787602 Tel: +(65) 6459-2712 Fax: +(65) 6459-1520

Snap-on Trading (Shanghai) Co., Ltd. Fax: +(852) 2370-3400

Unit 2001-2005, Cross Tower 318 Fuzhou Road, Shanghai 200001 P.R.China

Tel: +(86-21) 6391-2388 Fax: +(86-21) 6391-2382

Snap-on Trading (Shanghai) Co., Ltd. **Beijing Branch**

517B, Grand Pacific Building 8A Guanghua Road Beijing 100026 P.R.China

Tel: +(86-10) 6581-8838 Fax: +(86-10) 6581-6681

Snap-on Tools India Private Ltd.

6/2, Begumpur Khatola, 39 Milestone, NH-8, Gurgaon, Harvana-122004. India Tel: +(91-124) 459-9700 Fax: +(91-124) 405-6866

Snap-on Tools Japan, K.K.

2-1-6 Shinkiba, Koto-ku, Tokyo, 136-0082 Japan Tel: +(81-3) 5534-1285 Fax: +(81-3) 5534-1284

Snap-on Tools Hong Kong Ltd.

Unit 2010, 20/F, Laford Centre. 838 Lai Chi Kok Road. Cheung Sha Wan, Kowloon Hong Kong

Tel: +(852) 2370-3700

Snap-on Tools Korea Ltd.

#505, Building 301, Bucheon Techno Park Block 3 365 SamJung-Dong. OhJung-Gu, Bucheon City GyeongGi-Do 421-809, Korea Tel: +(82-32) 326-7310 Fax: +(82-32) 326-7312

Snap-on Tools Singapore Pte. Ltd.

25 Tagore Lane, #01-01 Singapore 787602 Tel: +(65) 6451-5570 Fax: +(65) 6451-5574

Snap-on Tools Singapore Pte. Ltd. Indonesia Representative Office

Graha Pratama Building, 20th Floor Jl. M. T. Haryono Kav.15, Jakarta 12810, Indonesia Tel: +(62-21) 8370-9611 Fax: +(62-21) 8370-9612

Snap-on Tools Singapore Pte. Ltd. Malaysia Branch

B-6-10, Street Mall, One South Jalan OS, Taman Serdang Perdana 43300 Seri Kembangan, Selangor Malavsia

Tel: +(603) 8957-1938 Fax: +(603) 8957-2938

Snap-on Tools Singapore Pte. Ltd. **Philippines Branch**

4/F. 2053 Building, Edison Street San Isidro, Makati City Philippines 1234 Tel: +(63-2) 843-7935

Fax: +(63-2) 843-7730

Snap-on Tools Singapore Pte. Ltd. **Taiwan Branch**

3F-4, #9 Wuquan 1st Road, New Taipei Industrial Park, Xinzhuang District 24892, New Taipei City, Taiwan ROC Tel: +(886-2) 2298-9789 Fax: +(886-2) 2298-2288

Snap-on (Thailand) Company Ltd.

5th Floor, Talomsin Building, 924 Rama 3 Road Bangpongpang Yannawa, Bangkok 10120. Thailand Tel: +(66) 2294-9660 Fax: +(66) 2294-9665











Sub-Category

1/2" Sockets, Ratchets & Accessories	33-37
1/4" Sockets, Ratchets & Accessories	22-26
3/4" Sockets, Ratchets & Accessories	37
3/8" Sockets, Ratchets & Accessories	27-32
Adjustable Click-Type Torque Wrenches	72
Adjustable Wrenches	42-43
Air Tools	78-92
Automotive Specialty Tools	136-157
Automotive Tool Sets	14-16
Bits	53
Combination Wrenches	43
Cordless Tools	93-94
Cutting Tools	111-115
Digital Torque Testers	75
Double Open End Wrenches	43
Electronic Type Torque Wrenches	74
Flashlights	
General Service Sets	
Hammers	
Impact Sockets	
L and T shape Wrenches	
Locking Pliers	
Measuring Tools	
Miscellaneous	
Modular Tool Sets	
Offset Box Wrenches	
Other Wrenches	
Plier Sets	
Power Tools Accessories	
Preset Click-Type Torque Wrenches	
Punches & Chisels	
Ratcheting Wrenches	
Retaining Ring Pliers	
Roll Cab Accessories	
Roll Cabinets	
Roll Carts	
Safety Tools	
Screwdrivers	
Shop Equipment	
Special Pliers	
Special Tools	
Standard Pliers	
Testing and Electronics	
Tool Boxes	
VDE Pliers	
Wrench Sets	40-42

INDEX

INDEX	
1-9	
1412A	134
1470K-AC1	7
1470K-AC2	7
1470K-AC4	7
1470K-ACSIDE	7
1658C	134
2420A	134
2430C	134
2438C	134
2842C	134
А	
A91E	150
A1310A	154
AC2Z40T27MP	102
AC2Z60T27MP	102
AC2Z80T27MP	102
AC4Z60T27MP	102
AC17D	103
AC243	103
AC420A	103
AC421A	103
AC616	103
AC3160FWMP	103
AC3180FWMP	103
AC10302	103
AC10306	103
AC31120FWMP	103
ACT73A	144
ACT83A	144
ACT106B	145
ACT110B	146
ACT118B	145 146
ACT407	144
ACT499A	145
ACT1008A	145
ACT1009A	145
ACT1046C	145
ACT1234PKT	143
ACT1290A	146
ACT1370	146
ACT81290	145
ACTB72.	143
ACTB72AACTMAN2100	143 144
ACTR4131A	143
ACTRB72	144
ACTRB96	144
ACTRR72	144
ACTRR96	144
ACTRY72	144
ACTRY96	144
ACTY72	143
ACTY72A	143
AF102	147
AHC21D	105
AHC21FD	105
AHC21MD	105
AHC21PD	104
AHC21PMD	105
AHC22E	105
AHC22FDAHC22MD	105 105
7.1 ICZZIVIU	103



AHC23MD 105	AT1070A 86
AHC23PMD 105	AT1070RA
AHC24D 105	AT1300A 78
AHC24FD 105	AT2050 84
AHC24MD 105	AT3000 83
AHC25D 105	AT5000 83
AHC25FD 105	ATC500 78
AHC25MD 105	AV1000A 128
AHC26D 105	7.0 10007.
	D.
AHC26FD 105	В
AHC26MD 105	
AHC27D 105	B45CMPAP 56
AHC27FD 105	B48CPAP 56
AHC28D 105	B58HLPAP 56
AHC28FD 105	B65CMPAP 56
AHC28MD 105	B75CMPAP 56
AHCC90C 157	B85CMPAP 56
AHCC91C 157	B85CTMPAP 56
AHCCP90C 157	B87CPAP 62
AHCCP97C 157	B95CLMPAP 56
AHRB200 102	B95CMPAP 56
AIRHOSE35 104	B96CPAP 56
AT105 85	B240B 155
AT109 85	B945CMPAP 56
AT109DGK	B960CMPAP 56
AT115 84	BADJC6
AT118 85	BADJC6AP
AT119 86	BADJC8 43
AT119DGK 86	BADJC8AP 43
AT123B 79	BADJC10 43
AT153 87	BADJC10AP 43
AT154 87	BADJC703 40
AT157R	BAWP100AP 56
AT180C	BB500 153
AT184 83	BBWDM67 44
AT185 88	BBWDM89 44
AT192A 88	BBWDM810 44
AT194A 88	BBWDM1011 44
AT195 88	BBWDM1012 44
AT200D 82	BBWDM1113 44
AT203A 82	BBWDM1213 44
AT204	BBWDM1214 44
AT215	BBWDM1415 44
AT235MCA 81	BBWDM1417 44
AT321 80	BBWDM1617 44
AT351 80	BBWDM1719 44
AT370 80	BBWDM1819 44
AT380A 80	BBWDM1921 44
AT401MCA 91	BBWDM1922 44
AT401MCKA 92	BBWDM2022 44
AT402MCA	BBWDM2123 44
AT402MCKA	BBWDM2123
AT403MCA	BBWDM2326 44
AT403MCKA 92	BBWDM2426 44
AT408 89	BBWDM2427 44
AT411A 89	BBWDM2430 44
AT415B 86	BBWDM2528 44
AT415CWMP 102	BBWDM2730 44
AT415T27MP 102	BBWDM3032 44
AT425R	BBWDM3436A 44
	BBWSM67 44
AT460RD 91	
AT460BP	BBWSM89 44
AT475A	BBWSM810 44
AT555B 78	BBWSM911 44
AT570 79	BBWSM1011 44
AT670 78	BBWSM1012 44
AT700F 82	BBWSM1113 44
AT702 81	BBWSM1213 44
AT704A	BBWSM1214 44
AT705B 81	BBWSM1314
AT738 82	BBWSM1415 44
AT801MCA 84	BBWSM1417 44
AT811 84	BBWSM1516 44

BBWSM1617	44
BBWSM1719	44
BBWSM1819	
	44
BBWSM1921	
BBWSM1922	44
BBWSM2022	44
BBWSM2122	44
BBWSM2123	
BBWSM2224	44
BBWSM2326	44
BBWSM2426	44
BBWSM2427	44
BBWSM2528	
BBWSM2730	44
BBWSM2732	44
BBWSM3032	44
BBWSM3436	44
	10
BCB6HD	61
BCB7HD	61
BCB9HD	61
BCC6HD	61
BCC8HD	
BCC10HD	61
BCEH5	65
BCEH6	65
BCER5	66
BCER6	66
BCER7	60
BCER9	60
BCES5	65
BCES6	65
BCES7	60
BCES9	60
BCIH5	65
BCIH6	65
BCIR5	65
BCIR6	65
BCIR7	60
BCIR9	60
BCIS5	65
BCIS6	65
BCIS7	60
BCIS9	60
BCT6HD	61
BCT7HD	61
BCT8HD	61
BD4SG 1	10
	56
RD(3450 MP	
BDG45CMP	F 6
BDG48CPZ	
BDG48CPZBDG57CPZ	56
BDG48CPZ	
BDG48CPZBDG57CPZ	56
BDG48CPZ	56 56 56
BDG48CPZ	56 56 56 57
BDG48CPZ	56 56 56 57 56
BDG48CPZ	56 56 56 57 56 57
BDG48CPZ	56 56 56 57 56
BDG48CPZ	56 56 56 57 56 57
BDG48CPZ	56 56 57 56 57 56 56
BDG48CPZ	56 56 57 56 57 56 56 56
BDG48CPZ	56 56 57 56 57 56 56 56
BDG48CPZ	56 56 57 56 57 56 56 56 56 57
BDG48CPZ	56 56 57 56 57 56 56 56 56 57 57
BDG48CPZ	56 56 57 56 57 56 56 56 57 57 57
BDG48CPZ	56 56 57 56 57 56 56 56 56 57 57
BDG48CPZ	56 56 57 56 57 56 56 56 57 57 56 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG98CPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG95CMP BDG95CMP BDG96LMPZ BDG911CPZ	56 56 57 56 57 56 56 56 57 57 56 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG95CMP BDG96LMPZ BDG97LMPZ BDG97LMPZ BDG97LMPZ BDG911CPZ BDG911CPZ BDG911CPZ	56 56 57 56 56 56 56 57 57 56 57 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG95CMP BDG911CPZ BDG911CPZ BDG916CPZ BDG9645LMPZ	56 56 57 56 57 56 56 56 57 57 57 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG95CMP BDG96LMPZ BDG911CPZ BDG911CPZ BDG916CPZ BDG9645LMPZ BDG9645LMPZ BBDG9645LMPZ	56 56 57 56 56 56 56 57 57 56 57 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG95CMP BDG96LMPZ BDG911CPZ BDG911CPZ BDG916CPZ BDG9645LMPZ BDG9645LMPZ BBDG9645LMPZ	56 56 57 56 57 56 56 56 57 57 57 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG911CPZ BDG911CPZ BDG911CPZ BDG964SLMPZ BDG964SLMPZ BDG91145CPZ	56 56 57 56 57 56 56 57 57 57 57 57 57 57 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMPZ BDG911CPZ BDG916CPZ BDG9645LMPZ BDG9845CPZ BDG9845CPZ BDG9145CPZ BDG91145CPZ BDG9165CPZ BDG91145CPZ BDG9165CPZ BDG9165CPZ BDG9165CPZ BDG9165CPZ BDG9165CPZ BDG9165CPZ	56 56 57 56 56 56 56 56 57 57 57 57 57 57 57 57
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG911CPZ BDG911CPZ BDG964SLMPZ BDG9645LMPZ BDG9645CPZ BDG91145CPZ BDG91145CPZ BDG9165CPZ BDG91645CPZ BDG9165CPZ BDG91645CPZ BDG9165CPZ BDG91645CPZ BDG9165CPZ BDG91645CPZ BDG91645CPZ BDG91645CPZ BDG91645CPZ BDG91645CPZ BDG91645CPZ BDG91645CPZ	56 56 57 56 56 56 56 56 57 57 57 57 57 57 56 57 57 57 56
BDG48CPZ BDG57CPZ BDG65CMP BDG85CMP BDG85CMP BDG85CTMP BDG86CPZ BDG86LMPZ BDG945CMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CLMP BDG95CMP BDG96LMPZ BDG911CPZ BDG911CPZ BDG9645LMPZ BDG9845CPZ BDG9845CPZ BDG9145CPZ BDG91145CPZ	56 56 57 56 56 56 56 57 57 57 57 57 57 56 57 57 56 57 57 57 56 57 57 57 57 57 57 57 57 57 57 57 57 57





BDGCT6K	58	BLPADJ703	40	BLPD121	34
BDGCT6W		BLPAFM1238		BLPD1212	
BDGEC7Z		BLPAFM1438		BLPD1234	
BDGLN6K		BLPAFM3812		BLPD1238	
BDGLP7SAP		BLPAFM3814		BLPD1258	
BDGLP10SAP				BLPD1278	
		BLPAIM134		_ =	
BDGMPEC5		BLPAIM341		BLPD12516	
BDGPL200XLR		BLPAIM1121		BLPD12716	
BDGPL300HG		BLPAIM1234		BLPD12916	
BDGPL300LR	57	BLPAIM1238		BLPD121116	
BDGPL400LMP	57	BLPAIM3412		BLPD121316	
BDGPL410HGZ		BLPAIM3812	95	BLPD121516	34
BDGPL411HGZ	57	BLPAIM3814	95	BLPDB12114	34
BDGPL412HGZ	57	BLPATSCM100	14	BLPDB12118	34
BDGPL800	52	BLPATSCM120		BLPDB121116	34
BDMAJ10		BLPATSCM128		BLPDM128	
BDMCB6		BLPATSIMM1215		BLPDM129	
BDMCB7		BLPATSIMM3813		BLPDM1210	
BDMCB8		BLPATSM1225		BLPDM1211	
BDMCT5				BLPDM1212	
		BLPATSM1232			
BDMCT6		BLPATSM1429		BLPDM1213	
BDMCT7		BLPATSM3824		BLPDM1214	
BDMLN6		BLPATSM3877		BLPDM1215	
BDMLN8		BLPBB146		BLPDM1216	
BDMLP7S		BLPBB1210		BLPDM1217	34
BDMLP10S	68	BLPBB1215	36	BLPDM1218	34
BDOE1012	43	BLPBB1224	36	BLPDM1219	34
BDOE1416	43	BLPBB3419	37	BLPDM1220	34
BDOE1820	43	BLPBB3810		BLPDM1221	34
BDOE2224		BLPBC18		BLPDM1222	
BDOEM67		BLPBC18-1		BLPDM1223	
BDOEM68		BLPBC24		BLPDM1224	
BDOEM89		BLPBC24-1		BLPDM1227	
BDOEM810				BLPDM1230	
		BLPBC30			
BDOEM1011		BLPBC30-1		BLPDM1232	
BDOEM1012		BLPBC36		BLPDM3419	
BDOEM1113		BLPBC36-1		BLPDM3421	
BDOEM1213		BLPBSS40		BLPDM3422	
BDOEM1214		BLPCGHD146	24	BLPDM3423	
BDOEM1314		BLPCGHD388		BLPDM3424	37
BDOEM1415	43	BLPCWM6AP	43	BLPDM3425	37
BDOEM1417	43	BLPCWM7AP	43	BLPDM3426	37
BDOEM1617	43	BLPCWM8AP	43	BLPDM3427	37
BDOEM1719	43	BLPCWM9AP		BLPDM3428	37
BDOEM1819		BLPCWM10AP		BLPDM3429	
BDOEM1921		BLPCWM11AP		BLPDM3430	
BDOEM1922		BLPCWM12AP		BLPDM3432	
BDOEM2022		BLPCWM13AP		BLPDM3433	
				BLPDM3434	
BDOEM2123		BLPCWM14AP			
BDOEM2224		BLPCWM15AP		BLPDM3435	
BDOEM2326		BLPCWM16AP		BLPDM3436	
BDOEM2426		BLPCWM17AP		BLPDM3438	
BDOEM2427		BLPCWM18AP		BLPDM3440	
BDOEM2528	43	BLPCWM19AP	43	BLPDM3446	37
BDOEM3032	43	BLPCWM20AP	43	BLPDM3450	37
BF555	154	BLPCWM21AP	43	BLPDM3455	37
BF620C	109	BLPCWM22AP	43	BLPDM3460	37
BF623	109	BLPCWM23AP	43	BLPEXIM17	101
BH141A	108	BLPCWM24AP		BLPEXIM113	
BH142A		BLPCWM25AP		BLPEXIM123	
BH232A		BLPCWM26AP		BLPEXIM125	
BKB6500		BLPCWM27AP		BLPEXIM126	
BL1B		BLPCWM28AP		BLPEXIM343	
BLED1		BLPCWM29AP		BLPEXIM344	
BLP10MHVLP		BLPCWM30AP		BLPEXIM346	
BLP13HVLP		BLPCWM31AP		BLPEXIM347	
BLP14CONV		BLPCWM32AP		BLPEXIM348	
BLP14HVLP		BLPCWM33AP	43	BLPEXIM383	
BLP15HVLP	156	BLPCWM34AP	43	BLPEXIM386	
BLP18HVLP	156	BLPCWM36	43	BLPEXIM1210	97
BLP404	61	BLPCWM38	43	BLPEXIM3410	99
BLPADJ404	40	BLPCWM41	43	BLPEXIM3413	99
BLPADJ404SG	40	BLPCWM46		BLPEXT344	37



BLPEXT348	37	BLPHBM5	53	BLPLM1232	33
BLPEXT3416	37	BLPHBM6	53	BLPLM3810	27
BLPEXTF146	24	BLPHL124	37	BLPLM3811	27
BLPEXTK123	35	BLPHL125	37	BLPLM3812	27
BLPEXTK125	35	BLPHL126	37	BLPLM3813	27
BLPEXTK126	35	BLPHL127	37	BLPLM3814	27
BLPEXTK383	29	BLPHL128	37	BLPLM3815	
BLPEXTK386		BLPHL1210	37	BLPLM3816	
BLPEXTK1210	35	BLPHL1212	37	BLPLM3817	27
BLPEXTK3810		BLPHL1214		BLPLM3818	
BLPEXTL1412		BLPHL1217		BLPLM3819	
BLPEXTL1418		BLPHSM0142		BLPLM3820	
BLPEXTL1424		BLPHSM0143		BLPLM3821	
BLPEXTL3812		BLPHSM0144		BLPLM3822	
BLPEXTL3818		BLPHSM0145		BLPLM3823	
BLPEXTL3824		BLPHSM0146		BLPLM3824	
BLPFB14		BLPHSM0147		BLPLS1412	
BLPFB316		BLPHSM0148		BLPLS1414	
		BLPHSM0149		BLPLS1438	
BLPFB532 BLPFB732		BLPHSM01410		BLPLS1458	
BLPFB932		BLPHSM01425		BLPLS14316	
BLPFS01414		BLPJIM1		BLPLS14516	
BLPFS01438		BLPJIM12		BLPLS14716	
BLPFT144		BLPJIM34		BLPLS14732	
BLPFT145.5		BLPJIM38		BLPLS14916	
BLPFT146.5		BLPK14HVLP		BLPLS14932	
BLPFT388		BLPL121		BLPLS141132	
BLPFT3855		BLPL381		BLPLSIM121	
BLPFT3865	32	BLPL1212	33	BLPLSIM1212	96
BLPGSS1233	13	BLPL1234	33	BLPLSIM1234	
BLPGSS1422	12	BLPL1238	33	BLPLSIM1238	96
BLPGSS1427	14	BLPL1258	33	BLPLSIM1258	96
BLPGSS1451A		BLPL1278	33	BLPLSIM1278	96
BLPGSS1462	11	BLPL3812	28	BLPLSIM3812	95
BLPGSS3837		BLPL3814		BLPLSIM3814	
BLPGSS3849		BLPL3834		BLPLSIM3834	
BLPGSS3885		BLPL3838		BLPLSIM3838	
BLPGSSC100		BLPL3858		BLPLSIM3858	
BLPGSSC155		BLPL3878		BLPLSIM12716	
BLPGSSCM78		BLPL12716		BLPLSIM12916	
BLPGSSCT71		BLPL12916		BLPLSIM38516	
BLPH123				BLPLSIM38716	
BLPH123		BLPL38516 BLPL38716		BLPLSIM38716BLPLSIM38916	
BLPH125			==	BLPLSIM121116	
		BLPL38916			
BLPH125L180		BLPL121116		BLPLSIM121316	
BLPH126	30	BLPL121316		DEL ESHATIZ IS TO	
BLPH126L70		BLPL121516		BLPLSIM381116	
BLPH126L140		BLPL381116		BLPLSIMB12114	
BLPH126L250		BLPL381316		BLPLSIMB12116	
BLPH127		BLPL381516		BLPLSIMB12118	
BLPH128		BLPLB12118		BLPLSIMB121316	96
BLPH128L120		BLPLB121116		BLPLSM144	
BLPH383		BLPLB125114		BLPLSM145	
BLPH384		BLPLM386	27	BLPLSM146	22
BLPH385		BLPLM387		BLPLSM147	
BLPH386		BLPLM388	27	BLPLSM148	22
BLPH387	32	BLPLM389	27	BLPLSM149	22
BLPH388	32	BLPLM1210	33	BLPLSM1410	22
BLPH1210	36	BLPLM1211	33	BLPLSM1411	22
BLPH1210L140	36	BLPLM1212	33	BLPLSM1412	22
BLPH1212	36	BLPLM1213	33	BLPLSM1413	22
BLPH1214	36	BLPLM1214	33	BLPLSM1414	22
BLPH1217		BLPLM1215		BLPLSMIM117	
BLPH1219		BLPLM1216		BLPLSMIM118	
BLPH3810		BLPLM1217		BLPLSMIM119	
BLPHB14		BLPLM1218		BLPLSMIM120	
BLPHB18		BLPLM1219		BLPLSMIM121	
BLPHB316		BLPLM1220		BLPLSMIM122	
BLPHB532		BLPLM1221		BLPLSMIM123	
BLPHB732		BLPLM1222		BLPLSMIM124	
BLPHB964		BLPLM1224		BLPLSMIM125	
				BLPLSMIM126	
BLPHBM3BLPHBM4		BLPLM1227 BLPLM1230		BLPLSMIM126BLPLSMIM127	
DEFTIDIVIT	33	DEF LIVITZOU	33	DEF EDIVITIVITE/	100







BLPLSMIM128	100	BLPLSMIM3455	98	BLPS3814	28
BLPLSMIM129		BLPLSMIM3810	94	BLPS3834	28
BLPLSMIM130		BLPLSMIM3811		BLPS3838	
BLPLSMIM131		BLPLSMIM3812		BLPS3858	
BLPLSMIM132		BLPLSMIM3813			
				BLPS3878	
BLPLSMIM133		BLPLSMIM3814		BLPS12516	
BLPLSMIM134		BLPLSMIM3815		BLPS12716	
BLPLSMIM135	100	BLPLSMIM3816	94	BLPS12916	33
BLPLSMIM136	100	BLPLSMIM3817	94	BLPS14316	22
BLPLSMIM137	100	BLPLSMIM3818	94	BLPS14516	22
BLPLSMIM138	100	BLPLSMIM3819	94	BLPS14532	
BLPLSMIM140		BLPLW3415		BLPS14716	
BLPLSMIM141		BLPMV4		BLPS14732	
BLPLSMIM142		BLPMV5		BLPS14916	
BLPLSMIM143		BLPMV6		BLPS14932	
BLPLSMIM146		BLPP140	26	BLPS38516	28
BLPLSMIM149	100	BLPP141	26	BLPS38716	28
BLPLSMIM150	100	BLPP142	26	BLPS38916	28
BLPLSMIM155	100	BLPP143	26	BLPS81414	
BLPLSMIM387		BLPP144		BLPS81438	
BLPLSMIM388		BLPP381		BLPS121116	
BLPLSMIM389		BLPP382			
				BLPS121316	
BLPLSMIM1210		BLPP383		BLPS121516	
BLPLSMIM1211		BLPP384		BLPS141132	
BLPLSMIM1212	96	BLPPB0	53	BLPS381116	28
BLPLSMIM1213	96	BLPPB1	53	BLPS381316	28
BLPLSMIM1214	96	BLPPB2	53	BLPS381516	28
BLPLSMIM1215	96	BLPPB3	53	BLPS814516	
BLPLSMIM1216		BLPPB704		BLPSB12114	
BLPLSMIM1217		BLPPD141		BLPSB12118	
BLPLSMIM1218		BLPPD142			
				BLPSB121116	
BLPLSMIM1219		BLPPD143		BLPSB121316	
BLPLSMIM1221		BLPPD381		BLPSH1238	
BLPLSMIM1222		BLPPD382	32	BLPSIM121	96
BLPLSMIM1224	96	BLPPD383	32	BLPSIM341	99
BLPLSMIM1226	96	BLPPD384	32	BLPSIM1212	96
BLPLSMIM1227	96	BLPPS141	26	BLPSIM1234	
BLPLSMIM1229		BLPPS142		BLPSIM1238	
BLPLSMIM1230		BLPPTA3438		BLPSIM1258	
BLPLSMIM1230					
		BLPPTEXT3		BLPSIM1278	
BLPLSMIM3417		BLPPTS12		BLPSIM3434	
BLPLSMIM3418		BLPPTS34		BLPSIM3478	
BLPLSMIM3419	98	BLPPTS38	31	BLPSIM3812	
BLPLSMIM3420	98	BLPPTS58	31	BLPSIM3814	95
BLPLSMIM3421	98	BLPPTS716	31	BLPSIM3834	95
BLPLSMIM3422	98	BLPPTS916	31	BLPSIM3838	
BLPLSMIM3423	98	BLPPTS1116	31	BLPSIM3858	
BLPLSMIM3424		BLPPTSM8		BLPSIM12716	
BLPLSMIM3425		BLPPTSM9		BLPSIM12916	
BLPLSMIM3426		BLPPTSM10			
				BLPSIM38516	
BLPLSMIM3427		BLPPTSM11		BLPSIM38716	
BLPLSMIM3428		BLPPTSM12		BLPSIM38916	
BLPLSMIM3429		BLPPTSM13		BLPSIM121116	96
BLPLSMIM3430	98	BLPPTSM14	31	BLPSIM121316	96
BLPLSMIM3431	98	BLPPTSM15	31	BLPSIM121516	96
BLPLSMIM3432	98	BLPPTSM16	31	BLPSIM341116	99
BLPLSMIM3433		BLPPTSM17	31	BLPSIM341316	
BLPLSMIM3434		BLPPTSM18		BLPSIM341516	
BLPLSMIM3435		BLPPTSM19		BLPSIM381116	
BLPLSMIM3436		BLPPTSS3822		BLPSIMB342	
BLPLSMIM3437		BLPS12		BLPSIMB12114	
BLPLSMIM3438		BLPS121		BLPSIMB12118	96
BLPLSMIM3440	98	BLPS381		BLPSIMB34112	99
BLPLSMIM3441	98	BLPS1212	33	BLPSIMB34114	99
BLPLSMIM3442	98	BLPS1234	33	BLPSIMB34118	
BLPLSMIM3443		BLPS1238		BLPSIMB34134	
BLPLSMIM3444		BLPS1258		BLPSIMB34138	
BLPLSMIM3445		BLPS1278		BLPSIMB34158	
BLPLSMIM3446		BLPS1412		BLPSIMB34178	
BLPLSMIM3447		BLPS1414		BLPSIMB121116	
BLPLSMIM3448		BLPS1438		BLPSIMB121516	
BLPLSMIM3449		BLPS1458		BLPSIMB121716	
BLPLSMIM3450	98	BLPS3812	28	BLPSIMB341116	99



BLPSIMB341316	99	BLPSMIM128	100	BLPSMIM3430	98
BLPSIMB341516		BLPSMIM129	100	BLPSMIM3431	98
BLPSIMB341716	99	BLPSMIM130	100	BLPSMIM3432	98
BLPSIMB341916		BLPSMIM131		BLPSMIM3433	
BLPSIMB3411116		BLPSMIM132		BLPSMIM3434	
BLPSIMB3411316		BLPSMIM133		BLPSMIM3435	
BLPSIMB3411516		BLPSMIM134		BLPSMIM3436	
BLPSM128	33	BLPSMIM135	100	BLPSMIM3437	
BLPSM129		BLPSMIM136	100	BLPSMIM3438	
BLPSM143.5	22	BLPSMIM137	100	BLPSMIM3439	
BLPSM144		BLPSMIM138	100	BLPSMIM3440	
BLPSM144.5	22	BLPSMIM139	100	BLPSMIM3441	98
BLPSM145	22	BLPSMIM140	100	BLPSMIM3442	
BLPSM145.5	22	BLPSMIM141	100	BLPSMIM3443	98
BLPSM146	22	BLPSMIM142	100	BLPSMIM3444	98
BLPSM147		BLPSMIM143	100	BLPSMIM3445	98
BLPSM148	22	BLPSMIM144	100	BLPSMIM3446	98
BLPSM149	22	BLPSMIM145	100	BLPSMIM3447	98
BLPSM386	27	BLPSMIM146	100	BLPSMIM3448	98
BLPSM387	27	BLPSMIM147	100	BLPSMIM3449	98
BLPSM388	27	BLPSMIM148	100	BLPSMIM3450	98
BLPSM389	27	BLPSMIM149	100	BLPSMIM3452	98
BLPSM1210	33	BLPSMIM150	100	BLPSMIM3454	98
BLPSM1211	33	BLPSMIM151	100	BLPSMIM3455	98
BLPSM1212	33	BLPSMIM152	100	BLPSMIM3456	98
BLPSM1213		BLPSMIM153	100	BLPSMIM3457	98
BLPSM1214	33	BLPSMIM154	100	BLPSMIM3458	98
BLPSM1215		BLPSMIM155	100	BLPSMIM3459	
BLPSM1216	33	BLPSMIM156	100	BLPSMIM3460	98
BLPSM1217		BLPSMIM157		BLPSMIM3463	98
BLPSM1218		BLPSMIM158		BLPSMIM3465	
BLPSM1219		BLPSMIM159		BLPSMIM3810	
BLPSM1220		BLPSMIM160		BLPSMIM3811	
BLPSM1221		BLPSMIM163		BLPSMIM3812	
BLPSM1222		BLPSMIM165		BLPSMIM3813	
BLPSM1223		BLPSMIM166		BLPSMIM3814	
BLPSM1224		BLPSMIM167		BLPSMIM3815	
BLPSM1227		BLPSMIM168		BLPSMIM3816	
BLPSM1230		BLPSMIM169		BLPSMIM3817	
BLPSM1232		BLPSMIM387		BLPSMIM3818	
BLPSM1234		BLPSMIM388		BLPSMIM3819	
BLPSM1236		BLPSMIM389		BLPSMS8	
BLPSM1410		BLPSMIM1210		BLPSMS10	
BLPSM1411		BLPSMIM1211		BLPSMS12	
BLPSM1412		BLPSMIM1212		BLPSPS1216	
BI PSM1413	22	BI PSMIM1213	96	BI PSPS1221	35
BLPSM1414	22	BLPSMIM1214	96	BLPSPS1258	35
BLPSM3810		BLPSMIM1215		BLPSPS3816	
BLPSM3811		BLPSMIM1216		BLPSPS3821	
BLPSM3812		BLPSMIM1217		BLPSPS3858	
BLPSM3813		BLPSMIM1218		BLPSPS121316	
BLPSM3814		BLPSMIM1219		BLPSPS381316	
BLPSM3815		BLPSMIM1221		BLPSQB1	
BLPSM3816		BLPSMIM1222		BLPSQB2	
BLPSM3817		BLPSMIM1223		BLPSTHD144	
BLPSM3818		BLPSMIM1224		BLPSTHD388	
BLPSM3819		BLPSMIM1227		BLPSTHD1215	
BLPSM3820		BLPSMIM1229		BLPSTHD3418	
BLPSM3821		BLPSMIM1230		BLPSTWR4	
BLPSM3822		BLPSMIM1232		BLPSTWR6	
BLPSM3823		BLPSMIM3417		BLPT146TP	
BLPSM3824		BLPSMIM3418		BLPT147TP	
BLPSMIM117		BLPSMIM3419		BLPT148TP	
BLPSMIM118		BLPSMIM3420		BLPT149TP	
BLPSMIM119		BLPSMIM3421		BLPT1220	
BLPSMIM120		BLPSMIM3422		BLPT1225	
BLPSMIM121		BLPSMIM3423		BLPT1227	
BLPSMIM122		BLPSMIM3424		BLPT1230	
BLPSMIM123		BLPSMIM3425		BLPT1240	
BLPSMIM124		BLPSMIM3426		BLPT1245	
BLPSMIM125		BLPSMIM3427		BLPT1243 BLPT1250	
BLPSMIM126		BLPSMIM3428		BLPT1255	
BLPSMIM127		BLPSMIM3429		BLPT1255TP	
DEI JIVIIIVI I Z./	. 100	DEI JIVIIIVIJTZJ	70	DEI 1123311	54







BLPT1260	36	BLPTS01425	25	BMPM8	. 119
BLPT1260TP		BLPTS01427	25	BOER8	44
BLPT1410TP		BLPTS01430	25	BOER10	40
BLPT1415TP		BLPTS01440		BOER12	40
BLPT1420TP		BLPTS01445	25	BOER14	40
BLPT1425TP		BLPTS01447	25	BOER16	40
BLPT1427TP		BLPTS01450	25	BOER18	40
BLPT1430TP		BLPTS3810		BOER20	
BLPT3810TP		BLPTS3815		BOER22	
BLPT3815TP		BLPTS3820		BOER24	
BLPT3820TP		BLPTS3825		BOER26	
BLPT3825TP		BLPTS3827		BOER28	
BLPT3827TP		BLPTS3830		BOER30	
BLPT3830TP		BLPTS3840		BOER32	
BLPT3840TP		BLPTS3845		BOER704	
BLPT3845TP		BLPTS3850		BOER708	
BLPT3850TP		BLPTS3855		BOERF10A	
BLPT3855TP		BLPTS3860		BOERF12A	41 //1
BLPTB10TP		BLPTSSC43		BOERF14A	
BLPTB15TP		BLPTXK1.5		BOERF16A	
BLPTB20TP		BLPTXK2		BOERF18A	
BLPTB25TP		BLPTXK3BLPTXK4		BOERF20A	
BLPTB30TP				BOERF22A	
BLPTE144		BLPTXK6		BOERF24A	
BLPTE145		BLPUJ12		BOERF708A	
BLPTE146		BLPUJ14		BOERFLCG10	
BLPTE147		BLPUJ34		BOERFLCG12	
BLPTE148		BLPUJ38		BOERFLCG14	
BLPTE384		BLPXZN144		BOERFLCG16	
BLPTE385		BLPXZN145		BOERFLCG18	
BLPTE386	28	BLPXZN146		BOERFLCG20	42
BLPTE387		BLPXZN148	26	BOERFLCG22	42
BLPTE388		BLPXZN1410	26	BOERFLCG24	
BLPTE1210		BLPXZN1412	26	BOERFLCG708	42
BLPTE1212	34	BLPXZNM125	36	BOERM6	44
BLPTE1214	34	BLPXZNM126	36	BOERM7	44
BLPTE1216	34	BLPXZNM128	36	BOERM8	40
BLPTE1218	34	BLPXZNM0384	32	BOERM9	40
BLPTE1220	34	BLPXZNM0385	32	BOERM10	40
BLPTE1222		BLPXZNM0386		BOERM11	40
BLPTE1224		BLPXZNM0388		BOERM12	
BLPTE3810	28	BLPXZNM1210	36	BOERM13	40
BLPTE3811		BLPXZNM1212		BOERM14	
BLPTE3812		BLPXZNM1214		BOERM15	
BLPTE3814	28	BLPXZNM1216		BOERM16	40
BLPTE3816		BLPXZNM03810		BOERM17	
BLPTE3818		BLPXZNM03812		BOERM18	
BLPTE3820		BLWM1.5		BOERM19	
BLPTHSM0142		BLWM2		BOERM21	
BLPTHSM0143		BLWM2.5		BOERM22	
BLPTHSM0144		BLWM3		BOERM24	
BLPTHSM0145		BLWM4		BOERM25	
BLPTHSM0146		BLWM5		BOERM704	
BLPTHSM0147		BLWM6		BOERM712	
BLPTHSM0148		BLWM8		BOERMF8A	
BLPTHSM0149		BLWM10		BOERMF9A	
BLPTHSM01410		BLWM11		BOERMF10A	
BLPTHSM01425		BLWM12		BOERMF11A	
BLPTL1220		BLWM13		BOERMF12A	
BLPTL1225		BLWM14		BOERMF13A	
BLPTL1227		BLWM15		BOERMF14A	
BLPTL1230		BLWM16		BOERMF15A	
BLPTL1240		BLWM17		BOERMF16A	
BLPTL1245		BLWM18		BOERMF17A	
BLPTL1250		BLWM19		BOERMF18A	
BLPTL1255		BLWSM9		BOERMF19A	
BLPTL1260		BLWTS9		BOERMF712A	
BLPTMBS1414		BMPEC5AP		BOERMFLCG8	
BLPTMBS3814		BMPL1000		BOERMFLCG9	
BLPTS0148		BMPLM3		BOERMFLCG10	
BLPTS01410		BMPLM5		BOERMFLCG11	
BLPTS01415		BMPM3		BOERMFLCG12	
BLPTS01420	25	BMPM5	. 119	BOERMFLCG13	41



				0.007500	
BOERMFLCG14		BP602NMRMH		BSGD75S3B	
BOERMFLCG15		BP1001-O-DTT		BSGD75S3R BSGD75S3Y	
BOERMFLCG17				BSGD100PH0B	
BOERMFLCG17 BOERMFLCG18		BP1002NMRMHBP2003NMRMH		BSGD100PH0R	
BOERMFLCG19		BP2401CI3		BSGD100PH0Y	
BOERMFLCG19		BP2502-I-DTT		BSGD100PH1B	
BOERMS8		BP2502NMRMH		BSGD100PH1R	
BOERMS9		BP2503CF3		BSGD100PH1Y	
BOERMS10		BP2503-F-DTT		BSGD100PH2B	
		BP3403NMRMH		BSGD100PH2R	
BOERMS11				BSGD100PH2Y	
BOERMS12		BP6004-F-DTT		BSGD100PH21	
BOERMS13		BP8004NMRMH			
BOERMS14		BP15005NMRMH		BSGD100S4V	
BOERMS15		BPAP1		BSGD100S4Y	
BOERMS16		BPAP2		BSGD125F5B	
BOERMS17		BPAPS1		BSGD125F5R	
BOERMS18		BPB4		BSGD125F5Y	
BOERMS19		BPB8		BSGD125F6B	
BOERMS712		BPB12		BSGD125F6R	
BOERMSF8		BPB16		BSGD125F6Y	
BOERMSF9		BPB24		BSGD125S4B	
BOERMSF10		BPB32		BSGD125S4R	
BOERMSF11		BPB40		BSGD125S4Y	
BOERMSF12		BPB48		BSGD125S5B	
BOERMSF13		BPBOX18		BSGD125S5R	
BOERMSF14		BPBOX20		BSGD125S5Y	
BOERMSF15		BPC6		BSGD150F6B	
BOERMSF16		BPECT1		BSGD150F6R	
BOERMSF17		BPL501		BSGD150F6Y	
BOERMSF18		BPN8B		BSGD150F8B	
BOERMSF19		BPN12B		BSGD150F8R	
BOERS10		BPN16B		BSGD150F8Y	
BOERS12		BPN24B	108	BSGD150PH0B	
BOERS14		BPN32B		BSGD150PH0R	
BOERS16	41	BPRFPT10		BSGD150PH0Y	
BOERS18	. 41	BPRFR938		BSGD150PH1B	
BOERS20	. 41	BPRFR938SG	28	BSGD150PH1R	
BOERS22	. 41	BPRSR940	34	BSGD150PH1Y	
BOERS24	. 41	BPRSR940SG	35	BSGD150PH2B	50
BOERS708	41	BPRSR942	34	BSGD150PH2R	
BOERSF10	. 41	BPRTR936		BSGD150PH2Y	50
BOERSF12	. 41	BPRTR936SG	23	BSGD150PH3B	
BOERSF14	. 41	BPS1	17	BSGD150PH3R	
BOERSF16	. 41	BPS2	17	BSGD150PH3Y	50
BOERSF18	. 41	BPS3	17	BSGD150S4B	50
BOERSF20	41	BPS4P	17	BSGD150S4R	50
BOERSF22	. 41	BPS5	17	BSGD150S4Y	
BOERSF24	. 41	BPS6	17	BSGD150S5B	50
BOERSF708	41	BPS6A	17	BSGD150S5R	50
BP5T-1R	72	BPS7	18	BSGD150S5Y	50
BP5T-I		BPS8	18	BSGD175F8B	50
BP10002-I-DTT	75	BPS9	18	BSGD175F8R	50
BP10ST-I	73	BPS10	18	BSGD175F8Y	
BP10T-2R	72	BPS11	19	BSGD200PH1B	
BP10T-2RL	72	BPS12	19	BSGD200PH1R	50
BP10T-I	73	BPS13	19	BSGD200PH1Y	
BP50T-2R	72	BPS14	19	BSGD200PH2B	
BP50T-2RL	72	BPTHM08	47	BSGD200PH2R	50
BP50T-I	73	BPTHM09	47	BSGD200PH2Y	50
BP100T-3R	72	BPTHM10	47	BSGD200PH3B	50
BP100T-3RL	72	BPTHM11	47	BSGD200PH3R	50
BP100T-I	73	BPTHM12	47	BSGD200PH3Y	50
BP200T-3R	72	BPTHM13	47	BSGD250F6B	50
BP200T-3RL	72	BPTHM14	47	BSGD250F6R	50
BP200T-I		BPTOTE		BSGD250F6Y	50
BP250T-3RL		BPWORKBENCH		BSGD250PH1B	
BP300T- 4R	72	BSGD75F4B	50	BSGD250PH1R	50
BP300T-I		BSGD75F4R		BSGD250PH1Y	50
BP501-I-DTT		BSGD75F4Y		BSGD250PH2B	
BP501NMRMH		BSGD75PH0B		BSGD250PH2R	
BP600T- 4R		BSGD75PH0R		BSGD250PH2Y	
BP600T-I*		BSGD75PH0Y		BSGD250S4B	50
	_				





BSGD250S4R	. 50	BSGDV200PH3	51	ETA125A	102
BSGD250S4Y		BSP6		ETB14401A	
BSGD300PH1B		BT9		ETB14410A	
BSGD300PH1R		BTC3A		ETB14419A	
BSGD300PH1Y		BTCP1		ETB14420A	
BSGD300PH2B		BTG8		ETB14430A	
BSGD300PH2R		BTQS500		ETB14438A	
BSGD300PH2Y		BTQS600		ETB14460A	93
BSGDM38F6		BTQ\$1000			
BSGDM38PH2		BTWM1.5		F	
BSGDM38PZ2		BTWM2.5			
BSGDM65F2		BTWM3		FB300A	118
BSGDM65PH00		BTWM4	47	FB307D	119
BSGDM65PZ00	52	BTWM5	47	FB308D	. 118
BSGDM75F3	52	BTWM6	47	FB310B	118
BSGDM75F5	52	BTWM7	47	FB316B	118
BSGDM75PH0	52	BTWM8	47	FB322	119
BSGDM75PH1	52			FB325A	118
BSGDM75PZ0		С		FB326B	
BSGDM75PZ1				FB328A	
BSGDM75TX6		CD7A	112	FB335	
BSGDM75TX7		CD10A		FBL325A	
BSGDM75TX8		CD12A		FBM320	
BSGDM75TX9		CD16A		FBM322	
BSGDM100F3		CF19B		FBS5	
BSGDM100F5		CF700B		FSD1	
BSGDM100F6		CF811B		FSD14	
BSGDM100PH0		CL404VIS	128	FSD38	23
BSGDM100PH1	52	CL406VIS	128	FSDR	23
BSGDM100PH2	52	CL408VIS	128	FSDR1	28
BSGDM100PZ0	52	CM6416	128	FUNN15	151
BSGDM100PZ1		CNT6521	120	FW7630A	151
BSGDM100PZ2		CW12A		FW656714A	
BSGDM100TX10		CW15A		FW757715A	
BSGDM100TX15		CW24A		FWA62121A	
BSGDM100TX19		CW24/A	47	FWK7A	
DCCDM100TV2E	E 2			LAI DUS	20
BSGDM100TX25		D		FXLBP3	
BSGDM100TX27	52		104	FXLBP6	30
BSGDM100TX27 BSGDM100TX30	52 52	DBBP21			30
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40	52 52 52	DBBP21 DBBPC21	104	FXLBP6FXLBP10	30
BSGDM100TX27	52 52 52 52	DBBP21 DBBPC21 DBBPT13	104 104	FXLBP6	30
BSGDM100TX27	52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300	104 104 128	FXLBP6FXLBP10G	30 30
BSGDM100TX27	52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530	104 104 128 136	FXLBP6	30 30
BSGDM100TX27	52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300	104 104 128 136	FXLBP6FXLBP10G	30 30
BSGDM100TX27	52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530	104 104 128 136 121	FXLBP6	30 30 125 136
BSGDM100TX27	52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6	104 104 128 136 121	FXLBP6	30 30 125 136 151
BSGDM100TX27	52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61	104 104 128 136 121 121	FXLBP6	30 30 125 136 151 137
BSGDM100TX27	52 52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62	104 104 128 136 121 121 121	FXLBP6	30 30 125 136 151 137 148
BSGDM100TX27	52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63	104 104 128 136 121 121 121 121 121	GA225	125 136 151 137 148 125
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PH3 BSGDM150PH3 BSGDM150PH3	52 52 52 52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM64 DM65	104 104 128 136 121 121 121 121 121	GA225	125 136 151 137 148 125 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PH3 BSGDM150PH3 BSGDM150PH3 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM65	104 104 128 136 121 121 121 121 121 121	GA225	125 136 151 137 148 125 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PH3 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ2	52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM66 DM66	104 104 128 136 121 121 121 121 121 121 121 121	GA225	125 136 151 137 148 125 42 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM65	104 104 128 136 121 121 121 121 121 121 121 121	GA225	125 136 151 137 148 125 42 42 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F6 BSGDM150F6 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5	52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DM6 DM6 DM62 DM63 DM64 DM65 DM66 DM66 DM67 DPFT528B	104 104 128 136 121 121 121 121 121 121 121	FXLBP6	125 136 151 137 148 125 42 42 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150FH0 BSGDM150PH0 BSGDM150PH2 BSGDM150PH2 BSGDM150PH3 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6	52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM66 DM66	104 104 128 136 121 121 121 121 121 121 121	FXLBP6	125 136 151 137 148 125 42 42 42 43 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM66 DM66 DM67 DPFT528B	104 104 128 136 121 121 121 121 121 121 121 121 121 121	FXLBP6	125 136 151 137 148 125 42 42 42 43 43 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM66 DM66 DM67 DPFT528B E	104 104 128 136 121 121 121 121 121 121 121 121 121 110	FXLBP6	125 136 151 137 148 125 42 42 42 43 43 42 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200F9	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM66 DM66 DM67 DPFT528B E	104 104 128 136 121 121 121 121 121 121 121 110	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6A GAJ6SG GAJ6SGAP GAJ8A GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8AP	125 136 151 137 148 125 42 42 42 42 43 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200F9 BSGDM200PH2 BSGDM200PH3	52 52	DBBP21	104 104 128 136 121 121 121 121 121 121 121 110	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6A GAJ6SG GAJ6SGAP GAJ8A GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8AP GAJ8SG GAJ8SGAP	125 136 151 137 148 125 42 42 42 42 43 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH3 BSGDM200PH4	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM64 DM65 DM66 DM66 DM67 DPFT528B E	104 104 128 136 121 121 121 121 121 121 121 110	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8AP GAJ8AP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP	125 136 151 137 148 125 42 42 42 43 43 43 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200F9 BSGDM200PH2 BSGDM200PH3	52 52	DBBP21	104 104 128 136 121 121 121 121 121 121 121 110	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6A GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP	125 136 151 137 148 125 42 42 42 43 43 43 43 43 43 43 43 43 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH3 BSGDM200PH4	52 52	DBBP21	104 104 128 136 121 121 121 121 121 121 121 110	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8AP GAJ8AP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP	125 136 151 137 148 125 42 42 42 43 43 43 43 43 43 43 43 43 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH3 BSGDM200PH4 BSGDM200PH4	52 52	DBBP21	104 104 128 136 121 121 121 121 121 121 121 110	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6A GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP	125 136 151 137 148 125 42 42 42 43 43 43 43 43 43 43 43 43 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH3 BSGDM200PH4 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH4	52 52	DBBP21	104 104 128 136 121 121 121 121 121 121 121 110 137 137 137 122 122 122 122	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6A GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP GAJ10AP GAJ10AP	125 136 151 137 148 125 42 42 42 43 43 43 43 43 43 43 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200PH4 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH4 BSGDM200PZ3 BSGDM200PZ3 BSGDM200PZ3 BSGDM200PZ3 BSGDM200PH4 BSGDM200PZ3 BSGDM200PZ2 BSGDM200PZ3 BSGDM200PZ3 BSGDM200PZ3 BSGDM200PZ3	52 52	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 122 122 122 122 124 124	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6A GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP GAJ8SGAP GAJ8SGAP GAJ10A GAJ10AP GAJ10AP GAJ10SG GAJ10SGAP	125 136 151 137 148 125 42 42 42 43 42 43 42 43 43 42 43 44 45
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150FH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ2 BSGDM200F5 BSGDM200F5 BSGDM200F6 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH3 BSGDM200PH4 BSGDM200PZ2 BSGDM200PZ2 BSGDM200PZ3 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM250PH2	52 52	DBBP21 DBBPC21 DBBPT13 DEBUR300 DG530 DM6 DM61 DM62 DM63 DM65 DM66 DM67 DPFT528B E E1020 E1025 ECF201A ECF1600 ECFB200BL ECFB200S ECFB20AP ECFLED24 ECFLED24 ECFLED24 ECFLED24 ECFLED24 ECFLED24 ECFLED24 DBBPC1 DM6 DM6 DM6 DM6 DM6 DM6 DM6 DM6 ECFLED24 DESTRIPTION DBBPC1 DBBPC1 DBBPC2 DBBPC2 DBBPC3 DBBPC3 DBBPC3 DBBPC3 DBBPC3 DBBPC3 DBBPC3 DBBPC3 DBBPC3 ECFLED24 DBBPC3 DBBCC3 DBBCC3 DBBCC3 DBBCC3 DBBCC3 DBB	104 104 104 128 136 121 121 121 121 121 121 121 121 121 122 122 122 122 124 124 124	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8AB GAJ8AP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP GAJ8SGAP GAJ10AP GAJ10AP GAJ10AP GAJ10SG GAJ10SG GAJ10SGAP GAJ12A	125 136 151 137 148 125 42 42 42 43 42 43 42 43 42 43 43 43 43 42 43 42 43 43 43 43 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150FH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM200F5 BSGDM200F6 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH4 BSGDM200PH4 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH4 BSGDM200PZ3 BSGDM200PZ3 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PH2 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ2 BSGDM200PZ4 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2	52 52	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 122 122 122 122 124 124 123	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SG GAJ8SG GAJ8SG GAJ8SG GAJ10A GAJ10AP GAJ10AP GAJ10SG GAJ10SG GAJ12A GAJ12AP GAJ12AP GAJ12SG	125 136 151 137 148 125 42 42 42 43 43 42 43 43 42 43 43 42 42 43 42 42 42 42 42 42 43 42 43 42 42 42 42 43 42 42 42 43 42 43 42 43 42 43 42 43 42 43 43 44
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150FH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PH3 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F9 BSGDM200PH4 BSGDM200PH4 BSGDM200PH4 BSGDM200PZ2 BSGDM200PZ3 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM250PH2	52 52	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 122 122 122 122 122 124 124 124 123 124	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP GAJ8SG GAJ8SGAP GAJ10A GAJ10AP GAJ10AP GAJ10AP GAJ10SG GAJ10SG GAJ10SG GAJ12A GAJ12AP GAJ12SG GAJ12SG GAJ12SG	125 136 151 137 148 125 42 42 42 43 43 42 43 43 42 43 43 42 43 43 42 42 43 42 42 43 42 43 43 42 42 43 43 42 42 43 42 42 43 42 42 42 43 42 42 43 42 42 42 42 43 42 43 42 42 42 43 42 43 42 43 43 42 43 42 43 43 42 43 43 42 43 43 43 44 43 44 43 44 45 45 45 46
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH2 BSGDM150PH3 BSGDM150PH2 BSGDM150PZ0 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ1 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F5 BSGDM200F6 BSGDM200F8 BSGDM200F9 BSGDM200PH2 BSGDM200PH4 BSGDM200PH3 BSGDM200PZ2 BSGDM200PZ3 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM250PH2 BSGDM100PH0 BSGDV100PH0	52 52	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 122 122 122 122 122 124 124 123 124 123	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ88A GAJ8AP GAJ10AP GAJ10AP GAJ10AP GAJ10AP GAJ10AP GAJ10SG GAJ10SGAP GAJ12A GAJ12AP GAJ12AP GAJ12SG GAJ12SG GAJ12SG	125 136 151 137 148 125 242 42 42 42 43 42 43 42 43 43 42 43 43 42 43 42 43 42 43
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH2 BSGDM150PH3 BSGDM150PH2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH3 BSGDM200PH4 BSGDM200PH4 BSGDM200PZ2 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM20PH2 BSGDM20PH2 BSGDM20PP2 BSGDM200PP3 BSGDM200PP3 BSGDM200PP4 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM100S2 BSGDV100S3	52 51 51	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 122 122 122 122 122 124 124 123 123 143	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SG GAJ8SG GAJ10A GAJ10AP GAJ10SG GAJ10SGAP GAJ12A GAJ12AP GAJ12SG GAJ12SG GAJ12SGAP GAJ12SG GAJ12SGAP GAJ15A	125 136 151 137 148 125 242 242 243 244 244 244 244 244 244 244
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH2 BSGDM150PH3 BSGDM150PH2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F9 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH4 BSGDM200PH4 BSGDM200PH4 BSGDM200PZ2 BSGDM200PZ4 BSGDM200PZ4 BSGDM200PZ4 BSGDM20PH2 BSGDM20PH2 BSGDM20PH2 BSGDM20PP2 BSGDM20PP3 BSGDM20PP4 BSGDM20PP4 BSGDM20PP4 BSGDM20PP4 BSGDM20PP4 BSGDM20PP4 BSGDM20PP4 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP2 BSGDM20PP3 BSGDM20PP4 BSGDM20PP4 BSGDM20PZ4 BSGDM20PP4 BSGDM20PP4 BSGDM250PP2 BSGDM250PP2 BSGDM250PP2 BSGDV100PH0 BSGDV100S2 BSGDV100S3 BSGDV100S3	52 51 51	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 122 122 122 122 122 124 124 123 123 124 123 143 122	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ10A GAJ10AP	125 136 151 137 148 125 42 42 42 43 43 42 43 43 42 43 43 42 43 42 43 42 43 42 42 43 42 43 42 43 42 43 42 42 42 42 42 42 42 42 43 42 43 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH2 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F9 BSGDM200PH4 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDV100S4 BSGDV100S4 BSGDV10S5	52 55 55 51 51 51	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 121 122 122 122 122 122 124 124 123 124 123 143 122 142	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ10A GAJ10AP	125 136 151 137 148 125 42 42 42 43 43 42 43 43 42 43 43 42 43 42 43 42 43 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH1 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F9 BSGDM200F9 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH4 BSGDM200PZ2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH2 BSGDM200PH4 BSGDM200PZ4 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDV100S4 BSGDV100S4 BSGDV10S4 BSGDV10S55 BSGDV150PH1	52 51 51 51 51	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 121 122 122 122 122 124 124 123 124 123 143 122 142 138	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ8ABP GAJ8SG GAJ8SGAP GAJ10A GAJ10AP	125 136 151 137 148 125 42 42 42 43 43 43 43 43 42 43 42
BSGDM100TX27 BSGDM100TX30 BSGDM100TX40 BSGDM150F3 BSGDM150F5 BSGDM150F6 BSGDM150F8 BSGDM150PH0 BSGDM150PH2 BSGDM150PH2 BSGDM150PH2 BSGDM150PZ2 BSGDM150PZ2 BSGDM150PZ3 BSGDM200F5 BSGDM200F6 BSGDM200F9 BSGDM200PH4 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDM250PH2 BSGDV100S4 BSGDV100S4 BSGDV10S5	52 51 51 51 51	DBBP21	104 104 104 128 136 121 121 121 121 121 121 121 121 121 121 121 122 122 122 122 124 124 123 124 123 124 123 143 122 142 138 138	FXLBP6 FXLBP10 G GA225 GA395 GA472 GA541 GA599A GA3200 GAJ4A GAJ4AP GAJ6A GAJ6AP GAJ6SG GAJ6SGAP GAJ8SG GAJ8SGAP GAJ10A GAJ10AP	125 136 151 137 148 125 42 42 42 43 43 43 43 42 42 43 43 42 43 42



GAJS30AP	42	KRBC2TC	3	PK23A	111
GAM541	137	KRBC2TCPCM	3	PK50A	111
GDCT16		KRBC3TD	3	PK52A	111
GLASS30BK		KRBC3TDPCM			111
GLASS30R		KRBC7TD			111
GLASS31BK		KRBC7TDPCM			111
GLASS31R	125	KRBC10TB			111
GLOVE103LA	124	KRBC10TBPCM	3	PKB53A	111
GLOVE103LAB	124	KRBC15T	4	PKB500A	111
GLOVE103MA		KRBC15TPCM			111
GLOVE103MAB		KRBC15TPCMTC			111
GLOVE103XLA		KRBCSST			120
GLOVE103XLAB		KRBCSSTPCM			103
GLOVE400L	124	KRU24B	5		69
GLOVE400M	124	KRW48C	4	PR7-1	69
GLOVE400S	124	KRW182B	5		69
GLOVE400XL		KRW183C			69
GLOVE400XXL	124	KRW184B	5		58
					58
н		L			58
				PR50A	58
HBR15	110	LBUK1	113		58
HBR25		LDT8			58
HCP3KT		LDT14			69
HD4SG		LOS145A			69
HDSCISSORS	113	LSR1000A	149	PR53-3	69
HP2	127			PR54	69
HP301C		М			69
HP650					
		MACMOENICI I	125		
HP650M		MAGWRENCH			58
HRC1300380		MCAL6A			58
HRC1401340	129	MCAL12A	120		58
HRC1502170	129	MIC1B	121	PRH502A	58
HRC1502171	129	MIC1MB	121	PRH503	58
HRC1502172		MIC2B			133
					133
HRC1502173		MIC2MB			
HRC1502174		MIC3B			133
HRC1600840		MIC3MB	121	PSLR4-3	133
HRC1600850	129	MIC4B	121	PSLR4-4	133
HRC1600860		MIC4MB	121	PSI R4-5	133
HRC1600870		MIC5B			133
HRC1600880		MIC5MB			133
HRC1600890		MIC103B			126
HRC1800710	129	MIC103MB	121	PT5CBL	126
HRC4300557	129	MICB1B	121	PWC6	133
HRC4301650		MICB2B	121	PWC12A	133
HRC4304482		MICB3B			133
HRC9000160		MICB4B			134
HRC9004484		MICB5B			133
HRC9004486	129	MICB103B	121	PWC28A	133
HRC9100614	129	MICED1B	121	PWC34	134
		MICINSIDE12	121	PWC60	147
		MIGCARTA			136
•		ML6000COMBO		1 WCOOA	130
1514104					Q
JCW8A		MRB5A			<u> </u>
JT13B	104	MRB10A	134		
		MRB12A	134	QJD8A-72	73
K		MRB15A	134	OJD12A	73
**		MSC1			73
VDD17	4			-	
KRB17		MSC2			73
KRB24		MT454C			73
KRB2006KPQP	2	MT501C		QJOM8A	73
KRB2006KPQR	2	MT574C	139	QJOM9A	73
KRB2055KPQP		MTPV1000			73
KRB2055KPQR					73
		N			73
KRB13005KPRB		N N			
KRB13005KPRR				-	73
KRB13006KPRB	2	NOZZLE360A	127	QJOM14A	73
KRB13006KPRR	2			QJOM15A	73
KRB13007KPRB	3	Р		QJOM16A	73
KRB13007KPRR					73
KRB13008KPRB		PBFG415	124		73
				-	
KRB13008KPRR	2	PHT5	126	QJUM19A	73











0.1014044		0.000		11070	
QJOM21A		RC980	154	UPT35	127
QJOM22A	73	RM130	154	UPT50A	127
QJOM23A		RTEMPB3A	141	UPT65	12/
QJOM24A	73	RULER12BSQ	120	US710	111
QJOM25A				US711	111
QJOM26A	73	5		US712	111
OJOM27A	73			USS103	111
		CDTOC	4.50	033103	
QXD16A		SBT26	153	W.	
QXD24A	73	SDM11KT	135	V	
QXD32A		SDM32KT			
QXOM18A	73	SKRSST4107	7	VAC201	150
QXOM19A		SKRWT4008	7	VGP12406	60
QXOM20A		SKRWT4800B	7	VGP12412	68
QXOM21A	73	SNP2A	112	VGP12418	68
QXOM22A		SQUAREB12	120	VGP12424	
QXOM23A	73	SQUAREB45	120	VGP12509	68
QXOM24A	73	SQUAREB90	120	VGP12808	60
QXOM26A		SQUAREB180	120	VGP18110	68
QXOM29A	73	SQUARECOMB12	120	VGP22406	68
		_			
QXOM30A		SVT275		VGP22412	
QXOM32A	73	SVTAB1400	146	VGP22418	68
QXOM34A		SXLBP3		VGP22424	68
QXOM36A		SXLBP6		VT1A	148
QYD12A	73	SXLBP10	35	VT14	148
QYD16A					
		-		W	
QYOM14A	73			W	
QYOM15A	73				
		T10	42	WE200A	120
QYOM16A		T10			
QYOM17A	73	T15	42	WE200A1	129
QYOM18A	72	T20	42	WE200A2	120
QYOM19A	73	T25	42	WT1001-6	67
QYOM20A	73	T27	42	WT1001-8	67
QYOM21A		T30		WT1003-6	
QYOM22A	73	T40	42	WT1014-6	67
QYOM23A		T45	42	WT1014-7	67
QYOM24A		T50	42	WT1014-8	
QYOM25A	73	TBS200A	136	WT1017C-6	67
QYOM27A	73	TC28B1	115	WT5403-8	67
QYOM27A QYOM29A	73 73		115		67
QYOM27A QYOM29A	73 73	TC28B1	115 115	WT5403-8	67 67
QYOM27A QYOM29A QYOM30A	73 73 73	TC28B1 TC28C TC123C	115 115 115	WT5403-8 WT5414-9	67 67
QYOM27A QYOM29A QYOM30A QYOM32A	73 73 73 73	TC28B1TC28CTC123CTC123C1		WT5403-8 WT5414-9	67 67
QYOM27A	73 73 73 73	TC28B1		WT5403-8 WT5414-9	67 67
QYOM27A	73 73 73 73	TC28B1		WT5403-8 WT5414-9	67 67
QYOM27A	73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10	67
QYOM27A	73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y	67 67 67 161
QYOM27A	73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10	67 67 67 161
QYOM27A	73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8	
QYOM27A	73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73 73 73 73 73 73 73 73 73 73 73 73 73 73 73 73 73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA261A YA263A YA328A YA427B YA444B YA444B1	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA278 YA427B YA444B YA444B1 YA4481	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA278 YA427B YA444B YA444B1 YA481 YA482	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA278 YA427B YA444B YA444B1 YA4481	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA278 YA427B YA444B YA444B1 YA4481 YA482 YA483	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B1 YA481 YA482 YA483 YA484	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B YA4481 YA481 YA482 YA483 YA484 YA486	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B1 YA481 YA482 YA483 YA484	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA486 YA512	
QYOM27A	73 73	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA427B YA444B YA444B YA444B YA444B YA444B YA4481 YA486 YA512 YA580A	
QYOM27A	73 74 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B YA4481 YA486 YA512 YA580A YA580A-1	
QYOM27A	73 74 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B YA4481 YA486 YA512 YA580A YA580A-1	
QYOM27A	73 74 74 42 42 42 47 47	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B YA4481 YA481 YA482 YA483 YA484 YA486 YA512 YA580A YA580A-1 YA581A	
QYOM27A	73 42 42 42 42 42 47 47	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA484 YA486 YA580A YA580A YA580A YA580A YA581A	
QYOM27A	73 42 42 42 42 42 47 47	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA486 YA512 YA580A YA580A YA580A-1 YA581A YA581A YA581A	
QYOM27A	73 74 74 42	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA486 YA512 YA580A YA580A YA580A-1 YA581A YA581A YA581A	
QYOM27A	73 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA484 YA486 YA512 YA580A YA580A YA580A YA581A YA581A YA581A-1 YA714D YA728A	
QYOM27A	73 42 42 42 42 47 47 47 47 42 42 42 42 42 42 42 42 42 42 42 42	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA484 YA486 YA512 YA580A YA580A YA580A-1 YA581A YA734A	
QYOM27A	73 42 42 42 42 47 47 47 47 42 42 42 42 42 42 42 42 42 42 42 42	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA481 YA482 YA483 YA484 YA486 YA512 YA580A YA580A YA580A YA581A YA581A YA581A-1 YA714D YA728A	
QYOM27A	73 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA4481 YA482 YA483 YA486 YA512 YA580A YA580A YA580A-1 YA581A YA745A	
QYOM27A	73 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B YA4481 YA482 YA483 YA486 YA512 YA580A YA580A YA580A-1 YA581A YA734A YA734A YA745A YA750	
QYOM27A	73 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA263A YA263A YA427B YA444B YA444B YA444B YA4481 YA482 YA483 YA484 YA486 YA512 YA580A YA580A-1 YA581A-1 YA714D YA728A YA745A YA750 YA751	
QYOM27A	73 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA262A YA263A YA328A YA427B YA444B YA444B YA444B YA4481 YA482 YA483 YA486 YA512 YA580A YA580A YA580A-1 YA581A YA734A YA734A YA745A YA750	
QYOM27A	73 7	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA263A YA263A YA427B YA444B YA444B YA444B YA4481 YA482 YA483 YA486 YA512 YA580A YA580A-1 YA581A-1 YA714D YA728A YA734A YA745A YA750 YA751 YA751 YA751	
QYOM27A	73 42 42 42 42 42 42 42 47 4	TC28B1		WT5403-8 WT5414-9 WT8627-10 Y YA12AP YA52PBSQC YA109C YA160A YA261A YA263A YA263A YA427B YA444B YA444B YA444B YA4481 YA482 YA483 YA484 YA486 YA512 YA580A YA580A-1 YA581A-1 YA714D YA728A YA745A YA750 YA751	



YA824ASTR	138
YA824C	138
YA874BP	160
YA879A	110
YA900	110
YA1050B	104
YA1055B	135
YA1228	161
YA1544A	137
YA1707	160
YA1715	160
YA2440	136
YA2612B	142
YA3000C	149
YA3100	149
YA3202	138
YA3500	149
YA4000B	156
YA4274	150
YA4275	151
YA4280	125
YA4282	125
YA4603	128
YA5100B	122
YA6160	147
YA6910	141
YA7500	152
YA8005	138
YA8230	154
YA8610B	155
YA9329A	136
YA9350B	153
YA76462	141
YA76562	141
YA105020	135
YAS203A	102
YB2AP	161
YB3AP	161
YB5AP	161
YF2AP	160
YF3AP	160







Showing Millimeter Sizes, Fractional and Decimal Inch Sizes, and Drill Number Sizes

Note: To convert from inches to millimeters, multiply by 25.4; to convert from millimeters to inches, multiply by 0.03937

М	DE	F	DN	М	DE	F	DN	М	DE	F	DN	М	DE	F	DN	М	DE	F	М	DE	F
0.10	0.0039	_	_	1.85	0.0728	_	_	_	0.1660	_	19	7.25	0.2854	_	_	13.49	0.5313	17/32	35.00	1.3780	_
0.15	0.0059	_	_	_	0.0730	_	49	4.25	0.1673	_	_	7.30	0.2874	_	_	13.50	0.5315	_	36.00	1.4173	_
0.20	0.0079	_	_	1.90	0.0748	_	-	4.30	0.1693	_	_	_	0.2900	_	L	13.89	0.5469	35/64	36.51	1.4375	1 7/16
0.25	0.0098		_	1.95	0.0760		48	4.37	0.1695 0.1719	11/64	18	7.40	0.2913	_	— М	14.00 14.29	0.5512	9/16	37.00 38.00	1.4567 1.4961	_
_	0.0135	_	80	1.98	0.0781	5/64	_	-	0.1730	-	17	7.50	0.2953	_	_	14.50	0.5709	_	38.10	1.5000	1 1/2
0.35	0.0138	_	_	_	0.0785	_	47	4.40	0.1732	_	_	7.54	0.2969	19/64	_	14.68	0.5781	37/64	39.00	1.5354	_
_	0.0145	_	79	2.00	0.0787	_	_	_	0.1770	_	16	7.60	0.2992	_	_	15.00	0.5906	_	39.69	1.5625	1 9/16
0.40	0.0156	1/64	_	2.05	0.0807		-	4.50	0.1772	_		7.70	0.3020	_	N	15.08	0.5938	19/32	40.00	1.5748	_
0.40	0.0157 0.0160		78		0.0810		46 45	4.60	0.1800	_	15	7.70 7.75	0.3031	_		15.48 15.50	0.6094	39/64	41.00	1.6142	15/8
0.45	0.0177	_	_	2.10	0.0827	_	_	_	0.1820	_	14	7.80	0.3071	_	_	15.88	0.6250	5/8	42.00	1.6535	-
_	0.0180	_	77	2.15	0.0846	_	_	4.70	0.1850	_	13	7.90	0.3110	_	_	16.00	0.6299	_	42.86	1.6875	1 11/16
0.50	0.0197	_	_	_	0.0860	_	44	4.75	0.1870	_	_	7.94	0.3125	5/16	_	16.27	0.6406	41/64	43.00	1.6929	_
	0.0200	_	76 75	2.20	0.0866		_	4.76 4.80	0.1875 0.1890	3/16	12	7.80	0.3150	_	0	16.50 16.67	0.6496	21/32	44.00 44.45	1.7323 1.7500	13/4
0.55	0.0210		- /s		0.0890		43		0.1910		11	8.10	0.3189		_	17.00	0.6693		45.00	1.7717	-
_	0.0225	_	74	2.30	0.0906	_	_	4.90	0.1929	_	_	8.20	0.3228	_	_	17.07	0.6719	43/64	46.00	1.8110	_
0.60	0.0236		_	2.35	0.0925	_	_	_	0.1935	_	10		0.3230	_	Р	17.46	0.6875	11/16	46.04	1.8125	1 13/16
_	0.0240	_	73	-	0.0935	-	42	-	0.1960	_	9	8.25	0.3248	_	_	17.50	0.6890	-	47.00	1.8504	- 170
0.65	0.0250	_	72	2.38	0.0938	3/32	_	5.00	0.1969	_	8	8.30 8.33	0.3268	21/64	_	17.86 18.00	0.7031	45/64	47.63 48.00	1.8750 1.8898	17/8
-	0.0260		71		0.0960		41	5.10	0.2008		_	8.40	0.3307	_		18.26	0.7188	23/32	49.00	1.9291	_
0.70	0.0276	_	_	2.45	0.0965	_	_	_	0.2010	_	7	_	0.3320	_	Q	18.50	0.7283	_	49.21	1.9375	1 15/16
_	0.0280		70	_	0.0980		40	5.16	0.2031	13/64		8.50	0.3346	_	_	18.65	0.7344	47/64	50.00	1.9685	_
_	0.0292	_	69	2.50	0.0984	_	-	_	0.2040	_	6	8.60	0.3386	_	_	19.00	0.7480	_	50.80	2.0000	2
0.75	0.0295	_	68	_	0.0995	_	39 38	5.20	0.2047	_	 5	8.70	0.3390	_	R —	19.05 19.45	0.7500 0.7656	3/4 49/64	51.00 52.00	2.0079	_
0.79	0.0313	1/32	_	2.60	0.1013		_	5.25	0.2053			8.73	0.3438	11/32		19.50	0.7677	— —	52.39	2.0625	21/16
0.80	0.0315	_	_	_	0.1040	_	37	5.30	0.2087	_	_	8.75	0.3445	_	_	19.84	0.7813	25/32	53.00	2.086	_
_	0.0320	_	67	2.70	0.1063	_	_	_	0.2090	_	4	8.80	0.3465	_	_	20.00	0.7874	_	53.98	2.1250	2 1/8
_	0.0330	_	66	_	0.1065	_	36	5.40	0.2126	_	_	-	0.3480	_	S	20.24	0.7969	51/64	54.00	2.1260	_
0.85	0.0335	_	65	2.75	0.1083	7/64	_	5.50	0.2130 0.2165	_	3	8.90 9.00	0.3504	_	_	20.50	0.8071	13/16	55.00 55.56	2.1654 2.1875	23/16
0.90	0.0354		-		0.1100		35	5.56	0.2103	7/32		<i>-</i>	0.3580		Т	21.00	0.8268	-	56.00	2.2047	
_	0.0360	_	64	2.80	0.1102	_	_	5.60	0.2205	_	_	9.10	0.3583	_	_	21.03	0.8281	53/64	57.00	2.2441	_
_	0.0370		63	_	0.1110		34	_	0.2210	_	2	9.13	0.3594	23/64	_	21.43	0.8438	27/32	57.15	2.2500	2 1/4
0.95	0.0374	_	-	-	0.1130	_	33	5.70	0.2244	_	_	9.20	0.3622	_	_	21.50	0.8465	-	58.00	2.2835	-
_	0.0380	_	62 61	2.90	0.1142		32	5.75	0.2264	_	1	9.25 9.30	0.3641	_	_	21.83	0.8594	55/64	58.74 59.00	2.3125	25/16
1.00	0.0394	_	_	3.00	0.1181	_	31	5.80	0.2283	_		_	0.3680	_	U	22.23	0.8750	7/8	60.00	2.3622	_
_	0.0400	_	60	_	0.1200	_	_	5.90	0.2323	_	_	9.40	0.3701	_	_	22.50	0.8858	_	60.33	2.3750	23/8
	0.0410		59	3.10	0.1220		_	_	0.2340	_	Α	9.50	0.3740	_	_	22.62	0.8906	57/64	61.00	2.4016	
1.05	0.0413	_	-	3.18	0.1250	1/8	_	5.95	0.2344	15/64		9.53	0.3750	3/8		23.00	0.9055	-	61.91	2.4375	27/16
_	0.0420	_	58 57	3.20 3.25	0.1260 0.1280		30	6.00	0.2362	_	В	9.60	0.3770	_	V —	23.02	0.9063	29/32 59/64	62.00	2.4409	_
1.10	0.0433	_	_	_	0.1285	_	_	6.10	0.2402	_	_	9.70	0.3819	_	_	23.50	0.9252	_	63.50	2.5000	2 1/2
1.15	0.0453	_	_	3.30	0.1299	-	_	_	0.2420	_	C	9.75	0.3838	_	_	23.81	0.9375	15/16	64.00	2.5197	_
_	0.0465	_	56	3.40	0.1339	_	_	6.20	0.2441	_	_	9.80	0.3858	_	_	24.00	0.9449	_	65.00	2.5591	_
1.19	0.0469	3/64	_	250	0.1360		29	6.25	0.2460	_	D	<u> </u>	0.3860	_	W	24.21	0.9531	61/64	65.09	2.5625	29/16
1.20	0.0472		_	3.50	0.1378 0.1405		28	6.30	0.2480	1/4	 E	9.90 9.92	0.3898	5/64	_	24.50 24.61	0.9646	31/32	66.68	2.5984	25/8
1.30	0.0492			3.57	0.1406	9/64	_	6.40	0.2520	—	_	10.00	0.3937	—		25.00	0.9843	—	67.00	2.6378	_
_	0.0520	_	55	3.60	0.1417	_	_	6.50	0.2559	_	_	_	0.3970	_	Х	25.00	0.9844	63/64	68.00	2.6772	_
1.35	0.0531		_	_	0.1440		27	_	0.2570	_	F	_	0.4040	_	Υ	25.40	1.0000	1	68.26	2.6875	211/16
1.40	0.0550		54	3.70	0.1457	_	-	6.60	0.2598	_	_	10.32	0.4063	3/32		26.00	1.0236	11/16	69.00	2.7165	- 22/4
1.40	0.0551	_	_	3.75	0.1470 0.1476	_	26 —	6.70	0.2610	_	G —	10.50	0.4130	_	Z —	26.99 27.00	1.0625	1 1/16	69.85 70.00	2.7500	23/4
1.50	0.0571		_	- -	0.1470		25	6.75	0.2656	17/64		10.72	0.4134	27/64		28.00	1.1024	_	71.00	2.7953	_
_	0.0595	_	53	3.80	0.1496	_	_	6.75	0.2657	_	_	11.00	0.4331	_	_	28.58	1.1250	1 1/8	71.44	2.8125	213/16
1.55	0.0610	_	_	_	0.1520	_	24	_	0.2660	_	Н	11.11	0.4375	7/16	_	29.00	1.1417	_	72.00	2.8346	_
1.59	0.0625	1/16	_	3.90	0.1535	_		6.80	0.2677	_	_	11.50	0.4528		_	30.00	1.1811	1 2/16	73.00	2.8740	— 27/9
1.60	0.0630	_	 52	3.97	0.1540 0.1563	5/32	23	6.90	0.2717	_		11.51 11.91	0.4531	29/64 15/32	_	30.16 31.00	1.1875	13/16	73.03 74.00	2.8750 2.9134	27/8
1.65	0.0650		- J2	- -	0.1503	3/32 —	22	7.00	0.2720	_		12.00	0.4000	15/32	_	31.75	1.2500	1 1/4	74.61	2.9134	2 15/16
1.70	0.0669	_	_	4.00	0.1575	_	_	-	0.2770	_	J	12.30	0.4844	31/64	_	32.00	1.2598	_	75.00	2.9528	-
_	0.0670	_	51	_	0.1590	_	21	7.10	0.2795	_	_	12.50	0.4921	_	_	33.00	1.2992	_	76.00	2.9921	_
1.75	0.0689	_	-	-	0.1610	_	20	_	0.2810	-	K	12.70	0.5000	1/2	_	33.34	1.3125	1 5/16	76.20	3.0000	3
1.90	0.0700		50	4.10	0.1614		_	7.14	0.2813	9/32		13.00	0.5118	22/6/	_	34.00	1.3386	1 2/9			
1.80	0.0709		_	4.20	0.1654		_	7.20	0.2835	_	_	13.10	0.5156	33/64	_	34.93	1.3750	1 3/8			

 $M = Millimeters, \, DE = Decimal \, Equivalents, \, F = Fractional, \, DN = Drill \, Number/Letter$

Blue-Point, No Compromise!



